
Finishing Products & Accessories

VENEER CORNER BEAD (MINI BEAD 800/900)



USE: Galvanized steel, used with one-coat or two-coat veneer systems to provide 3/32" grounds. With 1-1/4" fine mesh flanges, either stapled or nailed, provides an effective plaster key and eliminates shadowing

STOCK LENGTHS:

PACKAGING:

i				Carton Quantity				
Si	ze	Length		No.	Weight		Length	
in.	(mm)	ft.	(mm)	Pcs.	lbs.	(kg)	ft.	(m)
1-1/4	(31.8)	8	(2440)	60	40	(18.1)	480	(146.3)
i		10	(3050)	60	50	(22.1)	600	(182.9)
	in.		in. (mm) ft. 1-1/4 (31.8) 8	in. (mm) ft. (mm) 1-1/4 (31.8) 8 (2440)	in. (mm) ft. (mm) Pcs. 1-1/4 (31.8) 8 (2440) 60	Size Length No. We list in. (mm) ft. (mm) Pcs. lbs. 1-1/4 (31.8) 8 (2440) 60 40	Size Length No. Weight in. (mm) ft. (mm) Pcs. lbs. (kg) 1-1/4 (31.8) 8 (2440) 60 40 (18.1)	Size Length No. Weight Le in. (mm) ft. (mm) Pcs. lbs. (kg) ft. 1-1/4 (31.8) 8 (2440) 60 40 (18.1) 480

Length (m) (152.5)(152.5)

VENEER L TRIM



USE: As a veneer plaster stop and as an exposed trim around windows and doors. It is also used in conjunction with veneer corner bead.

						Car	ton Quar	ntity
	s	ize	Le	ngth	No.	We	ight	
Product	in.	(mm)	ft.	(mm)	Pcs.	lbs.	(kg)	ft.
Veneer	1/2	(12.7)	10	(3050)	50	41	(18.6)	50
L Trim	5/8	(15.9)	10	(3050)	50	44	(20.0)	50

K-RITE CORNER BEAD



USE: A veneer bead used as an alternate to mini mesh veneer bead. It has a 1-1/2" leg and triangle cut-outs for one or two coat veneer plaster application. K-Rite corner bead is compatible with all brands of one and two coat plaster systems or multi-layer drywall construction. Perfect choice for repairs, column construction and new construction.


STOCK LENGTHS:

10 Ft.

PACKAGING:


& 5/8"

60 pieces per carton




					Carton Quantity					
	Si	ze	Length		No.	Weight		Length		
Product	in.	(mm)	ft.	(mm)	Pcs.	lbs.	(kg)	ft.	(m)	
K-Rite	1-1/2	(38.1)	8	(2440)	60	58.1	(26.3)	480	(146)	
Corner Bead			9	(2730)	60	65.3	(29.6)	600	(165)	
			10	(3050)	60	72.6	(32.9)	600	(183)	
			12	(3657)	60	87.1	(39.5)	600	(219)	

#66 EXPANDED FLANGE CASING BEAD



USE: As a plaster stop and as exposed trim around window and door openings. Can also be used at the junction or the intersection of plaster and other wall or ceiling finishes. Zinc should be used for exterior applications. Available with weep holes.



	Dep	th or			Carton Quantity				
Product	Grounds		Length		No.	Weight		Length	
	in.	(mm)	ft.	(m)	Pcs.	lbs.	(kg)	ft.	(m)
#66 Expanded Flange	3/8	(9.5)	10	(3.05)	30	48	(21.8)	300	(91.4)
Casing Bead,	1/2	(12.7)	10	(3.05)	30	55	(24.9)	300	(91.4)
Galvanized	5/8	(15.9)	10	(3.05)	30	56	(25.5)	300	(91.4)
	3/4	(19.1)	10	(3.05)	30	58	(26.4)	300	(91.4)
	7/8	(22.2)	10	(3.05)	30	62	(28.2)	300	(91.4)
	1	(25)	10	(3.05)	30	65	(29.9)	300	(91.4)
	1-1/4	(31.8)	10	(3.05)	30	68	(31.0)	300	(91.4)
	1-1/2	(38.1)	10	(3.05)	30	72	(32.7)	300	(91.4)
#66 Expanded Flange	1/2	(12.7)	10	(3.05)	30	51	(23.2)	300	(91.4)
Casing Bead, Zinc	7/8	(22.2)	10	(3.05)	30	59	(26.8)	300	(91.4)