

# Marino\WARE® Product Submittal Data

**PRODUCT NAME:** 400VT200-30

**MARINO\WARE PART #** 400VT230

## PROPERTIES:

<b>A. Web (in)</b>	4	<b>Yield Strength Fy (KSI)</b>	33
<b>B. Leg (in)</b>	2	<b>Design Thickness (in)</b>	0.0312
<b>Mils</b>	30	<b>Minimum Thickness (in)</b>	0.0296
<b>Finish</b>	CP60	<b>Gauge</b>	20 DW

## SECTION PROPERTIES

### GROSS SECTION PROPERTIES

Weight of Member: <b>(lb/ft)</b>	0.850
Cross Sectional Area: <b>A (in<sup>2</sup>)</b>	0.250
Moment of Inertia: <b>Ix (in<sup>4</sup>)</b>	0.698
Section Modulus about the X-axis: <b>Sx (in<sup>3</sup>)</b>	0.336
Radius of Gyration: <b>Rx (in)</b>	1.670
Gross Moment of Inertia: <b>Iy (in<sup>4</sup>)</b>	0.102
Section Modulus about the Y-axis: <b>Sy (in<sup>3</sup>)</b>	0.068
Gross Radius of Gyration: <b>Ry (in)</b>	0.639

### EFFECTIVE SECTION PROPERTIES

Moment of Inertia-Deflection: <b>Ixd (in<sup>4</sup>)</b>	0.502
Section Modulus: <b>Sxe (in<sup>3</sup>)</b>	0.188
Allowable Moment: <b>Ma (in-k)</b>	3.710

### TORSIONAL PROPERTIES

Shear Center to Centroid on Principal X-axis: <b>Xo (in)</b>	-1.230
St. Venant Torsional Constant: <b>Jx10<sup>3</sup> (in<sup>4</sup>)</b>	0.0811
Torsional Warping Constant: <b>Cw (in<sup>6</sup>)</b>	0.306
Radius of Gyration on the Centroid Principal axis: <b>Ro (in)</b>	2.170
Torsional Flexural Constant: <b>β=1-(xo/Ro)<sup>2</sup></b>	0.680

## CODES & STANDARDS


- Meets IBC 2015, 2018 & FBC 2017
- Meets or tested to: ASTM C 645, C 754, E 90, E 119 & AISI S220
- Steel sheet meets ASTM A 1003 & A 653
- Third Party Code Evaluation Report: CCRR-0154
- Multiple Fire Rated Assemblies

## GREEN INFO

- LEED v3 & LEED v4 credits available
- Contact Technical Services for more information



09.22.16 Non-Structural Metal Stud



www.marinoware.com

For more information, please contact Marino\WARE Technical Services at 866-545-1545

This technical information reflects the most current information available and supersedes any and all publications, effective 11/30/19.

©Copyright 2019 by Ware Industries, Inc. All rights reserved