



202 Harger St. | PO Box 250 | Dover, OH 44662
330.343.6621 | Fax: 330.343.7269
www.marlite.com | info@marlite.com

RE: LEED Information for Marlite Brand Sealants

MS-250 Clear / MS-251 White Silicon Sealant – The current VOC content for this product is 49 g/L. Accordingly, the VOC content of Marlite MS-250 Clear / MS-251 White Silicon Sealant is less than the current VOC content limits of California's South Coast Air Quality Management District (SCAQMD) Rule #1168. This product is eligible for the U.S. Green Building Council LEED NC Green Building Rating System for New Construction & major Renovations v2.2 EQ credit 4.1. This statement is based on the Marlite Brand Sealant referenced above and the formulation of the product and the regulations in place according to the date of this letter. For the use of this product, you could be contributing up to one point under the Indoor Environmental Quality Version 2.2 Rating System.

Titebond Weathermaster Sealants (Various Colors) – The current VOC content for this product is 9 g/L. Accordingly, the VOC content of Titebond Weathermaster Sealants is less than the current VOC content limits of California's South Coast Air Quality Management District (SCAQMD) Rule #1168. This product is eligible for the U.S. Green Building Council LEED NC Green Building Rating System for New Construction & major Renovations v2.2 EQ credit 4.1. This statement is based on the Marlite Brand Sealant referenced above and the formulation of the product and the regulations in place according to the date of this letter. For the use of this product, you could be contributing up to one point under the Indoor Environmental Quality Version 2.2 Rating System.

All adhesive MSDS are available upon request.