Marlite Plank Section 09770

### Part 1: General

## 1.01 Section Includes:

A. Decorative pre-finished interior wall panels.

## 1.02 Submittals:

A. Provide manufacturer's product data sheets for approval.

# 1.03 Delivery, Storage and Handling of Materials:

- A. All products are to be factory packaged in heavy cardboard cartons.
- B. All products are to be stored flat in a cool, dry place.

Do not stack panels directly on the floor.

Do not subject panels to moisture.

## 1.04 Warranty:

A. All products shall be warranted to be free of defects for a period of 30 days from the date of delivery.

### Part 2: Products

### 2.01 Manufacturer:

A. Decorative pre-finished interior wall panels shall be as manufactured by Marlite, 202 Harger Street, Dover, OH 44622, (330) 343-6621.

#### 2.02 Materials:

- A. All decorative pre-finished wall panels shall be Marlite Plank (product # and name).
  - 1. Marlite Finish:

Federal Specification LLL-B-805 Class I Finish

A.B.P.A. PS 59-73

Meets ANSI and AHA Standards for pre-finishing paneling

2. Wood Veneer:

AWI Finish System TR-4 Custom grade finish

## 2.03 Accessories:

- A. All molding and trim shall be pre-finished at the factory. (Specifier to select molding/trim product # and name and finish).
- B. Adhesive
  - 1. C-375 Marlite Construction Adhesive as required. Meets ASTM Specification C557
- C. Silicone Sealant
- 1. MS250 Clear or MS251 Marlite Silicone Sealant as required.

### Part 3: Execution

# 3.01 Preparation:

A. Marlite Plank must be installed over a smooth, solid, flat subwall such as drywall or plywood.

# 3.02 Conditioning:

A. Cartons should be opened and allowed to acclimate to the room conditions for at least 48 hours prior to installation.

# 3.03 Installation:

A. Marlite Plank is to be installed in strict accordance with manufacturer's written instructions.

Fire Rated Test Results (ASTM E-84)

Marlite Finish Plank

Flame spread <200

Class C

Smoke development <450

Marlite Wood Veneer Plank

Flame spread <25

Class A Marlite Finish Firetest Plank

Smoke development <450