

# Celtec MSDS Sheets

Celtec PVCI-II  
(Foamed PVC Sheets)

## I. Product Identification

Manufacturing Site: Vycom Corp

Address: 801 Corey Street, Moosic, PA 18507

Trade Name: Polyvinyl Chloride (PVC, Vintec I, Vintec II, Celtec) sheet (Foamed PVC Sheets)

Synonyms: Vinyl Polymers

CAS Number(s): 9002-86-2

Telephone Number: 570.346.8254

Fax Number: 570.346.4122

Website: www.cpg-vycom.com

## II. Components and Hazard Classification

PVC Polymer: 70-95%

Inert Fillers: 0-30% CaCO<sub>3</sub>, TiO<sub>2</sub>

Heat Stabilizer: 0-2% Organotin Compounds

Lubricants: 0-4% Calcium Stearate; Paraffin, Polyethylene, Polyamide

Compounds or Esters

Process Aids: 0-2% Acrylic Compounds

Impact Modifiers: 0-10% CPE, ABS, MBS or Acrylic Compounds

Colorants: 0-2% Organic and Inorganic Colorants

Chemical Blowing Agents: 0-1% Azo Compounds or Sodium Bicarbonate

This product is an article as defined in 29 CFR 1910.1200. It will not result in exposure to hazardous chemicals under normal conditions of use. This product is not subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

## III. Physical Data

Boiling Point (oF): Solid

Specific Gravity (H<sub>2</sub>O=1): 0.45 – 1.4

Vapor Pressure (mm Hg.): Solid

Melting Point: Decomposes before melting

Solubility in Water: Solid

Vapor Density: Solid

Appearance and Odor: Finished sheet

## IV. Fire and Explosion Data

Flash Point (Test Method): Not applicable

Autoignition Temperature: Not applicable

Flammable Limits in Air (% by Volume):

Lower: Not applicable

Upper: Not applicable

Extinguishing Media: Water spraying (fog), foam, dry chemical or CO<sub>2</sub>

Special Fire Fighting Procedures: Cool exposed equipment with water spray. Use self-contained breathing apparatus if fighting fire in confined spaces.

Unusual Fire and Explosion Hazard: PVC evolves hydrogen chloride, carbon monoxide and other toxic gases when burned. Exposure to combustion products may be fatal and should be avoided.

## V. Health Hazard Information

Pertains to dust or chips as a by-product of fabricating finished sheet.

#### First Aid

Eyes: Immediately flush with plenty of water.

Call a physician if irritation persists.

Skin: Flush skin with plenty of water. Remove contaminated clothing.

Call a physician if irritation persists. Wash clothing before reuse.

Inhalation: Remove to fresh air.

Ingestion: Seek medical aid.

#### Nature of Hazard

Eyes: If exposed to high concentrations of dust, physical irritation of the eyes.

Skin: This material is not expected to present a hazard to the intact skin.

Molten sheet will produce thermal burns.

Inhalation: Under normal conditions and with normal use, no inhalation hazard is presented. Please refer to Section VI, Fire and Explosion Data.

Ingestion: No significant health hazard can be reasonably anticipated.

Exposure Limits None established.

ACGIH TLV of 10 mg/m<sup>3</sup> total dust as an 8-hour TWA is recommended.

#### Toxicity Data

Skin Contact: A review of the pertinent literature did not reveal specific information for PVC.

Eye Contact: A review of the pertinent literature did not reveal specific information for PVC.

Inhalation: Rodents exposed by the dietary or inhalation route for 6 to 24 months have shown no significant toxicological effects.

Ingestion: See above.

Special Precautions AVOID INHALATION OF COMBUSTION PRODUCTS.

#### VI. Reactivity Data

Conditions Contributing to Instability: Not applicable

Incompatibility: Not applicable

Hazardous Decomposition Products: Hydrogen chloride and other toxic fumes generated with combustion.

Conditions Contributing to Hazardous

Polymerization:

Not applicable

#### VII. Spill or Leak Procedures

When producing chips or dust from fabricating PVC sheet, sweep, scoop or vacuum and remove. Dispose of only in accordance with local, state and federal regulations.

#### VIII. Special Protection Information

Pertains to dust or chips as a by-product of fabricating finished sheet.

#### Ventilation Recommendations

General ventilation when fabricating and nuisance dust control.

#### Specific Personal Protective Equipment

Respiratory Protection: If dust is produced during handling, an approved particulate filter respirator should be used.

Eyes: Safety glasses or goggles.

Gloves: Necessary when handling hot or molten sheet.

Other Clothing and Equipment: As necessary when handling hot or molten sheet.

#### **IX. Shipping, Transfer and Storage**

##### Shipping Information

Non-hazardous for transportation purposes

##### Transportation and Storage

Usual Shipping Containers: Palletized sheets

Storage Transport Temperature: Temperatures above 150oF may cause slow degradation.

Electrostatic Accumulation Hazard: Yes

The data above is based upon tests performed by and experience of Vycom and/or Vyom's suppliers and is provided for informational purposes only. Vycom's products are intended for sale to industrial and commercial customers. Vycom requests that customers inspect and test products before use to satisfy themselves as to contents and suitability. Vycom disclaims any liability for damage or injury that results from the use of the data above, and nothing contained therein shall constitute a guarantee, warranty (including warranty of merchantability) or representation (including freedom from patent liability) by Vycom with respect to that data, the product described, or its use for any specific purpose, even if that purpose is known to Vycom. Compliance with all applicable federal, state and local laws and regulations remains the responsibility of the user.