
# Submittal Data - Structural Stud

## Member Designator 1150S250-97

Coating G90

#### **Physical Properties**

Design Thickness 0.1017 in Mil 97 mil Gauge 12 Gauge Web Width 11.50 in Flange Width 2.50 in Stiffening Lip 0.625 in Yield Strength 50 ksi



## **Gross Properties**


Area	Weight	lx	Sx	Rx	ly	Ry
(in²)	(lb/ft)	(in <sup>4</sup> )	(in <sup>3</sup> )	(in)	(in <sup>4</sup> )	(in)
1.728	5.88	30.651	5.331	4.211	1.110	

## **Effective Properties**

lx	Sx	Ma	Vag	
(in⁴)	(in <sup>3</sup> )	(in-k)	(lb)	
30.651	5.218	103.10	8515	

## **Torsional Properties**

J <sup>x1000</sup>	Cw	Xo	m	Ro	β
(in <sup>4</sup> )	(in <sup>6</sup> )	(in)	(in)	(in)	
		-1.358			0.909



#### **General Notes**

- 1. Physical properties and load tables have been calculated in conformance with the 2001 NASPEC for the Design of Cold-Formed Steel Structural Members, including the 2004 Supplement, and the IBC 2006, unless noted otherwise.
- 2. All structural framing members have a protective coating conforming to ASTM C 955.
- 3. Reference ASTM specification A 1003/A 1003 M table 1 for the universe of allowable coatings for light gauge steel framing.
- 4. Stud/joists are manufactured to custom lengths. Stud/joists are manufactured with punched webs unless otherwise specified at time of order.
- $5. \quad Track is \ produced in \ standard \ lengths \ of \ 10 \ feet \ unless \ a \ custom \ track \ length \ is \ indicated. \ Track \ is \ manufactured \ with \ unpunched \ webs.$
- 6. Structural framing members are marked with product information per the requirements of ASTM C 955 section 12.
- 7. All delivered material must be kept dry, preferably by being stored inside a building under a roof. If it is necessary to store material outside, it must be stacked off the ground, properly supported on a level platform, and fully protected from the weather. Reference ASTM C 754 section 8 and ASTM C 1007 section 4.

#### **LEED Green Building Credits**

MR Credit 2: Construction Waste Management – MBA steel framing is 100% recyclable.

MR Credit 4: Recycled Content – MBA steel framing is formed from no less than 25.5% post-consumer and 6.8% pre-consumer recycled content. MR Credit 5: Regional Materials – MBA has manufacturing facilities in multiple states.

