Sales: (888)248-8076 Fax: (847)680-7883 www.mbastuds.com

## **Submittal Data – Structural Track**

## **Member Designator**


1200T125-54

Coating

CP60

### **Physical Properties**

Design Thickness 0.0566 in Mil 54 mil Gauge 16 Gauge Inside Web Width 12.00 in Leg Length 1.25 in Yield Strength 33 ksi



# **Gross Properties**

| Gross Properties   |         |                    |                    |       |                    |       |  |  |
|--------------------|---------|--------------------|--------------------|-------|--------------------|-------|--|--|
| Area               | Weight  | lx                 | Sx                 | Rx    | ly                 | Ry    |  |  |
| (in <sup>2</sup> ) | (lb/ft) | (in <sup>4</sup> ) | (in <sup>3</sup> ) | (in)  | (in <sup>4</sup> ) | (in)  |  |  |
| 0.820              | 2.79    | 13.335             | 2.186              | 4.033 | 0.060              | 0.271 |  |  |

#### **Effective Properties**

| Effective Properties (33ksi) |                    |        |      |  |  |  |  |
|------------------------------|--------------------|--------|------|--|--|--|--|
| lxe                          | Sxe                | Ma     | Vag  |  |  |  |  |
| (in⁴)                        | (in <sup>3</sup> ) | (in-k) | (lb) |  |  |  |  |
| 12.296                       | 1.491              | 29.47  | 1354 |  |  |  |  |

## **Torsional Properties**

| Torsional          |                    |        |       |       |       |  |  |  |  |
|--------------------|--------------------|--------|-------|-------|-------|--|--|--|--|
| J <sup>x1000</sup> | Cw                 | Xo     | m     | Ro    | β     |  |  |  |  |
| (in⁴)              | (in <sup>6</sup> ) | (in)   | (in)  | (in)  |       |  |  |  |  |
| 0.876              | 1.820              | -0.333 | 0.230 | 4.055 | 0.993 |  |  |  |  |

#### **General Notes**

- 1. Physical properties and load tables have been calculated in conformance with the 2001 NASPEC for the Design of Cold-Formed Steel Structural Members, including the 2004 Supplement, and the IBC 2006, unless noted otherwise.
- 2. All structural framing members have a protective coating conforming to ASTM C 955.
- 3. Reference ASTM specification A 1003/A 1003 M table 1 for the universe of allowable coatings for light gauge steel framing.
- 4. Stud/joists are manufactured to custom lengths. Stud/joists are manufactured with punched webs unless otherwise specified at time of order.
- 5. Track is produced in standard lengths of 10 feet unless a custom track length is indicated. Track is manufactured with unpunched webs.
- 6. Structural framing members are marked with product information per the requirements of ASTM C 955 section 12.
- 7. All delivered material must be kept dry, preferably by being stored inside a building under a roof. If it is necessary to store material outside, it must be stacked off the ground, properly supported on a level platform, and fully protected from the weather. Reference ASTM C 754 section 8 and ASTM C 1007 section 4.

#### **LEED Green Building Credits**

MR Credit 2: Construction Waste Management – MBA steel framing is 100% recyclable.

MR Credit 4: Recycled Content – MBA steel framing is formed from no less than 25.5% post-consumer and 6.8% pre-consumer recycled content.

MR Credit 5: Regional Materials – MBA has manufacturing facilities in multiple states.

