


Sales: (888)248-8076 Fax: (847)680-7883 www.mbastuds.com

Submittal Data – Structural Track



Gross Properties						
Area	Weight	Ix	Sx	Rx	ly	Ry
(in ²)	(lb/ft)	(in ⁴)	(in ³)	(in)	(in ⁴)	(in)
0.537	1.83	2.578	0.905	2.191	0.199	0.609

Gross Properties

Effective	Properties
-----------	------------

Effective Properties (33ksi)					
lxe Sxe		Ma	Vag		
(in ⁴)	(in ³)	(in-k)	(lb)		
2.253	0.669	13.21	2739		

Torsional Properties

	Torsional						
l,	(1000	Cw	Хо	m	Ro	β	
(in ⁴)	(in ⁶)	(in)	(in)	(in)		
	0.573	1.133	-1.077	0.668	2.517	0.817	

General Notes

- 1. Physical properties and load tables have been calculated in conformance with the 2001 NASPEC for the Design of Cold-Formed Steel Structural Members, including the 2004 Supplement, and the IBC 2006, unless noted otherwise.
- 2. All structural framing members have a protective coating conforming to ASTM C 955.
- 3. Reference ASTM specification A 1003/A 1003 M table 1 for the universe of allowable coatings for light gauge steel framing.
- 4. Stud/joists are manufactured to custom lengths. Stud/joists are manufactured with punched webs unless otherwise specified at time of order.
- 5. Track is produced in standard lengths of 10 feet unless a custom track length is indicated. Track is manufactured with unpunched webs.
- 6. Structural framing members are marked with product information per the requirements of ASTM C 955 section 12.
- 7. All delivered material must be kept dry, preferably by being stored inside a building under a roof. If it is necessary to store material outside, it must be stacked off the ground, properly supported on a level platform, and fully protected from the weather. Reference ASTM C 754 section 8 and ASTM C 1007 section 4.

LEED Green Building Credits

MR Credit 2: Construction Waste Management – MBA steel framing is 100% recyclable.

MR Credit 4: Recycled Content – MBA steel framing is formed from no less than 25.5% post-consumer and 6.8% pre-consumer recycled content. MR Credit 5: Regional Materials – MBA has manufacturing facilities in multiple states.

