Image II[™] Panel Metal Sales Manufacturing Corporation



Architectural Standing Seam Metal Roof Panel

- Choose from MS Colorfast45[®], PVDF or Acrylic Coated Galvalume[®]
- > 26 ga. standard, 24 ga. available at select branches
- Available in a wide variety of colors
- Installs over a solid substrate
- Minimum roof slope 3:12



Metal Sales

800.406.7387 metalsales.us.com

IMAGE II[™] PANEL

Metal Sales

PANEL PROFILES*



*Not all profiles are available at all branches. Fastening leg may vary slightly from what's shown

PANEL INFORMATION

- ▶ 12" and 16" panel coverage
- ▶ Gauges: 26 ga. and 24 ga.
- Minimum roof slope: 3:12
- Concealed fasteners help enhance the beauty of any project

TESTING AND APPROVALS

- ▷ UL 2218 Impact Resistance Class 4
- ▷ UL 790 Fire Resistance Rating Class A, per building code
- ▷ UL 263 Fire Resistance Rating per assembly
- ▷ UL 580 Uplift Resistance Class 90 Construction: #529
- ▷ Texas Windstorm Evaluation RC-162 and RC-399
- ▷ 2023 FBC Approvals FL11560.4 and FL14645.10
- ▷ Miami-Dade County, Florida NOA 23-0711.05 expires 8/8/2028
- ▷ ICC Evaluation Report ESR-2385



GENERAL INFORMATION

▶ Features: Image II panels will not warp, split, crack or curl and are impervious to mildew, rot, termites and pests. Installation over solid substrate is a snap.

▶ Substructure: Image II is designed to be utilized over a solid substrate. To avoid panel distortion, use a properly aligned and uniform substructure.

▶ Length: Minimum factory cut length is 5'-0". Maximum recommended panel length is 30'-0". Longer panels require additional considerations in packaging, shipping and erection. Please consult Metal Sales for recommendations.

▶ Fasteners: The fastener selection guide should be consulted for choosing the proper fastener for specific applications. Quantity and type of fastener must meet necessary loading and code requirements.

▶ Finishes: Acrylic Coated Galvalume[®], MS Colorfast45[®] or various PVDF colors.

For all specific warranty, application, installation and technical information regarding these products, contact your representative.

LOAD TABLE

SECTION PROPERTIES								ALLOWABLE UNIFORM LOADS psf (3 or More Equal Spans)			
Ga.	Width in	Yield ksi	Weight psf	Top In Compression		Bottom In Compression		Outward Load			
				lxx	Sxx in ³ /ft	lxx in ⁴ /ft	Sxx in ³ /ft				
				in ⁴ /ft				0'-6"	1'-0″	1′-6″	2'-0"
26	16	50	0.92	0.0165	0.0174	0.0165	0.0177	103	96	90	84
24	16	50	1.19	0.0210	0.0226	0.0210	0.0226	103	96	90	84

1. Theoretical section properties have been calculated per AISI 2016 'North American Specification for the Design of Cold-Formed Steel Structural Members'. Ixx and Sxx are effective section properties for deflection and bending.

2. Allowable load is calculated in accordance with AISI 2016 specifications considering bending, shear, combined bending & shear and deflection. Allowable load does not address web crippling, fasteners, support material or load testing. Allowable load considers the three or more equal spans condition. Panel weight is not considered.

3. Deflection consideration is limited by a maximum deflection ratio of L/180 of span.

4. Allowable loads do not include a 1/3 stress increase for wind.

Metal Sales Manufacturing Corporation

Anchorage, AK: 866.640.7663 Bay City, MI: 888.777.7640 Deer Lake, PA: 800.544.2577 Denver, CO: 800.289.7663 Detroit Lakes, MN: 888.594.1394 Fontana, CA: 800.782.7953 Fort Smith, AR: 877.452.3915 Independence, MO: 800.747.0012 Jacksonville, FL: 800.394.4419 Jefferson, OH: 800.321.5833 Mocksville, NC: 800.228.6119 Nashville, TN: 800.251.8508 Rock Island, IL: 800.747.1206 Rogers, MN: 800.328.9316 Kelso, WA: 800.431.3470

1013 ©MS(1865) / 2-2024

metalsales.us.com

Sellersburg, IN: 800.999.7777 Sioux Falls, SD: 888.299.0024 Spokane, WA: 800.572.6565 Temple, TX: 800.543.4415 Woodland, CA: 800.759.6019