

APPROXIMATE COVERAGES RATES

NARROW JOINTS AND CRACKS

MM-80, EP-XL, SP 2000, RSF, RS 88

CARTRIDGE CONVERSION

 450 ML Divide Yield by 8
 900 ML Divide Yield by 4
 1500 ML Divide Yield by 2.5

1/8 x 3/4" = 200 lf/gal.	3/16 x 3/4" = 135 lf/gal.	1/4 x 3/4" = 100 lf/gal.
1/8 x 1" = 150 lf/gal.	3/16 x 1" = 100 lf/gal.	1/4 x 1" = 80 lf/gal.
1/8 x 1-1/4" = 125 lf/gal.	3/16 x 1-1/4" = 85 lf/gal.	1/4 x 1-1/4" = 60 lf/gal.
1/8 x 1-1/2" = 100 lf/gal.	3/16 x 1-1/2" = 70 lf/gal.	1/4 x 1-1/2" = 50 lf/gal.
1/8 x 1-3/4" = 85 lf/gal.	3/16 x 1-3/4" = 60 lf/gal.	1/4 x 1-3/4" = 45 lf/gal.
1/8 x 2" = 75 lf/gal.	3/16 x 2" = 50 lf/gal.	1/4 x 2" = 40 lf/gal.

LARGER JOINTS AND CRACKS

MM-80, Edge-Pro XL, SP 2000

CARTRIDGE CONVERSION

 450 ML Divide Yield by 8
 900 ML Divide Yield by 4
 1500 ML Divide Yield by 2.5

3/8 x 3/8" = 135 lf/gal.	3/4 x 1/2" = 50 lf/gal.	1 x 3/4" = 25 lf/gal.
3/8 x 1/2" = 100 lf/gal.	3/4 x 3/4" = 35 lf/gal.	1 x 1" = 20 lf/gal.
1/2 x 1/2" = 80 lf/gal.	1 x 1/2" = 40 lf/gal.	1 x 2" = 10 lf/gal.

MODIFIED EPOXY

MM-80, Edge-Pro XL, Armor-Hard Liquid

LIQUID EPOXY + SILICA SAND = MORTAR YIELD

GAL. EPOXY + GALS. SAND = GALS. MORTAR

1	1	1.6
1	1.5	1.9
1	2	2.2
1	2.5	2.5
1	3	2.8

POP-OUTS, HOLES, GOUGES

MM-80, SP 2000, Armor-Hard Kit

Length x Width x Depth = Cubic Inches

450 ML UNIT = 28.75 cubic inches

900 ML UNIT = 57.5 cubic inches

GALLON UNIT = 230 cubic inches

Armor-Hard Kit = 540 cubic inches

STAIN PREVENTION FILM

SPF Stain Preventing Film

Approx. Lineal Foot Coverage

Width of Film	Coverage/Gal
2"	4200 LF
3"	2800 LF
4"	2100 LF

SHRINKAGE VOIDS, CRACKS

Spal-Pro RS88 1500 ML Cartridge

Approx. Yield for 1500 ML Cartridge For Gallon Units Multiply by 2.5

512 lf	1/16" x 1/4"	256 lf	1/16" x 1/2"
256 lf	1/8" x 1/4"	128 lf	1/8" x 1/2"
192 lf	3/16" x 1/4"	96 lf	3/16" x 1/2"
128 lf	1/4" x 1/4"	64 lf	1/4" x 1/2"

Note: The above figures are approximate and for estimating purposes only. The rates shown do not allow for waste, overfill-and-shave, etc. Results may vary due to porosity of concrete, grade of silica used, etc. Metzger/McGuire assumes no liability for results from using these figures.

FOR DETAILED REPAIR SPECS VISIT OUR WEB SITE OR CALL 800/223-MM80
www.metzgermcguire.com

 Fax: 603/224-6020
 E-Mail: specmm80@aol.com