Safety Data Sheet 10-8510B

121 ASPHALT-SPRAY-PRIMER Safety Data

Sheet dated: 04/16/2020 - version 1 Date of first

edition: 04/16/2020



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: 121 ASPHALT-SPRAY-PRIMER

Recommended use of the chemical and restrictions on use

Recommended use: Bituminous adhesive solvent based

Restrictions on use: N.A.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MULE HIDE PRODUCTS CO. INC.

1195 PRINCE HALL DRIVE, BELOIT, WI, 53511. USA

Phone: 800-786-1492

Responsible: www.mulehide.com

Emergency 24 hour numbers: (USA) CHEMTREC 1-800-424-9300 (Canada) CANUTEC 1-613-996-6666

2. HAZARD(S) IDENTIFICATION





Classification of the chemical

Flam. Aerosol 1 Extremely flammable aerosol.

Compr. Gas Contains gas under pressure; may explode if heated.

Label elements

Pictograms and Signal Words



Danger

Hazard statements:

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Date 6/4/2020 Production Name MH 121 ASPHALT-SPRAY-PRIMER Page n. 1 of 8

Quantity	Name	Ident. Numb.	Classification	Registration Number
25-50 %	DIMETHYL ETHER	CAS:115-10-6	Flam. Gas 1, H220; Compr. Gas, H280	
20-25 %	Petroleum hydrocarbons	CAS:8052-41-3	Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2B, H320; STOT SE 3, H336; Aquatic Acute 2, H401; Aquatic Chronic 2, H411; Asp. Tox. 1, H304	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

N.A.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Date 6/4/2020 Production Name MH 121 ASPHALT-SPRAY-PRIMER Page n. 2 of 8

Storage temperature: N.A.

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term 3 ppm	Short Term mg/m3	Short Term Sppm	Behaviour	Note
DIMETHYL ETHER	EU			1920	1000			Indicative	
	MAK	GERMANY		1900	1000				
	MAK	AUSTRIA		1910	1000	3820	2000		
	MAK	SWITZERLAND		1910	1000				
Petroleum hydrocarbons	OSHA			2900	500				
	ACGIH				100				CNS impairment;eye, kidney and skin damage;nausea;
	ACGIH				100				CNS impairment;eye, kidney and skin damage;nausea

Appropriate engineering controls: N.A. **Individual protection measures**

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

N.A.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid

Appearance and colour: aerosol Black

Odour: hydrocarbons like Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: >116 °C (241 °F)

Flash point: >12,2 °C (54,0 °F)

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A. Vapour pressure: N.A. Relative density: 0.92 g/cm3 Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.

Date 6/4/2020 Production Name MH 121 ASPHALT-SPRAY-PRIMER Page n. 3 of 8

Oxidizing properties: N.A. Solid/gas flammability: N.A.

Other information

Substance Groups relevant properties N.A.

Miscibility: N.A. Fat Solubility: N.A. Conductivity: N.A.

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

DIMETHYL ETHER

a) acute toxicity

LC50 Inhalation Rat = 3085 mg/l 4h

LC50 Inhalation Rat = 164000 ppm 4h

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism and distribution information

- i) STOT-repeated exposure
- j) aspiration hazard

Substance(s) listed on the IARC Monographs:

None

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Date 6/4/2020 Production Name MH 121 ASPHALT-SPRAY-PRIMER Page n. 4 of 8

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Component Ident. Numb. Ecotox Infos

DIMETHYL ETHER CAS: 115-10-6 a) Aquatic acute toxicity: LC50 Fish Poecilia reticulata > 4,1 g/l 96h ECHA

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

14. TRANSPORT INFORMATION

UN number

ADR-UN number: 1950 DOT-UN Number: UN1950 IATA-Un number: 1950 IMDG-Un number: 1950

UN proper shipping name

ADR-Shipping Name: AEROSOLS

DOT-Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)

IATA-Technical name: AEROSOLS, FLAMMABLE IMDG-Technical name: AEROSOLS, FLAMMABLE

Transport hazard class(es)

ADR-Class: 2

DOT-Hazard Class: 2.1 IATA-Class: 2.1

IMDG-Class: 2

Packing group

ADR-Packing Group: -

DOT-Packing group: -

IATA-Packing group: -

IMDG-Packing group: -

Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): N82

DOT-Label(s): 2.1
DOT-Symbol: N/A
DOT-Cargo Aircraft: N/A
DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A
DOT-Non-Bulk: N/A
Road and Rail (ADR-RID) :

Date 6/4/2020 Production Name MH 121 ASPHALT-SPRAY-PRIMER Page n. 5 of 8

ADR-Label: 2.1

ADR-Hazard identification number: -

ADR-Transport category (Tunnel restriction code): 2 (D)

Air (IATA):

IATA-Passenger Aircraft: 203 IATA-Cargo Aircraft: 203

IATA-Label: 2.1

IATA-Subsidiary hazards: -

IATA-Erg: 10L

IATA-Special Provisioning: A145 A167 A802

Sea (IMDG):

IMDG-Stowage Code: SW1 SW22 IMDG-Stowage Note: SG69

IMDG-Subsidiary hazards: See SP63

IMDG-Special Provisioning: 63 190 277 327 344 381 959

IMDG-Page: N/A IMDG-Label: N/A IMDG-EMS: F-D, S-U IMDG-MFAG: N/A

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

DIMETHYL ETHER is listed in TSCA Section 8b Petroleum hydrocarbons is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

DIMETHYL ETHER is listed in CAA Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

No substances listed

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

DIMETHYL ETHER

Petroleum hydrocarbons

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

DIMETHYL ETHER

Petroleum hydrocarbons

Date 6/4/2020 Production Name MH 121 ASPHALT-SPRAY-PRIMER Page n. 6 of 8

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

DIMETHYL ETHER

Petroleum hydrocarbons

Canada - Federal regulations

DSL - Domestic Substances List

DSL Inventory:

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL Inventory:

No substances listed

NPRI - National Pollutant Release Inventory

Substances listed in NPRI:

No substances listed

16. OTHER INFORMATION

Code	Description
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H320	Causes eye irritation.
H336	May cause drowsiness or dizziness.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet dated: 4/16/2020 - version 1

Product code: 6PG100S

Additional classification information





HMIS Health: 1 = Slight

HMIS Health - Is health hazard chronic? No

HMIS Flammability: 4 = Flammable gas or extremely flammable liquid

HMIS Reactivity: 0 = Minimal HMIS P.P.E.: Safety glasses, gloves

NFPA Health: 1 = Slight

NFPA Flammability: 4 = Flammable gas or extremely flammable liquid

NFPA Reactivity: 0 = Minimal NFPA Special Risk: N.A.

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

Date 6/4/2020 Production Name MH 121 ASPHALT-SPRAY-PRIMER Page n. 7 of 8

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

ED30: Lection dose, for 30 percent of test population

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Date 6/4/2020 Production Name MH 121 ASPHALT-SPRAY-PRIMER Page n. 8 of 8