

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

Meets Requirements of OSHA's 29 CFR 1910.1200 (7-1-13 Edition)

SECTION I - Identification

- (a) Product identifier used on the label; MULE-HIDE **PYROXL**
- (b) Other means of identification; Ink stamp on panel
- (c) Recommended use of the chemical and restrictions on use; Fire Retardant (FR) Roof Panel – Used in areas not exposed to the weather or wetting where the code permits the use of wood or fire-retardant-treated wood.
- (d) Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party;

MANUFACTURER	SUPPLIER
Hoover Treated Wood Products, Inc. 154 Wire Road Thomson, Georgia 30824 706-595-5058	MULE-HIDE PRODUCTS CO., INC. 1195 Prince Hall Drive P.O. Box 1057 Beloit, Wisconsin 53512 800-786-1492 www.mulehide.com

- (e) Emergency phone number. 706-595-7355

SECTION II – Hazard(s) Identification

- (a) Classification of the chemical in accordance with paragraph (d) of § 1910.1200;

All classifications have been performed considering sawing, grinding, drilling, sanding or machining of the product has taken place and wood dust, sawdust, and small wood chips are present. Only “**Softwoods**” are used in the production of panels. So data derived from “**Hardwoods**” studies has not been considered.

Acute Toxicity – N/A

Skin Corrosion/Irritation – Irritant, category 2³

Serious Eye Damage/Eye Irritation – Irritant, category 2B

Respiratory or Skin Sensitization:

Respiratory Sensitizer, category 1, sub-category 1B

Skin Sensitizer, category 1, sub-category 1B

Germ Cell Mutagenicity – N/A

Carcinogenicity – Carcinogen, category 2

Reproductive Toxicity – N/A

Specific Target Organ Toxicity Single Exposure – N/A

Specific Target Organ Toxicity Repeated or Prolonged Exposure – N/A

Aspiration Hazard – N/A

Explosives – N/A

Flammable Gases – N/A

Flammable Aerosols – N/A

Oxidizing Gases – N/A

Gases Under Pressure – N/A

Flammable Liquids – N/A

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

Flammable Solids – Readily Combustible Solids, category 2
 Self-Reactive Chemicals – N/A
 Pyrophoric Liquids – N/A
 Pyrophoric Solids – N/A
 Self-Heating Chemicals – N/A
 Chemicals Which, In Contact With Water, Emit Flammable Gases – N/A
 Oxidizing Liquids – N/A
 Oxidizing Solids – N/A
 Organic Peroxides – N/A
 Corrosive to Metals – N/A

N/A = Not Applicable

(b) Signal word, hazard statement(s), symbol(s) and precautionary statement(s) in accordance with paragraph (f) of § 1910.1200. (Hazard symbols may be provided as graphical reproductions in black and white or the name of the symbol, e.g., flame, skull and crossbones);



Warning

Causes Skin Irritation

Precautionary Statements			
Prevention	Response	Storage	Disposal
<p>Wash all body parts which have come into contact with any sawdust generated from sawing, grinding, drilling, sanding, or machining thoroughly after handling.</p> <p>Wear protective gloves. Any type that creates a barrier is acceptable – Selection should be oriented to decrease contact with splinters and slivers of wood.</p>	<p>If on skin: Wash with plenty of water and soap.</p> <p>If skin irritation occurs: Get medical advice.</p> <p>Take off contaminated clothing and wash it before reuse.</p>		

Warning

Causes Eye Irritation


Precautionary Statements			
Prevention	Response	Storage	Disposal
<p>Wash all body parts which have come into contact with any sawdust generated from sawing, grinding, drilling, sanding, or machining thoroughly after handling.</p>	<p>If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>If eye irritation persists: Get medical advice.</p>		

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel



Danger

May Cause Allergy Or Asthma Symptoms Or Breathing Difficulties If Inhaled

Precautionary Statements			
Prevention	Response	Storage	Disposal
<p>Avoid breathing dust.</p> <p>In case of inadequate ventilation wear respiratory protection.</p> <p>Adequate ventilation is considered that which keeps exposure limits at or below 15mg/m³</p>	<p>If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.</p> <p>If experiencing respiratory symptoms: Call a poison center.</p> <p> For a poison emergency in the U.S. call 1-800-222-1222</p>		<p>Dispose of contents in accordance with all applicable local, regional, national, or international rules and regulations.</p>



Warning

May Cause An Allergic Skin Reaction

Precautionary Statements			
Prevention	Response	Storage	Disposal
<p>Avoid breathing dust.</p> <p>Contaminated work clothing must not be allowed out of the workplace</p> <p>Wear protective gloves. Any type that creates a barrier is acceptable – Selection should be oriented to decrease contact with splinters and slivers of wood.</p>	<p>If on skin: Wash with plenty of water and soap.</p> <p>If skin irritation occurs: Get medical advice.</p> <p>Wash contaminated clothing before reuse.</p>		<p>Dispose of contents in accordance with all applicable local, regional, national, or international rules and regulations.</p>

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel



Warning

Suspected Of Causing Cancer Of The Upper Respiratory System

Precautionary Statements			
Prevention	Response	Storage	Disposal
<p>Obtain special instructions before use.</p> <p>Do not handle until all safety precautions have been read and understood.</p> <p>Wear protective gloves and eye protection. Acceptable gloves are any type that creates a barrier – Glove selection should be oriented to decrease contact with splinters and slivers of wood.</p>	<p>If exposed or concerned: Get medical advice.</p>	<p>Store locked up.</p>	<p>Dispose of contents in accordance with all applicable local, regional, national, or international rules and regulations.</p>



Warning

Flammable Solid

Precautionary Statements			
Prevention	Response	Storage	Disposal
<p>Keep away from heat, sparks, open flames and hot surfaces. - No smoking.</p> <p>Ground or Bond container and receiving equipment.</p> <p>Use explosion-proof electrical, ventilating, lighting, and processing equipment.</p> <p>Wear protective gloves and eye protection. Acceptable gloves are any type that creates a barrier – Glove selection should be oriented to decrease contact with splinters and slivers of wood.</p>	<p>In case of fire: Use water or wood appropriate fire extinguishers to extinguish.</p>		

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

(c) Describe any hazards not otherwise classified that have been identified during the classification process;

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

The Occupational Safety and Health Administration (OSHA) in the United States defines combustible dust as *"a solid material composed of distinct particles or pieces, regardless of size, shape, or chemical composition, which presents a fire or deflagration hazard when suspended in air or some other oxidizing medium over a range of concentrations"*.

Dust particles with an effective diameter of less than 420 microns (those passing through a U.S. No. 40 standard sieves) should be deemed to meet the criterion of the definition.

(d) Where an ingredient with unknown acute toxicity is used in a mixture at a concentration $\geq 1\%$ and the mixture is not classified based on testing of the mixture as a whole, a statement that X% of the mixture consists of ingredient(s) of unknown acute toxicity is required.

N/A

SECTION III - Composition/Information on Ingredients

Except as provided for in paragraph (i) of §1910.1200 on trade secrets:

For Substances

- (a) Chemical name;
- (b) Common name and synonyms;
- (c) CAS number and other unique identifiers;
- (d) Impurities and stabilizing additives which are themselves classified and which contribute to the classification of the substance.

For Mixtures

In addition to the information required for substances:

- (a) The chemical name and concentration (exact percentage) or concentration ranges of all ingredients which are classified as health hazards in accordance with paragraph (d) of §1910.1200 and
 - (1) Are present above their cut-off/concentration limits; or
 - (2) Present a health risk below the cut-off/concentration limits.
- (b) The concentration (exact percentage) shall be specified unless a trade secret claim is made in accordance with paragraph (i) of §1910.1200, when there is batch-to-batch variability in the production of a mixture, or for a group of substantially similar mixtures (See A.0.5.1.2) with similar chemical composition. In these cases, concentration ranges may be used.

For All Chemicals Where a Trade Secret is Claimed

Where a trade secret is claimed in accordance with paragraph (i) of §1910.1200, a statement that the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret is required.

See Below For Requirements –

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

Chemical, Common or Synonyms Name	Approximate %	CAS #
Wood (mainly softwoods such as pine)	90% to 98%	None
Monosodium Phosphate Sodium Phosphate (monobasic) Sodium Dihydrogen Phosphate Dihydrogen Sodium Phosphate	1% to 3%	7558-80-7
Sodium Tetraborate Decahydrate 10 Mol Borax	0.25% to 1.5%	1303-96-4
Boric Acid	0.25% to 1.5%	10043-35-3
Urea Phosphate	1% to 3%	4861-19-2
Tetrachloroisophthalonitrile Chlorothalonil Daconil	0.01% to 0.03%	1897-45-6
5-Chloro-2-methyl-4-Isothiazolin-3-one	≤ 0.01%	26172-55-4
2-Methyl-4-Isothiazolin-3-one	≤ 0.01%	2682-20-4
Magnesium Nitrate	≤ 0.01%	10377-60-3
Bonding agents such as phenol, phenol resorcinol, melamine formaldehyde-based, or polyvinyl acetate resin and other ingredients below reportable levels	Balance	

SECTION IV – First-aid Measures

- (a) Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion;



First Aid Procedures

First Aid for Inhalation: – If inhalation symptoms appear remove from area of exposure and monitor. If persistent irritation, severe coughing, allergic-type responses or breathing difficulty occurs, get medical attention.

First Aid for Skin Contact: – If skin contact symptoms appear remove from area of exposure and monitor. Remove contaminated clothing. Wash affected area with soap and water. If irritation persists after washing, get medical attention.

First Aid for Eye Contact: – Wood dust may cause mechanical irritation. Treat dust in eye as foreign object. Remove contact lenses if worn. Flush eyes with large amounts of water to remove dust particles. Do not rub the eyes. Seek medical attention if irritation persists.

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

First Aid for Ingestion: – Not applicable under normal use, and considered unlikely. If occurred - Do not induce vomiting unless directed by a medical care giver, drink water. Never give anything by mouth to an unconscious person. Seek medical advice.

Notes to Physician: – All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

(b) Most important symptoms/effects, acute and delayed.

Potential Health Effects

Inhalation

Wood dust may cause nasal dryness, irritation, coughing and sinusitis. Repeated exposures (even below 15 mg/m³) to certain wood dusts such as Western Red Cedar, can produce allergic responses in some sensitive individuals. Wood dust can be irritating to eyes, nose and respiratory tract following prolonged exposure.

Skin Contact

Various species of wood dust may evoke allergic contact dermatitis in sensitized individuals. If an allergy preexists or develops, it may be necessary to remove the sensitized worker from further exposure to wood dust or wood-based products. The chemical components may cause slight to mild irritation.

Eye Contact

Dust or splinters may cause irritation or injury to the eyes. The chemical components can cause burning sensation, tearing, and redness.

Ingestion

Not applicable under normal use, and considered unlikely. If occurred may result in irritation of the digestive tract.

(c) Indication of immediate medical attention and special treatment needed, if necessary.

N/A

SECTION V – Fire-fighting Measures

(a) Suitable (and unsuitable) extinguishing media.

FIRE EXTINGUISHING MEDIA: Water, foam or Fire Extinguishers designated for wood. Partially burned dust is especially hazardous if dispersed into the air. Remove burned or wet dust to open area after fire is extinguished.

(b) Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products).

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

EXPLOSIVE LIMITS: Sawing, sanding or machining wood products can produce wood dust as a by-product. Wood dust is a strong to severe explosion hazard if a dust “cloud” contacts an ignition source. 212°F (100°C) has been suggested as the upper temperature limit for continuous exposure for wood without risk of ignition (wood dust may require a still lower temperature). An airborne concentration of 40 grams of dust per cubic meter of air is often used as the lowest explosion limit (LEL) for wood dust.

HAZARDOUS COMBUSTION PRODUCTS: Thermal-oxidative degradation, or burning, of wood can produce irritating and potentially toxic fumes and gases including carbon monoxide, aldehydes and organic acids. Chemical treatment has little or no effect on the above possibilities from untreated wood.

AUTOIGNITION TEMPERATURE: Unknown (Chemical Treatment Retards).

(c) Special protective equipment and precautions for fire-fighters.

None

SECTION VI - Accidental Release Measures

- (a) Personal precautions, protective equipment, and emergency procedures.
- (b) Methods and materials for containment and cleaning up.

Not applicable for product in purchased form. Sweep or vacuum up sawdust for recovery or disposal. Wood dust clean-up and disposal activities should be accomplished in a manner to minimize creation of airborne dust.

SECTION VII - Handling and Storage

- (a) Precautions for safe handling.
- (b) Conditions for safe storage, including any incompatibilities.

HANDLING:

Protective Gloves – Work gloves are recommended to avoid splinters.

Eye Protection – Safety goggles or glasses are recommended when machining to protect against sawdust and flying wood particles.

Protective Clothing or Equipment – Recommended as typical with any wood working.

Work/Hygienic Practices - Practice good hygiene, wash hands after use and before eating, drinking or using tobacco products.

STORAGE:

No ground contact allowed. Product is shipped dry and should not be exposed to the weather. Water spray may be used to wet down wood dust generated by sawing, grinding, drilling, sanding or machining to reduce the likelihood of ignition or dispersion of dust into the air.

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

SECTION VIII - Exposure Controls/Personal Protection

(a) OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available.

(b) Appropriate engineering controls.

(c) Individual protection measures, such as personal protective equipment.

EXPOSURE GUIDELINES:

Chemical	OSHA PEL	ACGIH TLV
Wood (mainly softwoods such as pine)	15 mg/m ³ TWA (Listed under Particulates Not Otherwise Regulated - Total dust) 5 mg/m ³ TWA Respirable Fraction	1 mg/m ³ TWA* *Inhalable Fraction
Monosodium Phosphate	None Listed	None Listed
Sodium Tetraborate Decahydrate	None Listed	2 mg/m ³ TWA* 6 mg/m ³ STEL* *Inhalable Fraction (TLV listed under Borate compounds, Inorganic)
Boric Acid	None Listed	2 mg/m ³ TWA* 6 mg/m ³ STEL* *Inhalable Fraction (TLV listed under Borate compounds, Inorganic)
Urea Phosphate	None Listed	None Listed
Tetrachloroisophthalonitrile	None Listed	None Listed
5-Chloro-2-methyl-4-Isothiazolin-3-one	None Listed	None Listed
2-Methyl-4-Isothiazolin-3-one	None Listed	None Listed
Magnesium Nitrate	None Listed	None Listed
Bonding agents such as phenol, phenol resorcinol, melamine formaldehyde-based, or polyvinyl acetate resin and other ingredients below reportable levels	Unknown	Unknown

ENGINEERING CONTROLS: Due to the explosive potential of wood dust when suspended in air, precautions should be taken during sawing, grinding, drilling, sanding or machining of wood products to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended. Provide local exhaust as necessary to meet OSHA requirements for airborne exposure limits.

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

INDIVIDUAL PROTECTION MEASURES:

RESPIRATORY PROTECTION: When sawing, grinding, drilling, sanding or machining, a dust mask is recommended. Typical use of this material does not result in workplace exposures that exceed the exposure limits listed in the Exposure Limit Information Section. For those special workplace conditions where the listed exposure limits are exceeded, a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed.

VENTILATION REQUIREMENTS: In enclosed environments, ventilation may be required in order to maintain exposure limits.

PROTECTIVE GLOVES: Not required. However, cloth, canvas, or leather gloves are recommended to minimize potential splinters, slivers or mechanical irritation when handling product or wood dust generated from the product.

EYE PROTECTION: Goggles or safety glasses are recommended when excessive exposures to wood dust may occur (e.g. during clean up).

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: As necessary to limit exposure when handling the product or wood dust generated from the product.

WORK/HYGIENIC PRACTICES: Follow good hygienic and housekeeping practices. Clean up areas where wood dust settles to avoid excessive accumulation of this combustible material. Minimize compressed air blow down or other practices that generate high airborne-dust concentrations. Do not handle material near food, feed or drinking water. Use good personal hygiene. Wash hands before eating or smoking.

SECTION IX - Physical and Chemical Properties

- (a) Appearance (physical state, color, etc.);
- (b) Odor;

Rigid panel usually ½” to ¾” thick and 4’ width and 8’ length. Color and odor are dependent upon wood specie. Chemical treatment only darkens the woods natural color.

- (c) Odor threshold; N/A
- (d) pH; N/A
- (e) Melting point/freezing point; N/A
- (f) Initial boiling point and boiling range; N/A
- (g) Flash point; N/A
- (h) Evaporation rate; N/A
- (i) Flammability (solid, gas); Wood Dust Combustible

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

- (j) Upper/lower flammability or explosive limits; Wood Dust $\geq 40 \text{ g/m}^3$
- (k) Vapor pressure; N/A
- (l) Vapor density; N/A
- (m) Relative density; Variable - Dependent on wood species and moisture content (typically 22 – 37 lbs/ft³)
- (n) Solubility(ies); Chemical treatment might be leachable under extreme wetness which is not allowed
- (o) Partition coefficient: n-octanol/water; N/A
- (p) Auto-ignition temperature; Auto-ignition Temperature is $\geq 572 \text{ F}$
- (q) Decomposition temperature; $\geq 572 \text{ F}$
- (r) Viscosity. N/A

SECTION X - Stability and Reactivity

- (a) Reactivity; N/A
- (b) Chemical stability; Stable under normal conditions. Wood dust generated from sawing, grinding, drilling, sanding or machining the product is combustible. Keep in cool, dry place away from ignition sources.
- (c) Possibility of hazardous reactions; None Known
- (d) Conditions to avoid (e.g., static discharge, shock, or vibration); Large accumulations of air-borne wood dust. Product in direct ground contact. Product becoming wet.
- (e) Incompatible materials; Oxidizing agents, Drying Oils, Strong Bases, and Reducing Agents.
- (f) Hazardous decomposition products. Thermal-oxidative degradation, or burning, of wood can produce irritating and potentially toxic fumes and gases including carbon monoxide, aldehydes, oxides of sodium, oxides of phosphorus. Reaction with strong reducing agents, such as metal hydrides or alkali metals, will generate hydrogen gas, which could create an explosive hazard.

SECTION XI - Toxicological Information

Description of the various toxicological (health) effects and the available data used to identify those effects, including:

- (a) Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact);
- (b) Symptoms related to the physical, chemical and toxicological characteristics;
- (c) Delayed and immediate effects and also chronic effects from short- and long-term exposure;
- (d) Numerical measures of toxicity (such as acute toxicity estimates).
- (e) Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA.

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

PRODUCT AS PRODUCED:

Is an article and no toxicological information is available.

OSHA: Wood products are not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, wood dust generated by sawing, sanding or machining this product may be hazardous.

COMPONENTS:

Monosodium Phosphate (Acute Toxicity) -

Eye Effects: Slightly irritating (Rabbit, 12.6/110.0, 1 hour exp) - 150 mg (std. Draize), Rabbit.

Skin Effects: Practically Nonirritating (Rabbit, 0.0/0.8, Avg. Max)

Ingestion Effects: Practically Nontoxic (Rat LD₅₀ - 8290 mg/kg)

Sodium Tetraborate Decahydrate (Acute Toxicity) -

Ingestion: Low acute oral toxicity; LD₅₀ in rats is 4,500 to 5,000 mg/kg of body weight.

Skin/dermal: Low acute dermal toxicity; LD₅₀ in rabbits is greater than 10,000 mg/kg of body weight.

Inhalation: Low acute inhalation toxicity; LC₅₀ in rats is greater than 2.0 mg/L (or g/m³)

Eye irritation: Draize tests in rabbits produced eye irritation effects. Years of occupational exposure to Sodium Tetraborate Decahydrate indicates no adverse effects on human eye.

Boric Acid (Acute Toxicity) -

Ingestion: Low acute oral toxicity; LD₅₀ in rats is 3,500 to 4,100 mg/kg of body weight.

Skin/dermal: Low acute dermal toxicity; LD₅₀ in rabbits is greater than 2,000 mg/kg of body weight.

Inhalation: Low acute inhalation toxicity; LC₅₀ in rats is greater than 2.0 mg/L (or g/m³)

Eye irritation: Draize tests in rabbits produced mild eye irritation effects. Years of occupational exposure to Boric Acid indicates no adverse effects on human eye.

Diurea Phosphate (Acute Toxicity) -

Ingestion Effects: Low acute oral toxicity; LD₅₀ in rats is 5,840 mg/kg of body weight.

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

Chlorothalonil (Acute Toxicity) -

Ingestion: Low acute oral toxicity; LD₅₀ in rats is 4,200 mg/kg of body weight. Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Can result in some corrosive action to the mouth, throat, esophagus, and stomach tissue. Studies on rats and mice have suggested that technical chlorothalonil (97%), when fed at high levels in diet, may have oncogenic potential to these laboratory animals. However, neither chlorothalonil nor its metabolites interact with DNA and thus are not mutagenic. Metabolism studies have demonstrated that the rat metabolizes chlorothalonil to form metabolites that are toxic to kidney mitochondria. Much lower levels (150 to >2000 fold) of these metabolites are formed in dogs and monkeys, thus, effects seen in rats may not translate to man. Tumor formation has been related to a non-genotoxic mechanism of action for which threshold levels have been established on rats and mice. Comprehensive dietary and worker exposure studies have shown exposure levels for humans to be well below these threshold levels. In addition, surveillance of chlorothalonil plant workers for over twenty years has not demonstrated any increase in oncogenic potential to humans.

Skin/dermal: Low acute dermal toxicity; LD₅₀ in rabbits is greater than 2,000 mg/kg and less than 20,000 mg/kg of body weight. Repeated or excessive dermal exposure may cause marked skin irritation. On overexposed skin, may cause moderate irritation, redness, and a flaky rash may result. Skin rash is seldom observed if the following recommended safeguards are followed:

Wear rubber gloves when handling, using, or applying this product. Special precautions should be taken to ensure that material cannot get inside gloves. Wear long-sleeved shirts, long pants, and rubber boots or disposable coveralls when handling this product.

Inhalation: LC₅₀ in rats is greater than 0.20 mg/L and less than 2.1 mg/L (or g/m³).

Eye irritation (Rabbit/Monkey): Reversible corneal, iridal and conjunctival effects. Maximum mean score (noted at 24 hours): Rabbit = 23.3/110 Monkey = 25.3/110. Human experience indicates that this product may cause mild to severe irritation, depending on the degree of exposure.

The Following Are Taken As A Group:

5-Chloro-2-methyl-4-Isothiazolin-3-one

2-Methyl-4-Isothiazolin-3-one

Magnesium Nitrate

(Acute Toxicity) -

The below statements are with the above components at 10.6%, 3.5% and 15.0% respectively; numerous times the actual present in the product.

ROUTES OF ENTRY: Inhalation, dermal absorption, skin contact and eye contact.

SIGNS AND SYMPTOMS OF ACUTE OVEREXPOSURE:

Eyes - Corrosive to eyes. Severely irritating to the eyes and may cause eye burns. May cause permanent eye injury.

Skin - Corrosive to the skin. Severely irritating to the skin and may cause chemical burns to the skin. May cause allergic skin sensitization of susceptible persons. May be fatal if absorbed through the skin.

Ingestion - May be harmful or fatal if swallowed. Ingesting may produce chemical burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

Inhalation - Harmful if inhaled. Inhalation of vapors, mists or sprays can cause irritation or burns of the nose, throat and lungs.

CHRONIC OVEREXPOSURE: Allergic contact dermatitis observed. Collective data indicate non-mutagenic; not teratogenic.

CHEMICAL LISTED AS A CARCINOGEN OR POTENTIAL CARCINOGEN?:

- NATIONAL TOXICOLOGY PROGRAM (Y/N): N
- IARC MONOGRAPHS (Y/N) N
- OSHA (Y/N) N:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

TOXICOLOGICAL DATA:

Dermal LD50 - rabbit: > 1,000 mg/kg

Oral LD50 - rat: 481 mg/Kg

Eye Irritation - rabbit: corrosive

Skin Irritation - rabbit: corrosive

Inhalation LC50 (4hr) – 1.23 mg/l (aerosol)

WOOD DUST (softwood or hardwood) -

OSHA Hazard Rating = 3.3; moderately toxic with probable oral lethal dose to humans being 0.5-5 g/kg (about 1 pound for a 150 pound person) Source: *OSHA Regulated Hazardous Substances*, Government Institutes, Inc., February 1990.

Wood dust generated from sawing, grinding, drilling, sanding or machining may cause nasal dryness, irritation, coughing and sinusitis. NTP and IARC classify wood dust as a human carcinogen (IARC Group 1). This classification is based primarily on increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust. The evaluation did not find sufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum with exposure to wood dust.

SECTION XII - Ecological Information

(a) Ecotoxicity (aquatic and terrestrial, where available); Not available

(b) Persistence and degradability;

(c) Bioaccumulative potential;

Environmental fate of wood dust would be expected to be biodegradable.

(d) Mobility in soil; N/A

(e) Other adverse effects (such as hazardous to the ozone layer). None Known

SECTION XIII - Disposal Considerations

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging.

Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose of material according to Local, State, Federal, and Provincial Environmental Regulations.

The producer has made a determination that this product is not considered hazardous waste under Federal hazardous waste regulations 40 CFR Part 261. Incinerate or landfill in accordance with Local, State, and Federal regulations.

SECTION XIV – Transport Information

- (a) UN number;
- (b) UN proper shipping name;
- (c) Transport hazard class(es);
- (d) Packing group, if applicable;
- (e) Environmental hazards (e.g., Marine pollutant (Yes/No));
- (f) Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code);

- (g) Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises.

This product is not regulated as a dangerous good or hazardous material by the U.S. Department of Transportation (DOT).

SECTION XV - Regulatory Information

Safety, health and environmental regulations specific for the product in question.

Toxic Substance Control Act (TSCA): N/A

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA): N/A

Domestic Substance List (DSL): N/A

OSHA: Wood products per se are not hazardous under the criteria of the federal OSHA Hazard Communication Standard 29CFR 1910.1200. However, wood dust generated by sawing, sanding or machining wood products may be hazardous and hence included under 1910.1200.

STATE RIGHT-TO-KNOW:

California Prop 65:

Warning: Drilling, sawing, sanding or machining wood products generates wood dust, a substance known to the State of California to cause cancer.

Pennsylvania – When cut or otherwise machined, wood products may emit wood dust. Wood dust appears on Pennsylvania's Appendix A, Hazardous Substance List.

New Jersey – When cut or otherwise machined, wood products may emit wood dust. Wood dust appears on New Jersey's Environmental Hazardous Substance List.

Section 302 extremely hazardous substance: No regulated ingredients.

SAFETY DATA SHEET (SDS) for MULE-HIDE **PYROXL** Roof Deck Panel

SARA 313 Information: This product contains one chemical ingredient with known CAS number that exceed the de minimis reporting levels established by SARA Title III, section 313 and 40 CFR section 372. This is Chlorothalonil.

SARA 311/312 Hazard Category: This product has been reviewed according to the EPA “Hazard Categories” promulgated under SARA Title III Sections 311 and 312 and is considered, under applicable definitions, to meet the following categories:

An immediate (acute) health hazard	Yes
A delayed (chronic) health hazard	Yes
A corrosive hazard	No
A fire hazard	No
A reactivity hazard	No
A sudden release hazard	No

FDA: Not intended for use as a food additive or indirect food contact item.

SECTION XVI - Other Information

The date of preparation of the SDS or the last change to it.

Current Issue: 04/11/2014

Previous Issue: None

User’s Responsibility: The information contained in this Safety Data Sheet is based on the experience of health and safety professionals and comes from sources believed to be accurate or otherwise technically correct. It is the user’s responsibility to determine if the product is suitable for its proposed application(s) and to follow necessary safety precautions. The user has the responsibility to make sure that this SDS is the most up-to-date issue.

NOTICE: Although the information and recommendations set forth herein (hereinafter “Information”) are presented in good faith and believed to be correct as of the date hereof, Hoover Treated Wood Products, Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for the purposes prior to use. In no event will Hoover Treated Wood Products, Inc. be responsible for damages or any nature whatsoever resulting from the use of or reliance upon this information. **NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.**