

MAINTENANCE & REPAIR SOLUTIONS

LOW-SLOPE ROOFING

WE'VE GOT WHAT YOU NEED IN THE SIZES YOU NEED THEM AND THE OPTIONS TO MATCH THE RESULTS THAT BUILDING OWNERS WANT



"The name trusted in roofing since 1906"



SEAL-FAST® TEMPORARY ROOF SEALER

Now you can immediately seal a leak on a low-slope roof when weather does not permit a longer-term, proper repair. Comes in a sturdy 2-1/2" gallon waterproof container that is easy to transport and easy to pour. It keeps the product dry and ready for use and will reduce waste, store easily, and prevent messy cleanup in your vehicle.

INSTRUCTIONS

- Apply Seal-Fast® TEMPORARY LOW-SLOPE ROOF SEALER in approximately a 1/2" layer over suspected leak area
- Application area must be in a wet, ponding condition
- Seal-Fast® TEMPORARY LOW-SLOPE ROOF SEALER will seek out and temporarily seal the leak, even during rain
- Seal-Fast® TEMPORARY LOW-SLOPE ROOF SEALER will expand to several times its original size and become a sealant material
- Longer-term, proper repairs should be made as soon as weather permits
- Existing Seal-Fast® TEMPORARY LOW-SLOPE ROOF SEALER should be removed from the roof area prior to the longer-term, proper repair work.

COVERAGE


Seal-Fast® TEMPORARY LOW-SLOPE ROOF SEALER comes in a 25 lb. container that covers approximately 50 sq. ft.

CAUTION

When exposed to moisture, Seal-Fast® TEMPORARY LOW-SLOPE ROOF SEALER becomes a gel-like material that is extremely slippery. DO NOT STEP IN OR PLACE ANY LADDERS OR TOOLS in any area when it is used. To prevent lung injury, Seal-Fast® TEMPORARY LOW-SLOPE ROOF SEALER dust should NOT BE INHALED. DO NOT POUR INTO AREAS OF RUNNING WATER.

FOR COMMERCIAL USE ONLY

Haul It!




Carry It!



Pour It!



Store It!



KEEP OUT OF REACH OF CHILDREN

Sold as is. Mule-Hide will not be responsible or liable for any consequential or incidental damages. Buyer's sole remedy is replacement of purchased product.



SEAL-FAST® TEMPORARY LOW-SLOPE ROOF SEALER

For temporary repair of roof leaks until weather permits proper repair.

25 lb. container

SEAL-FAST® TAPE & SEAL-FAST® FABRIC TAPE

MAINTENANCE & REPAIR OF LOW-SLOPE ROOFS

Seal-Fast® Tape seals clean surfaces on contact and provides a superior watertight seal that can withstand temperature extremes.

- Clean and prep the area thoroughly
- Replace any loose fasteners (Prime if needed)
- Cut tape to size and position on surface
- Peel release liner from the tape
- Place and roll with steel hand roller
(For Seal-Fast Fabric Tape - apply coating)

ADHERES TO MANY LOW-SLOPE ROOFS & SURFACES

- Metal - Most PVC - TPO - Hypalon
- Other Thermoplastics - It's ideal when you don't know what the white membrane is
- BUR (& Coal Tar) - Modified Bitumen APP & SBS

SEALFAST® TAPE AND SEALFAST® FABRIC TAPE ARE MANUFACTURED WITH MICROSEALANT™ TECHNOLOGY



One-Step - Made from synthetic rubbers (non-butyl) and resins with a proprietary built-in primer, these versatile tapes provide an instant, watertight seal.

CHEMICAL RESISTANT AND STRONG

Self-sealing and very tolerant of chemicals.

WIDE TEMPERATURE RANGE

Remains pliable and can be applied in temperatures above 40°F without primer, down to -20°F with Seal-Fast® Primer. (Materials must be maintained at room temperature)

ENVIRONMENTALLY FRIENDLY

No solvents or VOC's.

Clean



Cut Tape



Peel



Roll



10-YEAR LIMITED MATERIAL-ONLY WARRANTY

SEAL-FAST® FABRIC TAPE

Roll ideal for reinforcing metal roof seams prior to applying coatings.

6" x 25'
White

SEAL-FAST® CLEANER

For cleaning surfaces prior to applying Seal-Fast® Tapes.

14 oz aerosol spray container

SEAL-FAST® PRIMER

For cleaning surfaces prior to applying Seal-Fast® Tapes.

1 quart can or Spray Primer in 14 oz Aerosol can



SEAL-FAST® TAPE

Rolls for repairing BUR (& Coal Tar), and Mod Bit.

4" x 50', 6" x 50', and 12" x 25'
Black

SEAL-FAST® TAPE

Rolls for repairing Metal, most PVC, TPO, other Thermoplastics.

3" x 50', 6" x 25', 6" x 50', and 12" x 50'
White



FAST-CAPS®

STOP METAL ROOF FASTENER LEAKS!

Quickly seal rusted, leaking fasteners and prevent fastener backout. Thermal shock is the biggest culprit in causing fasteners to loosen and back out, the major cause of metal roof leaks. As they loosen, the metal panels lift allowing moisture to travel along the panel edge, which causes leaks.

Fast-Caps® are aluminum-faced conforming disks with a pressure-sensitive adhesive that assures a flexible, self-sealing barrier for maximum, long-term performance. Fast-Caps® are reinforced with special high-density polymers providing extraordinary tear strength and elongation values up to 300%. The aluminum covering reflects heat and UV.

FOLLOWING THESE SIMPLE STEPS, A TWIST OF THE WRIST PROVIDES A TIGHT SEAL

- Clean and prepare the surface
- Tighten loose fasteners & replace missing or worn fasteners
- Position Fast-Cap® over fastener and remove the release liner
- Bend Fast-Cap® to center over fastener head and apply
- Use supplied securing tool - center and push down, then twist & rock tool to firmly adhere
- Leave as is or apply roof coating - we recommend Mule-Hide Elastomeric Acrylic Coatings
- Fast-Caps® are ideal in cold weather situations

Stop Leaks



Save Time



Save Money



**HANDY SLIDE CHART
HELPS YOU SELECT
THE RIGHT PRODUCTS.**



FAST-CAPS®

Bag of 500 for repairing fasteners on metal roofs.

Includes tool to apply.



EPDM CURED COVER TAPE

THE ONLY PRODUCT TO PROPERLY REPAIR EPDM - IN CONVENIENT 6" X 25' ROLLS!

Ideal for use as a patching material when making EPDM repairs, this "cured" tape is also used to strip in edge metal, cover exposed batten bar, and as a seam cover typically required in longer term warranted systems.

EASY APPLICATION - FEW STEPS

Simply clean/prime*, position tape, remove release liner, and roll with a 2" steel roller.

EXCELLENT PEEL AND SHEAR STRENGTH

Provides a consistent thickness and width of seam "adhesive", eliminating the guesswork of liquid adhesives. Tape strength actually improves with age...for less callbacks.

OTHER LABOR-SAVING PRODUCTS

Pre-Molded Pipe Boots with Tape, Pre-Cut Corners with Tape, Reinforced Membrane Strips with Tape, and Pourable Sealer Pockets with Tape.

**NOTE - Heavily soiled membrane should be cleaned with soap and water, thoroughly rinsed and allowed to dry prior to application of Tape Primer.*

Apply Tape Primer



Apply Tape



EPDM CURED COVER TAPE

For EPDM repairs.

6" x 25', 6" x 100' or 12" x 50'
Black



For EPDM repairs.

6" x 25', 6" x 100' or 12" x 50'
Black



EPDM TAPE PRIMER

For preparing EPDM prior to applying Cured Cover Tape.

1 qt.

FULL LINE OF SOLUTIONS



ASPHALT CEMENTS & COATINGS

- Aluminum Roof Coatings, 5 gal.
- Asphalt Roofing Mastics, 3 or 5 gal.
- Asphalt Primer, 14 oz. Spray can or 5 gal.
- Protective Coatings/Emulsions, 5 gal.

ELASTOMERIC ACRYLIC COATINGS

Metal Roof Coating System

- 115 CLEANER, 5 gal.
- A-125 METAL ROOF PRIMER, 5 gal.
- A-200 FLASHING GRADE SEALANT, 1 or 5 gal.
- A-300 FINISH, 1 gal. or 5 gal. - ENERGY STAR® listed

EPDM Restoration System™

- 115 CLEANER, 5 gal.
- A-300 FINISH, 1 gal. or 5 gal. - ENERGY STAR® listed

Other Applications / Specialty Coatings

- A-300 FINISH, 1 gal or 5 gal. - for coating weathered Hypalon
- A-301 SKYLIGHT FINISH, 1 or 5 gal.
- A-320 FINISH, 1 or 5 gal. - for asphaltic substrates and ponded water areas.
- A-400-W MASONRY WALL COATING, 5 gal.
- A-600 BASE for Coating Aged TPO



Contact Mule-Hide Products for specific product approvals and ratings. Featured industry association/organization logos are U.S. registered trademarks. Mule-Hide is an AIA registered CES provider. Energy Star is only valid in the United States for Roofing Products.

“The name trusted in roofing since 1906”

Customer Line: 800-786-1492 • www.mulehide.com

Check our website monthly for the latest updates & technical bulletins.

National Support Center • 1195 Prince Hall Drive • Beloit, WI 53511 • tel. 608.365.3111 • fax. 608.365.7852

The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Mule-Hide Products Co., Inc. does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.

Visit the Mule-Hide website at www.mulehide.com prior to any installation for updated technical specifications and details. Mule-Hide, Seal-Fast and Fast-Caps are U.S. registered trademarks. All rights reserved.

