

Material Name: TPO Tape Primer SDS 10-3215

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

**Material Name** 

**TPO Tape Primer** 

**Chemical Family** 

Primer, mixture

**Restrictions on Use** 

For industrial use only.

**Manufacturer Information:** 

Carlisle SynTec 1285 Ritner Highway Carlisle, PA 17013

**USA** 

Phone: +1-800-479-6832

Emergency Phone #: +1-800-424-9300 (CHEMTREC)

**Supplier Information:** 

Mule-Hide Products Co., Inc 1195 Prince Hall Dr. Beloit, WI 53511

USA

Phone: 800-786-1492

#### Section 2 - HAZARDS IDENTIFICATION

### Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 2 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Eye Irritation - Category 2A Skin Sensitization - Category 1A Carcinogenicity - Category 2 Specific Target Organ Toxicity - Single Exposure - Category 3

CHC I also I Elamana

### **GHS Label Elements**

### Symbol(s)







### Signal Word

Danger

### **Hazard Statement(s)**

Highly flammable liquid and vapor Causes skin irritation Causes serious eye irritation May cause allergic skin reaction



Material Name: TPO Tape Primer SDS 10-3215

Suspected of causing cancer May cause drowsiness or dizziness

### **Precautionary Statement(s)**

#### **Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep container tightly closed

Keep away from heat/sparks/open flame/hot surfaces - No smoking

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Take precautionary measures against static discharge

Use only non-sparking tools

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

### Response

In case of fire: Use appropriate media to extinguish IF exposed or concerned: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with

water/shower

If skin irritation or rash occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Specific treatment (see label)

### Storage

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

#### **Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-89-8	Solvent naphtha, petroleum, light aliphatic	10-30



**Material Name: TPO Tape Primer** 

SDS 10-3215

Trade Secret	Isophorone Diisocyanate	0.1-1
108-88-3	Toluene	40-70
Trade Secret	Chlorinated polypropylene	0.5-1.5
Trade Secret	Heat reactive phenolic resin	0.1-1
Trade Secret	Isophorondiamine-isobutyraldimine	0.1-1

### Section 4 - FIRST AID MEASURES

### **Description of Necessary Measures**

IF exposed or concerned: Get medical advice/attention.

#### Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

#### Skin

Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.

### **Eyes**

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### **Ingestion**

If swallowed, get medical attention.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

### **Most Important Symptoms/Effects**

### Acute

Causes skin irritation. Causes serious eye irritation. May cause allergic skin reaction. May cause drowsiness or dizziness.

### **Delayed**

May cause allergic skin reaction. Suspected of causing cancer.

### Section 5 - FIRE FIGHTING MEASURES

### **Extinguishing Media**

### **Suitable Extinguishing Media**

Dry chemical, foam or carbon dioxide. Water may be ineffective.

Page 3 of 12 Issue date: 2015-05-19 Revision 1.0 Print date: 2016-09-08



Material Name: TPO Tape Primer SDS 10-3215

### Unsuitable Extinguishing Media

Do not use high-pressure water streams.

### **Special Hazards Arising from the Chemical**

Highly flammable liquid and vapor.

#### **Hazardous Combustion Products**

Carbon monoxide, carbon dioxide, oxides of nitrogen, aldehydes

### **Fire Fighting Measures**

Move container from fire area if it can be done without risk.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

### Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Avoid breathing vapors. Wear self-contained breathing apparatus and protective clothing. Ventilate the area. Use non-sparking tools. Large spills: Dike for later disposal. Cleanup Methods: Absorb with sand or other non-combustible material. Use clean non-sparking tools to collect absorbed material and place it into loosely-covered metal or plastic containers for later disposal. Dispose in accordance with all applicable federal, state/regional and local laws and regulations.

#### **Environmental Precautions**

Avoid release to the environment. Collect spillage.

#### Section 7 - HANDLING AND STORAGE

### **Precautions for Safe Handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. KEEP OUT OF REACH OF CHILDREN.

### Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Keep dry. Keep away from heat and ignition sources. Do not puncture or burn containers, even when empty. Empty containers may contain product residue.

### **Incompatible Materials**

Strong oxidizing agents, acids, bases



Material Name: TPO Tape Primer SDS 10-3215

### Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Component Exposure Limits**

Toluene	108-88-3		
ACGIH:	20 ppm TWA		
NIOSH:	100 ppm TWA; 375 mg/m3 TWA   150 ppm STEL; 560 mg/m3 STEL		
	500 ppm IDLH		
Europe:	50 ppm TWA; 192 mg/m3 TWA		
	Possibility of significant uptake through the skin		
OSHA (US):	200 ppm TWA 300 ppm Ceiling		
Mexico:	50 ppm TWA LMPE-PPT; 188 mg/m3 TWA LMPE-PPT		
	Skin - potential for cutaneous absorption		

### **Biological limit value**

There are no biological limit values for any of this product's components.

### **Engineering Controls**

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

### Individual Protection Measures, such as Personal Protective Equipment

#### **Eve/face protection**

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

### **Skin Protection**

Wear appropriate chemical resistant clothing. Wear protective shoes.

### **Respiratory Protection**

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

### **Glove Recommendations**

Wear appropriate chemical resistant gloves.

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	orange to red liquid	Physical State	liquid
Odor	characteristic	Color	orange to red
Odor Threshold	Not available	рН	Not available

Page 5 of 12 Issue date: 2015-05-19 Revision 1.0 Print date: 2016-09-08



Material Name: TPO Tape Primer SDS 10-3215

<b>Melting Point</b>	-95 °C(-139°F)	<b>Boiling Point</b>	111 - 141 °C(-232 -259°F)	
Freezing point	Not available	<b>Evaporation Rate</b>	2.7	
<b>Boiling Point Range</b>	Not available	Flammability (solid, gas)	Not available	
Autoignition	500 °C(932°F)	Flash Point	4 °C(40°F)	
<b>Lower Explosive Limit</b>	0.9	Decomposition	Not available	
<b>Upper Explosive Limit</b>	6.7	Vapor Pressure	19.3 mmHg	
Vapor Density (air=1)	3.4	Specific Gravity (water=1)	Not available	
Water Solubility	Insoluble	Partition coefficient: n-octanol/water	Not available	
Viscosity	<200 cps	Solubility (Other)	Not available	
Density	0.75 - 0.81	<b>VOC</b> 645 g/L		

### Section 10 - STABILITY AND REACTIVITY

### Reactivity

No reactivity hazard is expected.

### **Chemical Stability**

Stable under normal conditions of use.

### **Possibility of Hazardous Reactions**

Will not polymerize.

### **Conditions to Avoid**

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

### **Incompatible Materials**

Strong oxidizing agents, acids, bases

### **Hazardous decomposition products**

Carbon monoxide, carbon dioxide, aldehydes

### Section 11 - TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

### Inhalation

May cause drowsiness or dizziness.



Material Name: TPO Tape Primer SDS 10-3215

### **Skin Contact**

May cause allergic skin reaction. Causes skin irritation.

#### **Eye Contact**

Causes serious eye irritation.

### **Ingestion**

No information on significant adverse effects.

### **Acute and Chronic Toxicity**

### **Component Analysis - LD50/LC50**

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

Oral LD50 Rat >2000 mg/kg Dermal LD50 Rat >2000 mg/kg Inhalation Rat >5000 ppm 1 hour

Isophorone Diisocyanate (Trade Secret)

Oral LD50 Rat >20000 mg/kg Dermal LD50 Rabbit 4000 mg/kg Inhalation LC50 Rat 5 mg/l 4 h

Toluene (108-88-3)

Oral LD50 >7000 mg/kg Dermal LD50 12 - 14 g/kg Inhalation LC50 30 - 35 mg/L

Chlorinated polypropylene (Trade Secret)

Oral Rat 5000 mg/kg

Heat reactive phenolic resin (Trade Secret)

Oral LD50 Rat 2160 mg/kg Dermal Rabbit 1880 mg/kg

Isophorondiamine-isobutyraldimine (Trade Secret)

Oral Rat 4150 mg/kg [OECD Test Guideline 401] Dermal Rat >5000 mg/kg [OECD Test Guideline 402]

### **Immediate Effects**

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause allergic skin reaction.

### **Delayed Effects**

May cause allergic skin reaction. Suspected of causing cancer.

### **Irritation/Corrosivity Data**

Causes skin irritation. Causes serious eye irritation.

#### **Respiratory Sensitization**

No information available for the product.

Page 7 of 12 Issue date: 2015-05-19 Revision 1.0 Print date: 2016-09-08



Material Name: TPO Tape Primer SDS 10-3215

### **Dermal Sensitization**

May cause allergic skin reaction.

### **Component Carcinogenicity**

Toluene	108-88-3
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))

### **Germ Cell Mutagenicity**

No information available for the product.

### **Tumorigenic Data**

No data available

### **Reproductive Toxicity**

No information available for the product.

### **Specific Target Organ Toxicity - Single Exposure**

central nervous system

### **Specific Target Organ Toxicity - Repeated Exposure**

No target organs identified.

### **Aspiration hazard**

No information available for the product.

### **Medical Conditions Aggravated by Exposure**

No data available.

### Section 12 - ECOLOGICAL INFORMATION

**Component Analysis - Aquatic Toxicity** 

- v		
Solvent naphtha, petroleum, light aliphatic	64742-89-8	
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID	
Isophorone Diisocyanate	Trade Secret	
Fish:	LC50 96 h Oncorhynchus mykiss 9.22 mg/L	
Invertebrate:	EC50 48 h Daphnia magna 6.14 mg/L IUCLID	
Toluene	108-88-3	
Fish:	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through] (1	



Material Name: TPO Tape Primer SDS 10-3215

	day old); LC50 96 h Pimephales promelas 12.6 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static]; LC50 96 h Oryzias latipes 54 mg/L [static]; LC50 96 h Poecilia reticulata 28.2 mg/L [semi-static]; LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L IUCLID; EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L [static] EPA
Invertebrate:	EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [static] EPA; EC50 48 h Daphnia magna 11.5 mg/L IUCLID
Heat reactive phenolic resin	Trade Secret
Fish:	LC50 96 h Pimephales promelas 0.25 mg/L [flow-through]
Algae:	EC50 72 h Desmodesmus subspicatus 1.1 mg/L IUCLID; EC50 96 h Pseudokirchneriella subcapitata 1.9 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 0.07 - 0.12 mg/L [static] EPA

### Section 13 - DISPOSAL CONSIDERATIONS

### **Disposal Methods**

Dispose of contents/container in accordance with local/regional/national/international regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.

### Section 14 - TRANSPORT INFORMATION

**US DOT Information:** 

**Shipping Name:**ADHESIVES

Hazard Class: 3 UN/NA #: UN1133 Packing Group: II Required Label(s): 3

**IATA Information:** 

**Shipping Name:**ADHESIVES

**Hazard Class:** 3

Page 9 of 12 Issue date: 2015-05-19 Revision 1.0 Print date: 2016-09-08



Material Name: TPO Tape Primer SDS 10-3215

UN#: UN1133 Packing Group: II Required Label(s): 3

**TDG Information:** 

**Shipping Name:**ADHESIVES

Hazard Class: 3 UN#: UN1133 Packing Group: II

### Section 15 - REGULATORY INFORMATION

### **U.S. Federal Regulations**

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Toluene	108-88-3
SARA 313:	1 % de minimis concentration
CERCLA:	1000 lb final RQ; 454 kg final RQ
TSCA 12b:	Section 4, 1 % de minimus concentration (related to Hydrocarbons, C>4)

### SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No

#### **U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes

# The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Toluene	108-88-3
Repro/Dev. Tox	developmental toxicity, 1/1/1991

### **Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Toluene	108-88-3
---------	----------



	1	%									
	<b>ponen</b> ent nap		-		ntory ight aliphati	c (64742-89	-8)				
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes
Isopl	horone	Diiso	cvana	te (Tra	ide Secret)						
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes
Tolu	ene (10	08-88-	.3)		-						
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Chlo	rinated	l nolvi	ronyl	ene (T	rade Secret)	1					
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No
Heat	reactiv	ze nhe	nolic	resin (	Trade Secre	t)					
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Isopl	horond	iamin	e-isob	utvral	dimine (Trac	le Secret)					
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	No	No	Yes	Yes	No
					Section	16 - OTHE	R INFORMATION				



Material Name: TPO Tape Primer SDS 10-3215

Health: 3 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

**NFPA Ratings** 

Health: 3 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**Summary of Changes** New SDS: 4/29/2015

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits: NFPA - National Fire Protection Agency: NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

### **Other Information**

#### Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.