



Gold Bond® Seaspray Hi-Strength MVR® Ceiling Panels

Easy-to-Use Prefinished Decorative Ceiling Panel

Seaspray Hi-Strength MVR® Ceiling Panels provide an attractive textured ceiling and a code-approved moisture/vapor retarder, all in one easy-to-use product.

Seaspray Hi-Strength MVR Ceiling Panels are specialty gypsum panels with increased uniformity and integrity of the gypsum core, making the sag resistance superior to regular gypsum board.

ADVANTAGES

- Vapor retarder characteristics meet code standards of 1 perm or less as required by HUD Manufactured Home Construction and Safety Standards, Section 3280.504(a). (Per NGC test PTL-4-88G.)
- Vapor retarder built into the texture finish ensures uniform performance without the risk of over or underspraying.
- Square-edged linear panels are coated with durable latex texture finish that resists surface marking.
- Bolder, heavier texture helps hide joints.
- Fire-resistant gypsum core panels are UL labeled and meet HUD Manufactured Home Construction and Safety Standards for homeowner security.
- Easy installation. Ceiling panels with built-in vapor retarder eliminate the need for vapor retarder paint, polyethylene or kraft-face insulation, depending on application.
- Improved sag resistance.
- 24" o.c. foam adhesive attachment.
- Built-in vapor barrier.
- Hard painted surface.
- Easy touch-up.
- Achieves GREENGUARD Gold Certification for low chemical emissions.

Seaspray Hi-Strength MVR Ceiling Panels are specifically designed for ceilings where framing members are spaced up to 24" o.c. with mechanical or adhesive attachment methods.

Gold Bond Building Products, LLC warrants Seaspray Hi-Strength MVR with a 5-year limited warranty against sag when foam adhesive attachment is used with trusses spaced 24" o.c.

TECHNICAL DATA

Complies with ASTM C1396 Standard Specification for Gypsum Board

Physical Properties	5/16"	1/2"
Thickness: ASTM permissible variations: +/- 1/64" (0.4 mm) nominal thickness +/- 1/32" (0.8 mm) local nominal thickness	5/16" (9.5 mm)	1/2" (12.7 mm)
Width: ASTM permissible variations: + 0", -3/32" (2.4mm)	4' (1,219 mm)	4' (1,219mm)
Lengths: ASTM permissible variations: +/- 1/4" (6.4mm)	84"-192" (1/2" increments)	84"-192" (1/2" increments)
Corners: ASTM permissible variations: +/- 1/8" (3.2mm) in the full width of the board	Square	Square
Edges:	Square	Square
Weight:	Approx. 1.4 lbs/ sq. ft.	Approx. 1.9 lbs/ sq. ft.
Colorfastness: No significant color change with normal sunlight exposure.		
Surface Burning Characteristics: (per ASTM E 84) (Fire Hazard Classification) Flame Spread Index (15) Smoke Developed: 0		

SIZE & PACKAGING

Thickness	Pieces per skid
5/16" x 4' (9.5 mm x 1,219 mm)	60
1/2" x 4' (12.7 mm x 1,219 mm)	30

Skids are banded and protectively wrapped.



National Gypsum Company is the exclusive service provider for products manufactured by Gold Bond Building Products, LLC.

Gold Bond® Hi-Strength MVR® Seaspray Ceiling Panels are manufactured by Gold Bond Building Products, LLC.



Gold Bond®
Building Products

goldbondbuilding.com