Gold Bond® Shaftliner XP® Gypsum Panels by Gold Bond Building Products, LLC provided by National Gypsum Company

Health Product Declaration v2.2

created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 26788

CLASSIFICATION: 09 29 00 Gypsum Board

PRODUCT DESCRIPTION: Gold Bond® Shaftliner XP® Gypsum Panels consist of a fire-resistant Type X gypsum core encased in a heavy moisture/mold/mildew-resistant, 100% recycled, original PURPLE paper on the face and back sides. Shaftliner XP® are designed to provide extra protection against mold and mildew. The face paper is folded around the long edges to reinforce and protect the core, and the ends are square-cut and finished smooth. Long edges of panels are beveled for ease of installation. Shaftliner XP® are designed to be used to construct lightweight fire barriers for cavity shaftwalls (1-4 hr), stairwells and area separation fire walls in multifamily housing. The panels are key components in the I-Stud, C-T Stud and C-H Stud Cavity Shaftwall Systems and the H-Stud Area Separation Fire Wall Systems. This HPD covers 1" Gold Bond® Shaftliner XP® Gypsum Panels. National Gypsum Company is the exclusive service provider for products manufactured by Gold Bond Building Products, LLC, PermaBASE Building Products, LLC and ProForm Finishing Products, LLC.



Section 1: Summary

Nested Method / Material Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
- C Basic Method

Threshold Disclosed Per

- Material
- Product

Threshold Level

- C 100 ppm
- ⊙ 1,000 ppm
- C Per GHS SDS
- Other

Residuals/Impurities

Considered in 2 of 2 Materials

Explanation(s) provided for Residuals/Impurities?

Yes ○ No

All Substances Above the Threshold Indicated Are: Characterized ⊙ Yes Ex/SC ○ Yes ○ No

% weight and role provided for all substances except SC substances characterized according to SC guidance. Screened ⊙ Yes Ex/SC ○ Yes ○ No

All substances screened using Priority Hazard Lists with results disclosed except SC substances screened according to SC guidance.

Identified

All substances disclosed by Name (Specific or Generic) and Identifier except SC substances identified according to SC guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

GYPSUM CORE [GYPSUM BM-3dg GLASS / MINERAL FIBER LT-UNK STARCH LT-UNK SILOXANES AND SILICONES, DI-ME, POLYMERS WITH 3-MERCAPTOPROPYL SILSESQUIOXANES LT-UNK GLUCOSE BM-3] PAPER FACERS [SC:RECYCLED PAPER Not Screened STARCH LT-UNK 2,5-FURANDIONE, DIHYDRO-, MONO-C15-20-**ALKENYL DERIVS. LT-UNK]**

Number of Greenscreen BM-4/BM3 contents ... 1

Contents highest concern GreenScreen

Benchmark or List translator Score ... LT-UNK

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Special conditions applied: BiologicalMaterial

[LEED v4] "Yes ex/SC" result is due only to materials and substances for which Special Conditions were applied. Thus "Yes ex/SC" does not disqualify the product for the LEED v4 Materials and Resources Disclosure and Optimization credit, Option 1.

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.2, and discloses hazards associated with all substances present at or above 1000 parts per million (ppm) in the finished product, along with the role and percent weight for each substance.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified Other: UL Evaluation Report (UL ER R3501-02)

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1

Third Party Verified? C Yes

PREPARER: Elixir Environmental VERIFIER:

VERIFICATION #:

PUBLISHED DATE: 2021-12-17 EXPIRY DATE: 2024-12-17

SCREENING DATE: 2021-12-17

Gold Bond Shaftliner XP Gypsum Panels hpdrepository.hpd-collaborative.org



This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

GYPSUM CORE %: 96.7000 - 97.3000

MATERIAL THRESHOLD: 1000 ppm RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities were "Considered", as outlined in Emerging Best Practices. No residuals or impurities are known or expected to be present at or above the Content Inventory Threshold indicated that have a GS score of BM-1, LT-1, LT-P1 or NoGS based on information provided in supplier disclosures and as predicted by process chemistry (Pharos CML).

OTHER MATERIAL NOTES: Percent by weight of Material and Substances reported as ranges to account for possible formulation variations between manufacturing facilities.

GYPSUM ID: 13397-24-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-12-17 14:48:56

%: 97.4000 - 99.2000 GS: BM-3dg RC: PreC NANO: No SUBSTANCE ROLE: Structure component

HAZARD TYPE AGENCY AND LIST TITLES WARNINGS

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: GreenScreen Benchmark® assessment score of BM-3dg was provided by the HPD Builder Tool. This product is manufactured at Apollo Beach, FL; Baltimore, MD; Medicine Lodge, KS; Phoenix, AZ; Waukegan, IL; Wilmington, NC. The use of pre-consumer recycled content gypsum, or FGD gypsum, varies by manufacturing location. Please contact manufacturer if more information is required.

GLASS / MINERAL FIBER ID: 65997-17-3

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-12-17 14:48:57

%: 0.2000 - 0.6000 GS: LT-UNK RC: None NANO: No SUBSTANCE ROLE: Structure component

HAZARD TYPE AGENCY AND LIST TITLES WARNINGS

TIAZAND TIFE AGENCT AND LIST TITLES WARNINGS

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

STARCH ID: 65996-63-6

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-12-17 14:48:58

%: **0.2000 - 0.6000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE AGENCY AND LIST TITLES WARNINGS

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

MATERIAL TYPE: Geologically Derived Material

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-12-17 14:48:59

%: 0.0200 - 0.2000 GS: BM-3 RC: None NANO: No SUBSTANCE ROLE: Humectant

HAZARD TYPE AGENCY AND LIST TITLES WARNINGS

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Identified on the US EPA Safer Chemical Ingredient List (Green Circle - Verified Low Concern). GreenScreen Benchmark® assessment score of BM-3 was provided by the HPD Builder Tool.

PAPER FACERS %: 2.7000 - 3.3000

MATERIAL THRESHOLD: 1000 ppm RESIDUALS AND IMPURITIES CONSIDERED: Yes MATERIAL TYPE: Paper or Cardboard

RESIDUALS AND IMPURITIES NOTES: No residuals or impurities are known or expected to be present at or above the Content Inventory Threshold indicated that have a GS score of BM-1, LT-1, LT-P1 or NoGS based on supplier disclosures and as predicted by process chemistry (Pharos CML).

OTHER MATERIAL NOTES: Percent by weight of Material and Substances reported as ranges to account for possible formulation variations between manufacturing facilities.

SC:RECYCLED PAPER ID: SC:Bio HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: Not Screened %: 98.7000 - 99.3000 **GS: Not Screened** RC: PostC NANO: No SUBSTANCE ROLE: Structure component **HAZARD TYPE AGENCY AND LIST TITLES WARNINGS** Hazard Screening not performed

SUBSTANCE NOTES:

Version: SCBioMats/2018-02-23 Category: Tree-based materials

Identifier: 65996-61-4

This disclosure does not provide information on allergens, hyper-accumulation of metals, production of any toxic substances during normal metabolic activities, pesticides, and other potential hazards or sources of hazards which may be found in certain biological materials. 100% of our gypsum board face and back paper is produced with post-consumer recycled content. The company's three paper mills produce paper from discarded cardboard and magazines.

STARCH ID: 9005-25-8 HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-12-17 14:48:57 GS: LT-UNK %: 0.3000 - 0.4000 RC: None NANO: No SUBSTANCE ROLE: Binder **HAZARD TYPE** AGENCY AND LIST TITLES WARNINGS None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Identified on the US EPA Safer Chemical Ingredient List (Green Circle - Verified Low Concern).

2,5-FURANDIONE, DIHYDRO-, MONO-C15-20-ALKENYL DERIVS.

ID: 68784-12-3

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-12-17 14:48:58 %: 0.2000 - 0.3000 GS: LT-UNK RC: None NANO: No SUBSTANCE ROLE: Sizing agent **HAZARD TYPE** AGENCY AND LIST TITLES **WARNINGS** No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Synonym: Alkenyl Succinic Anhydride

None found

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

UL/GreenGuard Gold Certified

CERTIFYING PARTY: Third Party APPLICABLE FACILITIES: AII

ISSUE DATE: 2008-12- EXPIRY DATE: 2021-

CERTIFIER OR LAB: UL

31

12

12-28

Environment

CERTIFICATE URL:

http://certificates.ulenvironment.com/default.aspx?

id=24723&t=cs

CERTIFICATION AND COMPLIANCE NOTES: Certificate Number: 24723-420. UL 2818 - 2013 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings Building products and interior finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office and Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2.

OTHER

UL Evaluation Report (UL ER R3501-02)

CERTIFYING PARTY: Third Party

ISSUE DATE: 2015-06- EXPIRY DATE:

CERTIFIER OR LAB: UL

APPLICABLE FACILITIES: All

CERTIFICATE URL: https://tinyurl.com/zvx9cpfd

CERTIFICATION AND COMPLIANCE NOTES: UL ER R3501-02. SUBJECT: One, Two, Three, and Four-Hour Fire-Resistive Interior Partition Systems; One and Two-Hour Ceiling Assemblies; Two-Hour Horizontal Membrane and Duct Protection Assemblies. The assemblies consist of steel studs and tracks faced with Gold Bond Fire-Shield Shaftliner gypsum board on one side and Gold Bond gypsum board on the other side. SCOPE OF EVALUATION - Compliance with the following codes: 2006, 2009, 2012, 2015 International Building Code (IBC); 2006, 2009, 2012, 2015 International Residential Code (IRC). The products were evaluated for the following properties: Fire-resistance-rated construction; Structural; Physical Properties; Surface Burning Characteristics; Noncombustibility.

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

GOLD BOND® FIRE-SHIELD® GYPSUM BOARDS

HPD URL: https://hpdrepository.hpd-collaborative.org

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Component of Gold Bond® Interior Partition Systems, as referenced in UL Evaluation Report (UL ER R3501-02).

GOLD BOND® FIRE-SHIELD C™ GYPSUM BOARDS

HPD URL: https://hpdrepository.hpd-collaborative.org

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Component of Gold Bond® Interior Partition Systems, as referenced in UL Evaluation Report (UL ER R3501-02).

STEEL FRAMING

HPD URL: No HPD available

HPD URL: No HPD available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Component of Gold Bond® Interior Partition Systems, as referenced in UL Evaluation Report (UL ER R3501-02).

FASTENERS

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

As referenced in UL Evaluation Report (UL ER R3501-02).

Section 5: General Notes

MANUFACTURER INFORMATION

MANUFACTURER: Gold Bond Building Products, LLC provided by

National Gypsum Company ADDRESS: 2001 Rexford Road Charlotte NC 28211, USA

WEBSITE: https://www.goldbondbuilding.com

CONTACT NAME: Amy Hockett

TITLE: Manager - Architectural Services & Sustainability

PHONE: 704-365-7931

EMAIL: AmyH@NationalGypsum.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity **END** Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

LAN Land toxicity

MAM Mammalian/systemic/organ toxicity

MUL Multiple
NEU Neurotoxicity

NF Not found on Priority Hazard Lists

OZO Ozone depletion

PBT Persistent, bioaccumulative, and toxic

PHY Physical hazard (flammable or reactive)

REP Reproductive

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (due to insufficient data)

LT-P1 List Translator Possible 1 (Possible Benchmark-1)

Recycled Types

PreC Pre-consumer recycled content

PostC Post-consumer recycled content

UNK Inclusion of recycled content is unknown

None Does not include recycled content

LT-1 List Translator 1 (Likely Benchmark-1)

LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the

information contained within the list did not result in a clear mapping

to a LT-1 or LTP1 score.)
NoGS No GreenScreen.

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.