



Gold Bond® XP® Hi-Abuse® Gypsum Board
Gold Bond Building Products, LLC
provided by National Gypsum Company

Final Assembly: Multiple Locations in the United States of America

Life Expectancy: 60+ Year(s)

End of Life Options: Recyclable (100%), Landfill (100%)

Ingredients:

Gypsum Core: Gypsum; Paraffin; Vermiculite; STARCH; Continuous Filament Glass Fiber, Non-Respirable; Starch; Siloxanes and Silicones, di-Me, polymers with 3-mercaptopropyl silsesquioxanes; Dextrose; Polignate Sodium; POTASSIUM SULFATE; **Sodium polynaphthalenesulfonate¹**; Boric acid; Tartaric Acid; Metaphosphoric acid (H₃P₃O₉), trisodium salt; Alcohols, C8-10, ethoxylated, sulfates, ammonium salts; **Paper Facers:** Mixed Recycled Paper

¹LBC Temp Exception RL-009 - Formaldehyde

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

NGC-0028

EXP. 01 JUN 2024

Original Issue Date: 2019