





Exclusive service provider of PermaBASE Building Products, LLC





- Fiberglass Mesh/Mat
  Gementitious Core
  EdgeTech\* Reinforced Edge
  Fiberglass Mesh
- PermaBASE UltraBacker® Cement Board features a smooth mesh and mat surface that creates a more rigid and easier to handle product and an improved surface providing superior tile bond. It is ideally suited as an underlayment for ceramic tile on floors, countertops, tub decks and outdoor kitchen counters.

## Features/Benefits:

- Smoother surface/stronger bond
- Moisture & mold resistant
- Easy to cut speeds up installation
- EdgeTech® Reinforced Edge
- GREENGUARD Gold Certification



- Provides an exceptionally hard, durable surface and can
- No need to modify adjacent thresholds when abutting to carpet, wood flooring or other common flooring materials, due to 1/4" (6.4 mm) thickness.
- EdgeTech® Reinforced Edge allows for more secure application of fasteners closer to the edge.
- Works with all brands of thin-sets and grouts.
- Qualifies as a low-VOC emitting material by meeting California Specification 01350.
- Limited lifetime product warranty for interior installations.



## **TECHNICAL DATA**

| Property                              | Method     | Results                     |
|---------------------------------------|------------|-----------------------------|
| Thickness, Nominal                    | ASTM C473  | 1/4" (6.4 mm)               |
| Weight, Nominal                       |            | 1.8 lbs./sq. ft. (8.8 k/m²) |
| Edges                                 |            | Round                       |
| Flexural Strength                     | ASTM C947  | ≥ 1,750 lbf.                |
| Fastener Holding (Wet and Dry)        | ASTM D1037 | ≥ 90 lbs.                   |
| Freeze/Thaw Cycles                    | ASTM C666  | 100                         |
| Compressive Strength                  | ASTM D2394 | N/A                         |
| Thermal Resistance                    | ASTM C518  | R = .2, K = 2.7             |
| Permeance                             | ASTM E96   | > 10 perms                  |
| Water Absorption (% of Weight)        | ASTM C473  | < 8%                        |
| Falling Ball Impact (12" Drop)        | ASTM D1037 | Pass                        |
| Linear Variation with Change Moisture | ASTM D1037 | ≤ 0.07%                     |
| Mold Resistance                       | ASTM D3273 | Score of 10                 |
| Mold Resistance                       | ASTM G21   | Score of 0                  |
| Product Standard Compliance           | ASTM C1325 |                             |
| Fire-Resistance Characteristics       |            |                             |
| Core Type                             |            | N/A                         |
| UL Type Designation                   |            | N/A                         |
| Surface Burning Characteristics       |            | Class A                     |
| Flame Spread                          |            | 0                           |
| Smoke Development                     |            | 0                           |

## SIZE AND PACKAGING

| Thickness, Width and Length                  | Pieces per Unit |
|--|-----------------|
| 1/4" x 36" x 5' (6.4 mm x 914 mm x 1,524 mm) | 60              |

## **TECHNICAL INFORMATION**

Visit **permabase.com** or call National Gypsum Company Construction Services: 1-800-NATIONAL (628-4662).



National Gypsum Company is the exclusive service provider for products manufactured by PermaBASE Building Products, LLC.

PermaBASE UltraBacker® Cement Board is manufactured by PermaBASE Building Products, LLC.



PermaBASE Building Products, LLC 2001 Rexford Road Charlotte, NC 28211 704.365.7300 permabase.com

111354 02/21