


Bowlag Anchor

AR Bowlag Anchors provide an effective and efficient She-Bolt reanchorage for cantilever and Ty back lift forms. The continuous lag thread and the bow shape provide good anchorage even in green concrete and consistently outperforms smooth crimped rods and/or pigtails. The lag thread engagement is quick to install or disconnect. The bow shape prevents loosening during vibration and resists rotating or spinning during stripping.



APPROXIMATE SAFE WORKING LOAD 2:1

To order, please specify the following information

EXAMPLE

Name Bowlag Anchor
 Nominal Diameter 25 mm (1")
 Length 900 mm (36")
 Quantity 200

Anchor diameter	Length "L"	Drop "D"	Working Loads	
			@ 3.5 MPa (500 psi)	@ 4.8 MPa (700 psi)
20 mm (3/4")	600 mm (24")	150 mm (6")	53 kN (12,000 lbs)	71 kN (16,000 lbs)
	750 mm (30")	150 mm (6")	64 kN (14,500 lbs)	80 kN (18,000 lbs)
22 mm (7/8")	750 mm (30")	225 mm (9")	90 kN (20,000 lbs)	102 kN (23,000 lbs)
	900 mm (36")	225 mm (9")	98 kN (22,000 lbs)	111 kN (25,000 lbs)
25 mm (1")	900 mm (36")	225 mm (9")	120 kN (27,000 lbs)	135 kN (30,000 lbs)

