


Heavy Tyscru (4-Strut and 6-Strut)

The AR 6-Strut Heavy Tyscru is available in 32 mm and 38 mm (1¼" and 1½") nominal diameter and may be fabricated to required lengths to the nearest 3 mm (1/8"). The AR 6-Strut Heavy Tyscru is available as a standard or water seal Tyscru for both diameters. A 32mm (1¼") Cone Tight 6-strut Heavy Tyscru is also available.

**APPROXIMATE SAFE
WORKING LOAD**
see table on page 51
2:1 Safety Factor



To order, please specify
the following information

EXAMPLE

Name 4-Strut Heavy Tyscru
Diameter 20 mm (¾")
Length 300 mm (12")
Strength 40 kN (9,000 lbs.)
Quantity 100

Name 6-Strut Heavy Tyscru
Diameter 32 mm (1")
Length 300 mm (12")
Strength 165 kN (37,000 lbs.)
Quantity 200

4-STRUT

Diameter mm (in)	Type	Safe Load	
		kN	(lbs)
*13 mm (½")	9 M	40 kN	(9,000 lbs)
20 mm (¾")	18 M	80 kN	(18,000 lbs)
25 mm (1")	18 M	80 kN	(18,000 lbs)
25 mm (1")	27 M	120 kN	(27,000 lbs)
25 mm (1")	37 M	165 kN	(37,000 lbs)
32 mm (1¼")	27 M	120 kN	(27,000 lbs)
32 mm (1¼")	37 M	165 kN	(37,000 lbs)

6-STRUT

Diameter mm (in)	Safe Load	
	kN	(lbs)
32 mm (1¼")	200 kN	(45,000 lbs)
38 mm (1½")	245 kN	(55,000 lbs)