

# Product Data Sheet

## 7061 Neocrylic (38AJB) Acrylic Wall Coating, Satin Finish



<b>Description:</b>	7061 Neocrylic (Hempel 38AJB) is an acrylic, water-based, decorative, high-hiding, exterior acrylic coating with a satin finish.
<b>Recommended use:</b>	As a protective and decorative exterior coating over masonry, wood, incidental metal surfaces, and Insulation and Finish Systems (EIFS). Recommended areas include exterior walls, ceilings, columns, and beams.
<b>Features:</b>	Meets OTC and EPA VOC requirements.
<b>Availability:</b>	Special order only. Available in North America. Not included in Group Assortment; other regions must confirm.

### Colors and packaging:

7061 (38AJB10000)	White	5-gallon
7061 (38AJB00010)	White Base	

### Physical constants:

Gloss at 60°	12.0	ASTM D523
Weight/gallon	10.74 lbs/gal	ASTM D1475
Weight solids	49.60%	ASTM D4209
Volume solids	35.0%	Calculated
Viscosity	100 KU	ASTM D562
VOC	< 150 g/L	EPA Method 24
Flash point	None	ASTM D3278
Dry time to touch*	0.5–1 hour	
Dry time to recoat*	2–4 hours	
Dry time to full cure*	5 days	
Shelf life	2 years (unopened)	

*\*Times assume 70°F/21°C and 50% relative humidity. The above tested results are typical values. Individual lots may vary up to 10% from the typical value. Further technical information can be found at [www.neogard.com](http://www.neogard.com).*

### Application details:

Application method:	Roller/Brush/Spray (contact Neogard for spray equipment information)
Thinner (max.vol.):	Do not thin
Mixing:	Mix for a minimum of 3–5 minutes before applying
Cleaning of tools:	Water

**Safety:** Handle with care. Use with adequate ventilation. Before and during use, observe all safety labels on packaging and paint containers, consult Neogard Safety Data Sheets and follow all local or national safety regulations.

**Surface preparation:** According to Neogard Guide Specifications.

**Application conditions:** Apply only when substrate or ambient temperatures are above 40°F/4°C. Do not apply if temperatures are expected to fall below 40°F/4°C within 24 hours after application. Do not apply if rain is expected within 24 hours of application.

# Product Data Sheet

## 7061 Neocrylic (38AJB)

### Acrylic Wall Coating, Satin Finish



Note: **7061 is for professional use only.**

Issued by: Hempel (USA) – 38AJB

This Product Data Sheet (“PDS”) relates to the supplied product (“Product”) and is subject to update from time-to-time. Accordingly, the buyer/applicator should refer to the PDS current as of the time of delivery. In addition to the PDS, the buyer/applicator may receive some or all of the specifications, statements and/or guidelines listed below or available at [www.neogard.com](http://www.neogard.com) (the “Additional Documents”):

No.	Document Description
1	PDS
2	Guide Specification
3	Application Manual
4	Other Technical Support Information (i.e. summary application tables, troubleshooting guides, maintenance manuals, chemical resistance charts and other technical information )

In the event of a conflict between this PDS and the Additional Documents, the conflict shall be resolved in accordance with the order of priority set forth above. In addition, the buyer/applicator should refer to the relevant Safety Data Sheet current as of the time of delivery and available at [www.neogard.com](http://www.neogard.com). Buyer/applicator is responsible for determining the suitability of the intended use of the Product, and Neogard disclaims all responsibility for any use, handling and storage of the Product that is not in accordance with the requirements set forth in the relevant PDS and the Additional Documents. The terms and provisions hereof apply to this PDS, the Additional Documents and any other documents supplied by Neogard in respect of the Product. The Product is supplied and all technical assistance is given subject to the General Conditions of Sale of Hempel Products and/or Services available at [www.hempel.com](http://www.hempel.com). NEOGARD MAKES NO OTHER WARRANTY THAT EXTENDS BEYOND THE WARRANTY REFERENCED THEREIN INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. NEOGARD WILL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR BREACH OF ANY EXPRESS OR IMPLIED WARRANTY OR CONDITION, OR THAT IN ANY WAY ARISE IN RELATION TO THE PRODUCT. 7061-PDS ksk 11292021.docx

Neogard®, a part of Hempel  
2728 Empire Central - Dallas, Texas 75235 - Phone (214) 353-1600 - Fax (214) 357-7532 - [www.neogard.com](http://www.neogard.com)