Revision Date: 09-30-2015 **Product Code:** 70714-02

1. IDENTIFICATION

Product Name EPOXY RESIN GRAY

 Product Code
 70714-02

 Document ID
 G70714-02

Revision Number 2

Prior Version Date 06-05-2015

Industrial Maintenance Floor Coating

Restrictions On Use For Industrial Use Only

Chemical Family Epoxy Coating

Chemical Manufacturer / Importer NEOGARD® - a Division of JONES-BLAIR® Company, LLC

2728 Empire Central Dallas, TX 75235 1-214-353-1600

Emergency Telephone Number: ChemTrec Center 1-800-424-9300

International: 703-527-3887

2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

Hazard Pictograms



GHS Classification Skin Sensitisation Category 1

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2

Carcinogenicity Category 2

Signal Word Warning

Hazard Statements Causes skin irritation. May cause an allergic skin reaction. Causes serious eye

irritation. Suspected of causing cancer.

Precautionary Statements

Prevention Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Avoid breathing dust, fume, mist, vapours or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as

required.

Response IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing and wash before reuse.

Storage Store locked up.

Revision Date: 09-30-2015 **Product Code:** 70714-02

Disposal Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Hazards Not Otherwise Classified (HNOC)

Not applicable

Additional Information

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Component	CAS#	<u>%</u>	
Bisphenol-A-diglycidylether	25068-38-6	50 - 70	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	68609-97-2	7 - 13	
Titanium dioxide	13463-67-7	5 - 10	
Carbon black	1333-86-4	0.1 - 1	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation Remove to fresh air. If breathing is difficult, have a trained individual administer

oxygen.

Eye Contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Get medical attention immediately.

Skin Contact Wash with soap and water. Remove contaminated clothing and launder. Get medical

attention if irritation develops or persists. Thoroughly wash or discard clothing and

shoes before reuse.

Ingestion If swallowed, do not induce vomiting. Get medical attention immediately.

Most Important Acute Symptoms

and Effects

Not Available

Most Important Delayed Symptoms

and Effects

Not Available

Special treatment needed: Pre-existing disorders of the following organs may be aggravated by

exposure to this material: skin, lung (for example, asthma-like symptoms)

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use alcohol foam, carbon dioxide, or water spray when fighting fires

involving this material.

Unsuitable Extinguishing Media Fire and/or Explosion Hazards

No data available

Material may be ignited only if preheated to temperatures above the

high flash point, for example in a fire.

Special Protective Equipment and Precautions for Fire-Fighters

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Do not enter fire area without proper protection including self- contained breathing

apparatus and full protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special

Revision Date: 09-30-2015 **Product Code:** 70714-02

circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material.

Gather and store in a sealed container pending disposal.

Methods and Material for Containment

and Cleaning Up

7. HANDLING AND STORAGE

Precautions for Safe Handling Harmful or irritating material. Avoid contacting and avoid breathing the

material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this

material

Conditions for Safe Storage Store in a cool dry place. Keep container(s) closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Talc	2mg/m³ (Respirable Dust)	20 mppcf TWA	
Titanium dioxide	15 mg/m³ TWA (total dust)	10 mg/m³ TWA	
Carbon black	3.5 mg/m3 TWA	3.5 mg/m3 TWA	

Appropriate Local exhaust ventilation or other engineering controls may be required when handling or

Engineering Controls using this product to avoid overexposure.

Respiratory Protection General or local exhaust ventilation is the preferred means of protection. In cases where

ventilation is inadequate, respiratory protection may be required to avoid overexposure.

Follow respirator manufacturer's directions for respirator use.

Eye Protection Wear safety glasses with side shields when handling this product. Wear additional eye

protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.

Skin Protection Where use can result in skin contact, practice good personal hygiene. Wash hands and

other exposed areas with mild soap and water before eating, drinking, and when leaving

work. Clothing suitable to prevent skin contact.

General Hygiene As with all chemicals, good industrial hygiene practices should be followed when

Conditions handling this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical State Liquid

Odor No data available
Odor Threshold No data available
pH No data available

Melting Point/Freezing Point (F/℃) No data available / No data available

Initial Boiling Point and Boiling Range

Low (♥) 392.0 High (♥) 392.0 Flash Point (♥/♥) 201 / 94

Flammability (solid, gas)
Upper Flammable/Explosive Limit
Lower Flammable/Explosive Limit
No data available
No data available

Revision Date: 09-30-2015 Product Code: 70714-02

Vapor Pressure < 13.30 PA @ 77°F (25°C)

Vapor Density No data available

Relative Density 1.000

Solubility in Water
Partition coefficient: n-octanol/water
Auto-ignition Temperature:
No data available
1,800 - 2,400 CPS

Volatiles, % by volume 1.45 Volatiles, % by weight 0.89

Volatile Organic Chemicals (g/L)

(Regulatory, Calculated) 10.96 (Actual, Calculated) 10.95

Density 10.74 - 11.04 lbs./Gal

10. STABILITY AND REACTIVITY

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions No data available

Conditions to Avoid

Temperatures above the high flash point of this combustible

material in combination with sparks, open flames, or other sources of ignition. Contamination.

11. TOXICOLOGICAL INFORMATION

Routes of Exposure Eye contact

Skin contact Inhalation

Immediate (Acute) Health Effects by Route of Exposure

Inhalation IrritationCauses nose and throat irritation. Inhalation of dusts produced during

cutting, grinding or sanding of this product may cause irritation of the

respiratory tract.

Skin ContactCan cause moderate skin irritation. May cause allergic skin reaction.

Eye Contact Causes eye irritation.

Long-Term (Chronic) Health Effects

Carcinogenicity Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic

to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals. Possible cancer hazard. Contains carbon black which may cause cancer based on animal data. (Risk of cancer depends on duration and level of

exposure.)

Skin Contact Prolonged contact may cause an allergic skin reaction.

Product Toxicology Data

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol-A-diglycidylether	Oral LD50 Rat > 15,000	Dermal LD50 Rabbit	
	mg/kg	23,000 mg/kg	
Talc	Oral LD50 Rat > 5000	Dermal LD50 Rabbit >	Inhalation LC50 (4h) Rat >
	mg/kg	5000 mg/kg	20.00 mg/L
Oxirane, mono[(C12-14-	Oral LD50 Rat > 2000	Dermal LD50 > 2000 mg/kg	Inhalation LC50 > 20.00
alkyloxy)methyl] derivatives	mg/kg		mg/L
Titanium dioxide	Oral LD50 Rat > 25,000	Dermal LD50 Rabbit >	Inhalation LC50 (4h) Rat >
	mg/kg	10,000 mg/kg	6.82 mg/L
Carbon black	Oral LD50 Rat > 8000	Dermal LD50 Rabbit >	

Revision Date: 09-30-2015 Product Code: 70714-02

mg/kg 2000 mg/kg

Carcinogen Information

Chemical Name IARC Carcinogen OSHA Carcinogen NTP Carcinogen

Talc2BTitanium dioxide2BCarbon black2B

12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available)

No data available

Mobility in soil No data available

13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste Refer to other sections of this SDS to determine the toxicity and physical

characteristics of the material to determine the proper waste

identification and disposal in compliance with applicable regulations.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint, Not-Regulated

Marine Pollutant: No

15. REGULATORY INFORMATION

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the

inventory notification requirements.

Regulated Components

SARA EHS ChemicalsCAS #%Epichlorohydrin106-89-8< 10 ppm</td>

CERCLA

Not applicable

SARA 313

Not applicable

SARA 311/312

Health (Acute): Y
Health (chronic): Y
Fire (Flammable): N
Pressure: N
Reactivity: N

U. S. State Regulations:

California Prop 65 Chemicals

 Cancer
 CAS #
 %

 Titanium dioxide
 13463-67-7
 5 - 10

Revision Date: 09-30-2015 **Product Code:** 70714-02

 Carbon Black
 1333-86-4
 0.1 - 1

 Ethyl Benzene
 100-41-4
 < 10 ppm</td>

 Phenyl glycidyl ether
 122-60-1
 < 10 ppm</td>

 1-Chloro-2,3-epoxypropane
 106-89-8
 < 10 ppm</td>

 Crystalline Silica
 14808-60-7
 < 10 ppm</td>

Reproductive Not applicable

Canadian Regulations:

CEPA DSL: The components of this product ARE listed on the Canadian Domestic Substances

List.

WHMIS Hazard Class: D2A

16. OTHER INFORMATION

Revision Date Disclaimer

09-30-2015

This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.