

Safety Data Sheet

Revision Date: 06-15-2015
Product Code: 45204

1. IDENTIFICATION

Product Name	ACRYLITHANE HS2 ENAMEL RED SPRAY
Product Code	45204
Document ID	G45204
Revision Number	1
Prior Version Date	None
Intended Use	Industrial Maintenance Coating
Restrictions On Use	For Industrial Use Only
Chemical Family	Acrylic Urethane Enamel
Chemical Manufacturer / Importer	JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

Hazard Pictograms



GHS Classification

Skin Sensitisation Category 1
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Carcinogenicity Category 2
Flammable Liquid Category 3

Signal Word

Warning

Hazard Statements

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer.

Precautionary Statements

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, mist, vapours or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required.

Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for

Safety Data Sheet

Revision Date: 06-15-2015

Product Code: 45204

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.

Storage

Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards Not Otherwise Classified (HNOC)

Not applicable

Additional Information

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Component</u>	<u>CAS #</u>	<u>%</u>
Ethyl 3-ethoxypropionate	763-69-9	10 - 30
Methyl Amyl Ketone	110-43-0	7 - 13
n-Butyl acetate	123-86-4	3 - 7
Butyl carbitol acetate	124-17-4	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation	Remove individual to fresh air after an airborne exposure if any symptoms develop as a precautionary measure.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.

Most Important Acute Symptoms and Effects Not Available

Most Important Delayed Symptoms and Effects Not Available

Special treatment needed: No additional first aid information available

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.
Unsuitable Extinguishing Media	No data available
Fire and/or Explosion Hazards	Vapors may be ignited by sparks, flames or other sources of ignition if

Safety Data Sheet

Revision Date: 06-15-2015

Product Code: 45204

**Hazardous Combustion Products
Special Protective Equipment and
Precautions for Fire-Fighters**

material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.
Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases
Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.
Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and Material for Containment and Cleaning Up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Remove contaminated clothing and wash before reuse. Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.

Conditions for Safe Storage

Materials to Avoid/Chemical Incompatibility

Oxidizing agents, Caustics (bases, alkalis), Acids

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
Methyl Amyl Ketone	100ppm; 465mg/m ³ (TWA)	50ppm; 233mg/m ³ TWA	
n-Butyl acetate	150 ppm TWA; 710 mg/m ³ TWA	150 ppm TWA; 713 mg/m ³ TWA	200 ppm STEL; 950 mg/m ³ STEL
Ferric oxide (Nuisance Dust)	10 mg/m ³ TWA	as Fe: 5 mg/m ³ TWA (welding fumes, dust, total particulate (N.O.C.))	

Safety Data Sheet

Revision Date: 06-15-2015

Product Code: 45204

Titanium dioxide	15 mg/m ³ TWA (total dust)	10 mg/m ³ TWA	
------------------	---------------------------------------	--------------------------	--

Appropriate Engineering Controls	Use local exhaust ventilation or other engineering controls to minimize exposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Explosion proof exhaust ventilation should be used.
Respiratory Protection	General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use.
Eye Protection	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
Skin Protection	Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.
General Hygiene Conditions	As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Remove contaminated clothing and wash before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical State	Liquid
Color	Red
Odor	Ester-Like
Odor Threshold	No data available
pH	No data available
Melting Point/Freezing Point (F/°C)	No data available / No data available
Initial Boiling Point and Boiling Range	
Low (°F)	244.0
High (°F)	456.0
Flash Point (F/°C)	103 / 39
Evaporation Rate	0.40 (n-Butyl Acetate = 1.0)
Flammability (solid, gas)	No data available
Upper Flammable/Explosive Limit	7.9 %
Lower Flammable/Explosive Limit	1.6
Vapor Pressure	8.00 mbar
Vapor Density	4.00 4.00 (air = 1)
Relative Density	4.500
Solubility in Water	Minimal; 1-9%
Partition coefficient: n-octanol/water	No data available
Auto-ignition Temperature	No data available
Decomposition Temperature:	No data available
Viscosity	35 - 45 Zz
Volatiles, % by volume	50.51
Volatiles, % by weight	36.72
Volatile Organic Chemicals (g/L)	
(Regulatory, Calculated)	449.11
(Actual, Calculated)	449.10
Density	10.01 - 10.41 lbs./Gal

10. STABILITY AND REACTIVITY

Chemical stability	Stable under normal conditions.
---------------------------	---------------------------------

Safety Data Sheet

Revision Date: 06-15-2015
Product Code: 45204

**Possibility of Hazardous Reactions
Conditions to Avoid**

No data available
Temperatures above flash point in combination with sparks, open flames, or other sources of ignition. Contamination.

**Incompatible Materials
Hazardous Decomposition Products**

Oxidizing agents, Caustics (bases, alkalis), Acids
Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases

11. TOXICOLOGICAL INFORMATION

Routes of Exposure Inhalation
Ingestion
Skin contact
Eye contact

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.
Inhalation Toxicity Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.
Skin Contact Can cause moderate skin irritation.
Skin Absorption May be harmful if absorbed through skin.
Eye Contact Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible.
Ingestion Toxicity Harmful if swallowed.

Long-Term (Chronic) Health Effects Carcinogenicity

Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals.
Inhalation NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Product Toxicology Data

Oral Acute Toxicity Estimate (ATE) 4,106.04 mg/kg
Inhalation Vapor Acute Toxicity Estimate (ATE) 86.64 mg/L

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl 3-ethoxypropionate	Oral LD50 Male Rat > 5000 mg/kg Oral LD50 Female Rat ~ 4309 mg/kg	Dermal LD50 Rabbit ~ 4080 - 4680 mg/kg	Inhalation LC50 (6h) Male Rat > 998.00 mg/L
Methyl Amyl Ketone	Oral LD50 Rat 1600 mg/kg	Dermal LD50 Rabbit 10,206 mg/kg	Inhalation LC50 (4h) Rat > 16.70 mg/L
n-Butyl acetate	Oral LD50 Rat 10,760 mg/kg	Dermal LD50 Rat 12,789 mg/kg	Inhalation LC50 (4h) Rat > 21.00 mg/L
Ferric oxide	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Butyl carbitol acetate	Oral LD50 Rat 6500 mg/kg	Dermal LD50 Rabbit 14,500 mg/kg	Inhalation LC50 (4h) Rat 72.50 mg/L
Titanium dioxide	Oral LD50 Rat > 25,000 mg/kg	Dermal LD50 Rabbit > 10,000 mg/kg	Inhalation LC50 (4h) Rat > 6.82 mg/L

Safety Data Sheet

Revision Date: 06-15-2015
Product Code: 45204

Carcinogen Information

Chemical Name	IARC Carcinogen	OSHA Carcinogen	NTP Carcinogen
Titanium dioxide	2B		

12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available)	No data available
Mobility in soil	No data available

13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Combustible Liquid, n.o.s. (contains n-Amyl methyl ketone, butyl acetates)
Hazard Class: 3
UN Number: NA1993
Packing Group: III
Other: Not regulated for non-bulk domestic ground shipments for packaging of 450 liters (119 gallons) or less (DOT 49CFR 173.150(f)).

IATA Air Shipping Name: Paint
IATA Hazard Class: 3
IATA UN Number: UN1263
IATA Packing Group: III

Marine Pollutant: No

15. REGULATORY INFORMATION

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

Regulated Components

<u>SARA EHS Chemicals</u>	<u>CAS #</u>	<u>%</u>
Not applicable		
<u>CERCLA</u> n-Butyl Acetate	123-86-4	3 - 7
<u>SARA 313</u> 2-(2-Butoxyethoxy)ethyl acetate	124-17-4	1 - 5
<u>SARA 311/312</u> Health (Acute):	Y	
Health (chronic):	Y	
Fire (Flammable):	Y	
Pressure:	N	
Reactivity:	N	

Safety Data Sheet

Revision Date: 06-15-2015
Product Code: 45204

U. S. State Regulations:

California Prop 65 Chemicals

Cancer	CAS #	%
Titanium dioxide	13463-67-7	1 - 5
Ethyl Benzene	100-41-4	0.01 - 0.1
Benzene	71-43-2	< 1 ppm

Reproductive		
Toluene	108-88-3	0.001- 0.01
Benzene	71-43-2	< 1 ppm

Canadian Regulations:

CEPA DSL: The components of this product ARE listed on the Canadian Domestic Substances List.

WHMIS Hazard Class: B3 D2A

16. OTHER INFORMATION

Revision Date 06-15-2015

Disclaimer This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.