

Safety Data Sheet

Revision Date: 08-28-2015
Product Code: 45191

1. IDENTIFICATION

Product Name	ACRYLITHANE HS2 ENAMEL CVX RED (31 RED)
Product Code	45191
Document ID	G45191
Revision Number	1
Prior Version Date	None
Intended Use	Industrial Maintenance Coating
Restrictions On Use	For Industrial Use Only
Chemical Family	Acrylic Urethane Enamel
Chemical Manufacturer / Importer	JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

Hazard Pictograms



GHS Classification

Skin Sensitisation Category 1
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2
Carcinogenicity Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 2
Flammable Liquid Category 3

Signal Word

Warning

Hazard Statements

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. May cause damage to organs.

Precautionary Statements

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fume, mist, vapours or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required.

Safety Data Sheet

Revision Date: 08-28-2015

Product Code: 45191

Response	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. IF exposed or if you feel unwell: Call a POISON CENTER or physician. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.
Storage	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards Not Otherwise Classified (HNOC)	Not applicable

Additional Information

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Component	CAS #	%
Methyl Amyl Ketone	110-43-0	7 - 13
Ethyl 3-ethoxypropionate	763-69-9	7 - 13
Ethylene glycol monobutyl ether acetate	112-07-2	1 - 5
Light aromatic solvent naphtha	64742-95-6	0.5 - 1.5
Butyl carbitol acetate	124-17-4	0.5 - 1.5
Xylene	1330-20-7	0.5 - 1.5
3-Oxazolidineethanol, 2-(1-methylethyl)-	28770-01-6	0.1 - 1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation	Remove individual to fresh air after an airborne exposure if any symptoms develop as a precautionary measure.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

Most Important Acute Symptoms and Effects Not Available

Safety Data Sheet

Revision Date: 08-28-2015
Product Code: 45191

Most Important Delayed Symptoms and Effects Not Available
Special treatment needed: No additional first aid information available

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.

Unsuitable Extinguishing Media No data available

Fire and/or Explosion Hazards Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.

Hazardous Combustion Products Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases, Sulfur containing gases

Special Protective Equipment and Precautions for Fire-Fighters Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and Material for Containment and Cleaning Up Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

7. HANDLING AND STORAGE

Precautions for Safe Handling Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Remove contaminated clothing and wash before reuse.

Conditions for Safe Storage Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.

Materials to Avoid/Chemical Incompatibility Oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Safety Data Sheet

Revision Date: 08-28-2015
Product Code: 45191

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
Methyl Amyl Ketone	100ppm; 465mg/m ³ (TWA)	50ppm; 233mg/m ³ TWA	
Ethylene glycol monobutyl ether acetate		20ppm TWA	
Xylene	100 ppm TWA; 435 mg/m ³ TWA	100 ppm TWA; 434 mg/m ³ TWA	150 ppm STEL; 651 mg/m ³ STEL
Ethylbenzene	100 ppm TWA; 435 mg/m ³ TWA	100 ppm TWA; 434 mg/m ³ TWA	125 ppm STEL; 543 mg/m ³ STEL

Appropriate Engineering Controls	Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Explosion proof exhaust ventilation should be used.
Respiratory Protection	General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use.
Eye Protection	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
Skin Protection	Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where splashing is possible, full chemically resistant protective clothing including a full chemically resistant suit and boots are required
General Hygiene Conditions	As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Remove contaminated clothing and wash before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical State	Liquid
Color	Red
Odor	No data available
Odor Threshold	No data available
pH	No data available
Melting Point/Freezing Point (°F/°C)	No data available / No data available
Initial Boiling Point and Boiling Range	
Low (°F)	300.0
High (°F)	456.0
Flash Point (°F/°C)	102 / 39
Evaporation Rate	0.40 (n-Butyl Acetate = 1.0)
Flammability (solid, gas)	No data available
Upper Flammable/Explosive Limit	7.9 %
Lower Flammable/Explosive Limit	0.5
Vapor Pressure	2.10 (air = 1)
Vapor Density	3.90 (air = 1)
Relative Density	4.500
Solubility in Water	Minimal; 1-9%
Partition coefficient: n-octanol/water	No data available
Auto-ignition Temperature	No data available
Decomposition Temperature:	No data available

Safety Data Sheet

Revision Date: 08-28-2015
Product Code: 45191

Viscosity	25 - 30 Z3
Volatiles, % by volume	45.21
Volatiles, % by weight	33.50
Volatile Organic Chemicals (g/L)	
(Regulatory, Calculated)	398.10
(Actual, Calculated)	398.10
Density	9.82 - 10.02 lbs./Gal

10. STABILITY AND REACTIVITY

Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	No data available
Conditions to Avoid	Temperatures above flash point in combination with sparks, open flames, or other sources of ignition. Contamination.
Incompatible Materials	Oxidizing agents
Hazardous Decomposition Products	Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases, Sulfur containing gases

11. TOXICOLOGICAL INFORMATION

Routes of Exposure	Inhalation Ingestion Skin contact Eye contact
---------------------------	--

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Toxicity	Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.
Skin Contact	Can cause moderate skin irritation.
Skin Absorption	May be harmful if absorbed through skin.
Eye Contact	Causes eye irritation.
Ingestion Toxicity	Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Long-Term (Chronic) Health Effects

Carcinogenicity	Possible cancer hazard. Contains ethylbenzene which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.)
Reproductive and Developmental Toxicity	Xylene may cause adverse reproductive and/or developmental effects. Pregnant women may be at an increased risk from exposure.
Mutagenicity	Xylene has been shown to be positive in mutagenicity assays.
Inhalation	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Product Toxicology Data

Oral Acute Toxicity Estimate (ATE)	2,705.78 mg/kg
Inhalation Dust/Mist Acute Toxicity Estimate (ATE)	37.95 mg/L
Inhalation Vapor Acute Toxicity Estimate (ATE)	30.46 mg/L
Dermal Acute Toxicity Estimate (ATE)	21,191.41 mg/kg

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Methyl Amyl Ketone	Oral LD50 Rat 1600 mg/kg	Dermal LD50 Rabbit 10,206 mg/kg	Inhalation LC50 (4h) Rat > 16.70 mg/L

Safety Data Sheet

Revision Date: 08-28-2015

Product Code: 45191

Ethyl 3-ethoxypropionate	Oral LD50 Male Rat > 5000 mg/kg Oral LD50 Female Rat ~ 4309 mg/kg	Dermal LD50 Rabbit ~ 4080 - 4680 mg/kg	Inhalation LC50 (6h) Male Rat > 998.00 mg/L
Ethylene glycol monobutyl ether acetate	Oral LD50 Rat 1880 mg/kg	Dermal LD50 Rabbit 1500 mg/kg	Inhalation LC50 (6h) Rat > 4.59 mg/L
Light aromatic solvent naphtha	Oral LD50 Rat 8400 mg/kg	Dermal LD50 Rat > 2000 mg/kg	Inhalation LC50 (4h) Rat 5.60 mg/L
Butyl carbitol acetate	Oral LD50 Rat 6500 mg/kg	Dermal LD50 Rabbit 14,500 mg/kg	Inhalation LC50 (4h) Rat 72.50 mg/L
Xylene	Oral LD50 Rat 3523 mg/kg	Dermal LD50 Rabbit 1100 mg/kg	Inhalation LC50 (4h) Rat 11.00 mg/L
Ethylbenzene	Oral LD50 Rat 3500 mg/kg	Dermal LD50 Rabbit 5510 mg/kg	Inhalation LC50 (4h) Rat 17.00 mg/L

Carcinogen Information

Chemical Name

Ethylbenzene

IARC Carcinogen

2B

OSHA Carcinogen

NTP Carcinogen

12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available) No data available

Mobility in soil No data available

13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste

Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint
Hazard Class: 3
UN Number: UN1263
Packing Group: III
Other: Not regulated for non-bulk domestic ground shipments for packaging of 450 liters (119 gallons) or less (DOT 49CFR 173.150(f)).

Marine Pollutant: No

15. REGULATORY INFORMATION

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

Regulated Components

SARA EHS Chemicals

Not applicable

CAS #

%

CERCLA

Safety Data Sheet

Revision Date: 08-28-2015
Product Code: 45191

Xylene (mixed isomers)	1330-20-7	0.5 - 1.5
Ethyl Benzene	100-41-4	0.1 - 1

SARA 313

Ethylene glycol monobutyl ether acetate	112-07-2	1 - 5
2-(2-Butoxyethoxy)ethyl acetate	124-17-4	0.5 - 1.5
Xylene (mixed isomers)	1330-20-7	0.5 - 1.5
Ethylbenzene	100-41-4	0.1 - 1

SARA 311/312

Health (Acute):	Y
Health (chronic):	Y
Fire (Flammable):	Y
Pressure:	N
Reactivity:	N

U. S. State Regulations:

California Prop 65 Chemicals

Cancer	CAS #	%
Ethyl Benzene	100-41-4	0.1 - 1
Cumene	98-82-8	0.01 - 0.1
Benzene	71-43-2	0.001- 0.01
Reproductive		
Toluene	108-88-3	0.001- 0.01
Benzene	71-43-2	0.001- 0.01

Canadian Regulations:

CEPA DSL: The components of this product ARE listed on the Canadian Domestic Substances List.

WHMIS Hazard Class: B3 D2A

16. OTHER INFORMATION

Revision Date	08-28-2015
Disclaimer	This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.