MAINTENANCE
DURO-POLISH & DURO-POLISH PLUS

Duro-Polish and Duro-Polish Plus are a synthetic polymer floor polishes that provide an, ultra-high gloss, slip resistant finish that is scuff and scratch resistant. Low molecular weight allows deep penetration and the unique metal cross-linked chemistry allows for easy removal. In addition, Duro-Polish Plus contains a fluoropolymer additive that provides stain protection from water and oil-based stains.

CLEANING DO'S AND DON'TS

- **DO** use a neutral based detergent cleaner such as **ZEP Commercial Neutral Floor Cleaner Concentrate,** diluted according to manufacturer's instructions for periodic cleaning. The use of any other floor cleaning products should be test applied before full scale cleaning to ensure compatibility.
- **DO** clean and sweep more in the winter time. Salt, sand, and gravel tracked in from outside cause more wear and tear on the surface.
- **DO** wipe up spills and stains immediately, even on a Duro-Polish Plus treated surface to prevent permanent staining or concrete etching.
- **DON'T** use ammonia or any amine containing detergents to clean a Duro-Polish or Duro-Polish Plus treated floor. This will cause irreparable damage, necessitating stripping, followed by reapplication.
- **DON'T** perform regular maintenance with aggressive pads such as diamond impregnated polishing pads. The use of aggressive polish pads will cause fading and loss of stain protection.
- **DON'T** clean or polish with wax.

TOUCH UPS

- Dry buffing with a white felt polishing pad restores gloss and removes scratches and scuff marks.

REAPPLICATION

- Frequency of reapplication depends on use conditions. Floors treated with Duro-Nox and Duro-Polish generally become glossier through use over time.
- To restore the high gloss appearance, clean the floor thoroughly and apply a light coat of Duro-Polish or Duro-Polish Plus following the original application procedures.
- Refer to product data sheet for application instructions.

Contact Nox-Crete for further information or more specific questions

402-341-2080 | customerservice@nox-crete.com | www.nox-crete.com