

DURO-POLISH STRIPPER

New generation, water based stripper specially designed for the removal of DURO-POLISH.



VOLATILE ORGANIC COMPOUND (VOC) REGULATORY COMPLIANCE

USEPA CARB-SCM SCAQMD LADCO, OTC UT-R307, CO MCAQMD CT, MD, DE, D.C. CANADA

DURO-POLISH STRIPPER



HOW IT WORKS

DURO-POLISH STRIPPER is a unique floor stripper designed specially for removing DURO-POLISH synthetic polymer floor polish. DURO-POLISH STRIPPER chemically “unzips” the DURO-POLISH polymer molecule, allowing it to be quickly and easily removed from the floor surface.

APPLICATIONS

- ◆ For use on any substrate that has been previously treated with DURO-POLISH.

ADVANTAGES

- ◆ Water based.
- ◆ 100% biodegradable.
- ◆ Low odor.
- ◆ Can be diluted with water.
- ◆ Will return concrete to its original appearance prior to application of DURO-POLISH.

⚠ PRECAUTIONS ⚠

- ◆ Protect from freezing. If allowed to freeze, product packaging may rupture and the emulsion stability of this product may be affected, making it difficult to keep product mixed during application. Product which is suspected of freezing should not be used.
- ◆ Verify that product is within the “USE BY” date stated on product packaging. Do not use expired product. The use of expired product may result in poor product performance or failure.

USE INSTRUCTIONS

- ◆ Request current product literature, labels and safety data sheets from manufacturer and read thoroughly before product use.
- ◆ Site environmental conditions, substrate conditions and construction have a major effect on product selection, application methods, procedures and rates, appearance and performance. Product literature provides general information applicable to some conditions. However, an adequate site test application by the purchaser or installer in advance of field scale use is mandatory (irrespective of any other verbal or written representations) to verify that product and quantities purchased can be satisfactorily applied and will achieve desired appearance and performance under intended use conditions.

- ◆ May be diluted with water prior to use. Dilute 1 part DURO-POLISH STRIPPER by volume with 2-3 parts volume of water (actual dilution ratio to be determined by site test applications). Typically, light application of DURO-POLISH can be removed using a dilution ratio of 1 part DURO-POLISH STRIPPER to 3 parts water. Applications of several heavy coats of DURO-POLISH may require using DURO-POLISH STRIPPER with no dilution.
- ◆ Mix well before use.
- ◆ Apply with a mop, floor scrubbing machine or a low pressure hand sprayer, such as the NOX-CRETE PERFECT FORM AND CONCRETE SPRAYER.
- ◆ After application to the floor, scrub with a floor scrubbing machine using 3M Black Stripper Pad 7200 or 3M Black High Productivity Stripper Pad 7300.
- ◆ Rinse with clean water. Squeegee dry.

TECHNICAL DATA

Color	Colorless
Clarity	Clear
Odor	Slight ammonia smell
Bulk Density	8.34 lbs / gal (1.0 kg / L)

PACKAGING

Packaged in 1 gal (3.8 L) jugs and 5 gal (19 L) pails.

SHELF LIFE

Shelf life is two years. Use before the “USE BY” date stated on product packaging.

HANDLING/STORAGE

Store in a dry location within a temperature range between 40° F (4° C) and 100° F (38° C).

AVAILABILITY & TECHNICAL SERVICES

In addition to corporate offices in Omaha, Nebraska, NOX-CRETE INC. maintains regional offices and distribution centers in principal markets throughout the world. For source or technical information, call 800-669-2738 or 402-341-2080.

DURO-POLISH STRIPPER

Floor Polish Remover



chemical solutions to concrete problems

LIMITED WARRANTY

NOTICE-READ CAREFULLY

CONDITIONS OF SALE

NOX-CRETE offers this product for sale subject to, and Buyer and all users are deemed to have accepted, the following conditions of sale and limited warranty which may only be varied by written agreement of a duly authorized corporate officer of NOX-CRETE. No other representative of or for NOX-CRETE is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

NOX-CRETE warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, NOX-CRETE will replace the defective product with new product without charge to the purchaser.

NOX-CRETE makes NO OTHER WARRANTY, either express or implied, concerning this product. There is NO WARRANTY OF MERCHANTABILITY. In no case shall NOX-CRETE be liable for special, indirect or consequential damages resulting from the use or handling of the product and no claim of any kind shall be greater in amount than the purchase price of the product in respect of which damages are claimed.

INHERENT RISKS

NOX-CRETE MAKES NO WARRANTY WITH RESPECT TO THE PERFORMANCE OF THE PRODUCT AFTER IT IS APPLIED BY THE PURCHASER, AND PURCHASER ASSUMES ALL RISKS ASSOCIATED WITH THE USE OR APPLICATION OF THE PRODUCT.