

Section 1. Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Product Form	Mixture
Trade Name	NATRASEAL LVOC
Product Code	NTLV

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use Industrial. For professional use only.

1.2.2 Uses Advised Against

No additional information available

1.3 Details of the supplier of the safety data sheet**Manufacturer**

NOX-CRETE MANUFACTURING INC
1444 SOUTH 20TH STREET
OMAHA, NE 68108
Tel: 402-341-2080
Fax: 402-341-9752
E-Mail: corporate@nox-crete.com
Web Site: www.nox-crete.com

1.4 Emergency telephone number**Emergency Number**

Chemtrec (800) 424-9300
Chemtrec Outside of U.S. 703-527-3887

Section 2. Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Regulations 29CFR 1910.1200 , (EC) No. 1272/2008(CLP)(GHS)

Flam Liq. 2	H225
Asp. Tox. 1	H304
Acute Tox. 4 (dermal)	H312
Acute Tox. 4 (inhalation)	H332
STOT SE 3 drowsiness	H336
Carc. 2	H351
STOT RE 2 inhalation	H373

Full text of H phrases see section 16

Adverse physiochemical, human health and environmental effects

No additional information available

2.2 Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

H225 - Highly flammable liquid and vapor
 H304 - May be fatal if swallowed and enters airways.
 H312 - Harmful in contact with skin.
 H332 - Harmful if inhaled.
 H336 - May cause drowsiness or dizziness.
 H351 - Suspected of causing cancer.
 H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements**Prevention**

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/light/equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
 P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
 P331 - Do NOT induce vomiting.
 P362 - Take off contaminated clothing and wash before reuse.
 P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction.

Storage**Disposal**

P405+P403+P235 - Store locked up in a well ventilated place. Keep cool.
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.
 None known

2.3 Other hazards

Full text of R, H and EUH phrases: see section 16

Section 3. Composition / information on ingredients**3.1 Substances**

Not applicable

3.2 Mixture

Name	Product identifier	%
Xylene	1330-20-7	< 5.0
Butyl Acetate	Trade Secret	Trade Secret

Ethylbenzene	100-41-4	< 1.6
Solvent Naphtha	Trade Secret	Trade Secret
Cumene	98-82-8	<0.15

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration is being withheld as Trade Secret, while all health and safety properties and effects are included in the SDS.

Section 4. First aid measures

4.1 Description of first aid measures

First-aid measures general

Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person.

First-aid measures after inhalation

If the individual experiences nausea, dizziness, has difficulty In breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a Poison Center or doctor/physician.

First-aid measures after skin contact

If skin irritation persists, seek medical attention. Remove or take off immediately all contaminated clothing. Rinse skin with water or shower. Wash off immediately with soap and plenty of water.

First-aid measure after eye contact

When contact lenses are worn, remove if possible. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.

First-aid measures after ingestion

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately.

4.2 Most important symptoms and effects, acute and delayed

Symptoms/injuries after inhalation

May cause irritation to the respiratory tract. Overexposure to vapors may result in headache, nausea, drowsiness or dizziness.

Symptoms/injuries after skin contact

May cause skin irritation or burning sensation

Symptoms/injuries after eye contact

May cause eye irritation or injury

Symptoms/injuries after ingestion

May cause severe irritation or burns to the mucous membrane of the mouth, throat, esophagus and stomach

4.3 Indication of any immediate medical attention and special treatment needed

No additional information available

Section 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry chemical, foam, carbon dioxide

Unsuitable extinguishing media

Do not use heavy water stream

5.2 Special hazards arising from the substance or mixture

Reactivity

Thermal decomposition products may cause a health hazard.

5.3 Advice for firefighters

Firefighting instructions

Flammable Liquid! This material releases vapors when heated above ambient temperatures. Vapors can cause a flash fire. Use water spray or fog to cool exposed containers.

Protective equipment for firefighters

Firefighters should always wear self-contained breathing apparatus (SCBA) and full protective gear when fighting any chemical fire.

Other information

On heating or burning harmful gasses/vapors may be released. This product may cause the floor to become slippery.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General measures

Extremely Flammable. Eliminate any ignition sources. Dike or impound spilled material. Use Non-sparking tools. All equipment must be grounded. Take proper precautions to ensure your own health and safety before attempting spill control or cleanup.

6.11 Protective Equipment

Equip cleanup crew with proper protective equipment.

6.2 Environmental precautions

Prevent entry to sewers and public waters.

Notify authorities if liquid enters sewers or public waters.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

Soak up spills with inert solids, such as clay or diatomaceous earth. Collect into vapor tight containers and dispose of properly.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measures

Wash hands and other exposed areas with soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use keep containers tightly closed. Avoid breathing vapor or mist.

Hygiene measures

Wash contaminated clothing before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Store in accordance with local regulations. Store in original container in a cool well ventilated place away from heat, sparks and open flame.. Keep containers tightly closed until ready for use.

Incompatible materials

Strong oxidizing agents

Storage temperature

Store in a cool dry environment away from sources of ignition.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient name	Occupational exposure limits ACGIH TLV (United States)
Xylene	TWA: 100 ppm 8 hours
Butyl Acetate	TWA: 200 ppm 8 hours
Ethylbenzene	TWA: 100 ppm 8 hours
Solvent Naphtha	TWA: 100 mg/m ³
Cumene	TWA: 50 ppm 8 hours

8.2 Exposure controls

Appropriate engineering controls

Use with adequate ventilation to keep product vapor concentrations below specified TLV

Eye and face protection

Chemical goggles and/or face shields are required to prevent potential eye contact, irritation or injury.

Skin protection

Wear chemical resistant gloves and appropriate protective clothing and boots as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.

Respiratory protection

General room ventilation is normally adequate. Avoid breathing the product mist or vapors. The use of an appropriate respirator is recommended whenever the airborne concentrations exceed the TLV.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Clear liquid
Odor	Strong Aromatic Odor
Odor Threshold	No data available
PH	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	> 280 C (>338 F)
Flash point	-4 C 40 F PMCC
Relative evaporation rate (butyl acetate=1)	No data available
Flammability (solid, gas)	Flammable liquid and vapor
Upper/lower explosive limits	No data available
Vapor pressure	No data available
Vapor density	No data available
Relative density (Specific gravity)	0.89 Kg per Liter 7.4 Lbs per Gallon
Solubility	Water: Negligible
Partition coefficient n-octanol/water	No data available
Auto-ignition temperature	Not applicable
Viscosity	No data available
VOC content	Less than 400 g/l

Section 10. Stability and reactivity

10.1 Reactivity	No additional information available
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Hazardous polymerization will not occur.
10.4 Conditions to avoid	Extreme high or low temperatures.
10.5 Incompatible materials	Strong acids and oxidizers
10.6 Hazardous decomposition products	carbon monoxide, carbon dioxide, various hydrocarbon derivatives

Section 11. Toxicology information

11.1 Information on toxicological effects

Acute toxicity	No adverse effects expected under intended use.
Irritation/Corrosion	May cause skin irritation
Skin	
Eyes	May causes serious eye irritation and damage.
Respiration or skin sensitization	May cause respiratory irritation
Germ cell mutagenicity	No data available
Carcinogenicity	
IARC	NTP

Xylene	3	
Ethylbenzene	2B	
Cumene	2B	Reasonably Anticipated To Be Human Carcinogen

2B - Limited evidence in humans and less than sufficient evidence in animals.

3 - Inadequate in humans and inadequate or limited in animals.

Reproductive toxicity No data available

Specific target organ toxicity

Single exposure No data available

Repeated exposure No data available

Aspiration hazard

May be fatal if swallowed and enters airways

Section 12. Ecological information**12.1 Ecotoxicity**

Not established

12.2 Persistence and degradability

Not established

12.3 Bioaccumulative potential

Not established

12.4 Mobility in soil

No additional information available

12.5 Other adverse effects

Avoid release to the environment

SECTION 13. Disposal Considerations**13.1 Waste treatment methods**

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

SECTION 14. Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1 UN number

UN1123

14.2 UN proper shipping name

Butyl Acetates, 3, UN1123

14.3 Transport hazard class(es)

Flammable Liquid

14.4 Packing group

II

14.5 Environmental hazards

No additional information available

14.6 Special precautions for user**14.7 Transport in bulk according to****Annex II of MARPOL 73/78 and the IBC Code**

No additional information available

14.8 Transport in bulk according to**CFR 49 173.15**

Not applicable

SECTION 15. Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.2 USA Regulations****Section 313**

Contains the following ingredients at or above the reporting level requirements of Section 313. This information must be included in all SDS's copied or distributed for this material.

CHEMICAL**CAS #****MAX WEIGHT %**

Xylene

1330-20-7

5.0

Ethylbenzene

100-41-4

1.6

1,2,4-Trimethylbenzene

95-63-6

1.7

TSCA**Proposition 65**

All ingredients are listed or exempted

This product contains one or more chemicals known to the State of California to cause cancer and/or reproductive toxicity.

15.1.3 Canada Regulations

This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

DSL

All ingredients are listed or exempted

WHMIS**15.2 Chemical safety assessment**

A Chemical Safety Assessment has not been carried out.

Section 16. Other information

Date of issue	5-13-2015
Version	2.2
Number	812
Date of previous issue	4-14-2015
Preparer	Nox-Crete Manufacturing Inc.

Reference Documentation

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyers risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Disclaimer

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of this use thereof. (NOX-CRETE MANUFACTURING INC)

Full text of R, H and EUH phrases

Flam Liq. 2	H225
Asp. Tox. 1	H304
Acute Tox. 4 (dermal)	H312
Acute Tox. 4 (inhalation)	H332
STOT SE 3 drowsiness	H336
Carc. 2	H351
STOT RE 2 inhalation	H373

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways.

H312 - Harmful in contact with skin.

H332 - Harmful if inhaled.

H336 - May cause drowsiness or dizziness.

H351- Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/light/equipment.

-
- P242 - Use only non-sparking tools.
- P243 - Take precautionary measures against static discharge.
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
- P271 - Use only outdoors or in a well-ventilated area.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P308+P313 - IF exposed or concerned: Get medical advice/attention.
- P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
- P331 - Do NOT induce vomiting.
- P362 - Take off contaminated clothing and wash before reuse.
- P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction.
- P405+P403+P235 - Store locked up in a well ventilated place. Keep cool.
- P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.