

RELEASE AGENT 15 (450) Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Form Mixture

Trade Name RELEASE AGENT 15 (450)

Product Code R15450

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use Industrial. For professional use only.

1.2.2 Uses Advised Against

No additional information available

1.3 Details of the supplier of the safety data sheet

Manufacturer

NOX-CRETE MANUFACTURING INC

1444 SOUTH 20TH STREET

OMAHA, NE 68108 Tel: 402-341-2080 Fax: 402-341-9752

E-Mail: corporate@nox-crete.com Web Site: www.nox-crete.com

1.4 Emergency telephone number

Emergency Number Chemtrec (800) 424-9300

Chemtrec Outside of U.S. 703-527-3887

Section 2. Hazards identification

Classification of the substance or mixture

Classification according to Regulations 29CFR 1910.1200, (EC) No. 1272/2008(CLP)(GHS)

H227 - Combustible liquid Flam Liq. 4 H304- May be fatal if swallowed and enters airways Asp. Tox. 1 H315 - Causes skin irritation Skin Irrit. 2 H320 - Causes eye irritation Eye Irrit. 2B

H332 - Harmful if inhaled Acute Tox. 4 (inhalation) H336 - May cause drowsiness or dizziness STOT SE 3 drowsiness

Full text of H phrases see section 16

Adverse physiochemical, human health and environmental effects

No additional information available

Label elements

Hazard pictograms





Signal word

Danger

Hazard statements H227 - Combustible liquid

H304- May be fatal if swallowed and enters airways

H315 - Causes skin irritation H320 - Causes eye irritation

EN (English) Page 1 of 7



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

Precautionary statements

Prevention: P210- Keep away from heat/sparks/open flames/hot surfaces-No

smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray P264 - Wash exposed skin thoroughly after handling P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face

protection

Response: P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest

in a position comfortable for breathing.

P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P331 - Do NOT induce vomiting

P332+P313 - If skin irritation occurs: Get medical advice/attention P362 - Take off contaminated clothing and wash before reuse. P337+P313 - If eye irritation persists: Get medical advice/attention P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for

extinction

Storage: P403+P235 - Store in a well ventilated place. Keep cool.

P405 - Store locked up.

Disposal: P501 - Dispose of contents/container in accordance with

local/regional/national/international regulations.

2.3 Other hazards None known

Full text of R, H and EUH phrases: see section 16

Section 3. Composition / information on ingredients

3.1 Substances

Not applicable

3.2 Mixture

Name	Product identifier	%
Petroleum Distillates, Hydrotreated	Trade Secret	Trade Secret

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration is being withheld as Trade Secret, while all health and safety properties and effects are included in the SDS.

Section 4. First aid measures

4.1 Description of first aid measures

First-aid measures general Get medical advice/attention if you feel unwell. Never give anything by

EN (English) Page 2 of 7



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

mouth to an unconscious person.

First-aid measures after inhalation If the individual experiences nausea, dizziness, has difficulty In

breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a Poison Center or doctor/physician.

First-aid measures after skin contact If skin irritation persists, seek medical attention. Remove or take off

immediately all contaminated clothing. Rinse skin with water or shower.

Wash off immediately with soap and plenty of water.

First-aid measure after eye contact When contact lenses are worn, remove if possible. In case of contact

with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.

First-aid measures after ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention

immediately.

4.2 Most important symptoms and effects, acute and delayed

Symptoms/injuries after inhalation May cause irritation to the respiratory tract. Overexposure to vapors may

result in headache, nausea, drowsiness or dizziness.

Symptoms/injuries after skin contact

May cause skin irritation or burning sensation May cause eye irritation or injury

Symptoms/injuries after eye contact Symptoms/injuries after ingestion

May cause severe irritation or burns to the mucous membrane of the

mouth, throat, esophagus and stomach

4.3 Indication of any immediate medical attention and special treatment needed

No additional information available

Section 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing mediaUse fire-extinguishing media appropriate for surrounding materials.

Dry chemical, foam, carbon dioxide

Unsuitable extinguishing media Do not use heavy water stream

5.2 Special hazards arising from the substance or mixture

Reactivity Thermal decomposition products may cause a health hazard.

5.3 Advice for firefighters

Firefighting instructions Combustible Liquid! This material releases vapors when heated above

ambient temperatures. Vapors can cause a flash fire. Use water spray

or fog to cool exposed containers.

Protective equipment for firefighters Firefighters should wear self-contained breathing apparatus (SCBA) and

full protective gear when fighting any chemical fire.

Other information On heating or burning harmful gasses/vapors may be released.

This product may cause the floor to become slippery.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General measures Eliminate any ignition sources. Dike or impound spilled material. Take

proper precautions to ensure your own health and safety before

attempting spill control or cleanup.

6.11 Protective Equipment Equip cleanup crew with proper protective equipment.

6.2 Environmental precautions Prevent entry to sewers and public waters.

Notify authorities if liquid enters sewers or public waters.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up Soak up spills with inert solids, such as clay or diatomaceous earth.

Collect into vapor tight containers and dispose of properly.

Section 7. Handling and storage

EN (English)



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

7.1 Precautions for safe handling

Protective measuresWash hands and other exposed areas with soap and water before

eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use

keep containers tightly closed. Avoid breathing vapor or mist.

Hygiene measures Wash contaminated clothing before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions Store in accordance with local regulations. Store in original container in

a cool well ventilated place. Keep containers tightly closed until ready

for use.

Incompatible materials Acids, prolonged contact with aluminum, brass, bronze, copper, lead,

tin, zinc or other alkali sensitive metals or alloys

Storage temperature Store in a cool dry environment away from sources of ignition.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient name	Occupational exposure limits ACGIH TLV (United States)
Petroleum Distillates, Hydrotreated	TWA: 5 mg/m3 8 hours as mist

8.2 Exposure controls

Appropriate engineering controls

Use with adequate ventilation to keep product vapor concentrations

below specified TLV

Eye and face protectionChemical goggles and/or face shields are required to prevent potential

eye contact, irritation or injury.

Skin protection Wear chemical resistant gloves and appropriate protective clothing and

boots as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered

before reuse.

Respiratory protectionGeneral room ventilation is normally adequate. Avoid breathing the

product mist or vapors. The use of an appropriate respirator is

recommended whenever the airborne concentrations exceed the TLV.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Clear to pale straw liquid

Odor Mild

Odor ThresholdNo data availablePHNo data availableMelting pointNo data availableFreezing pointNo data availableBoiling point150 C (300 F)

Flash point > 60 C (140 F) < 93 C (200 F)

Relative evaporation rate (butyl acetate=1)

Flammability (solid, gas)

Upper/lower explosive limits

Vapor pressure

Vapor density

No data available
No data available
No data available
No data available

Relative density (Specific gravity) 0.84 Kg per Liter 7.0 Lbs per Gallon

Solubility Water: Negligible Partition coefficient n-octanol/water No data available

EN (English) Page 4 of 7



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Auto-ignition temperatureNot applicableViscosityNo data available

VOC content Less than 450 grams per liter

Section 10. Stability and reactivity

10.1 ReactivityNo additional information available10.2 Chemical stabilityStable under normal conditions

10.3 Possibility of hazardous reactions
 10.4 Conditions to avoid
 10.5 Incompatible materials
 10.6 Hazardous decomposition products
 Hazardous polymerization will not occur.
 Extreme high or low temperatures.
 Strong acids, alkalies and oxidizers
 Carbon Monoxide, Carbon Dioxide

Section 11. Toxicology information

11.1 Information on toxicological effects

Acute toxicity

Irritation/Corrosion Skin May cause skin irritation

Eyes May causes serious eye irritation and damage.

No data available

No data available

Respiration or skin sensitization May cause respiratory irritation

Germ cell mutagenicity

Carcinogenicity

No component of this product present at levels greater than 0.1 % is identified as a carcinogen by the U.S. National Toxicology Program, the

No adverse effects expected under intended use.

U.S. Occupational Safety and Health Act, or the International Agency on

Research on Cancer (IARC)

Reproductive toxicity

Specific target organ toxicity

Single exposure No data available Repeated exposure No data available

Aspiration hazard May be fatal if swallowed and enters airways

Section 12. Ecological information

12.1 EcotoxicityNot established12.2 Persistence and degradabilityNot established12.3 Bioaccumulative potentialNot established

12.4 Mobility in soilNo additional information available12.5 Other adverse effectsAvoid release to the environment

SECTION 13. Disposal Considerations

13.1 Waste treatment methods

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

SECTION 14. Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1 UN number

Under 119 US gallons, single container Over 119 US gallons, single container 14.2 UN proper shipping name Not dangerous goods in sense of transport regulations.

UN1268, Petroleum Distillates, N.O.S., PG III

Compounds, Mold Release. N.O.I.

NMFC# 50244

EN (English) Page 5 of 7



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

14.3 Transport hazard class(es)

Under 119 US gallons, single container Not applicable

Over 119 US gallons, single container

14.4 Packing group

Under 119 US gallons, single container Not applicable

Over 119 US gallons, single container
PG III
No additional information available

14.5 Environmental hazards
14.6 Special precautions for user

14.7 Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code No additional information available

14.8 Transport in bulk according to

CFR 49 173.15 Not applicable

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.2 USA Regulations

Section 313 Contains no ingredients at or above the De Minimus reporting level

TSCA All ingredients are listed or exempted Proposition 65 None of the ingredients is listed

<u>15.1.3 Canada Regulations</u> This SDS has been prepared according to the hazard criteria of the

Hazardous Products Regulation (HPR) (WHMIS 2015) and the SDS

contains all of the information required by the HPR.

DSL All ingredients are listed or exempted

15.2 Chemical safety assessment A Chemical Safety Assessment has not been carried out.

Section 16. Other information

Date of issue 10-5-2015 Version 2.0 Number 823

Date of previous issue

Preparer Nox-Crete Manufacturing Inc.

Reference Documentation

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyers risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Disclaimer

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of this use thereof. (NOX-CRETE MANUFACTURING INC)

Full text of R, H and EUH phrases

EN (English) Page 6 of 7



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

H227 - Combustible liquid

H304- May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H320 - Causes eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

Flam Liq. 4

Asp. Tox. 1

Skin Irrit. 2

Eye Irrit. 2B

Acute Tox. 4 (inhalation)

STOT SE 3 drowsiness

P210- Keep away from heat/sparks/open flames/hot surfaces-No smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P331 - Do NOT induce vomiting

P332+P313 - If skin irritation occurs: Get medical advice/attention

P362 - Take off contaminated clothing and wash before reuse.

P337+P313 - If eye irritation persists: Get medical advice/attention

P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction

P403+P235 - Store in a well ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

EN (English) Page 7 of 7