

# **Safety Data Sheet**

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

#### Section 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Form Mixture

Trade Name SPARKL-SEAL LVOC

Product Code SPLV

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use Industrial. For professional use only.

1.2.2 Uses Advised Against

No additional information available

1.3 Details of the supplier of the safety data sheet

Manufacturer

NOX-CRETE MANUFACTURING INC

1444 SOUTH 20TH STREET

OMAHA, NE 68108 Tel: 402-341-2080 Fax: 402-341-9752

E-Mail: <a href="mailto:corporate@nox-crete.com">corporate@nox-crete.com</a>
Web Site: <a href="mailto:www.nox-crete.com">www.nox-crete.com</a>

1.4 Emergency telephone number

Emergency Number Chemtrec (800) 424-9300

Chemtrec Outside of U.S. 703-527-3887

#### Section 2. Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulations 29CFR 1910.1200, (EC) No. 1272/2008(CLP)(GHS)

Flam Liq. 2	H225
Asp. Tox. 1	H304
Acute Tox. 4 (dermal)	H312
Skin Irrit. 2	H315
Eye Dam. 1	H318
Acute Tox. 4 (inhalation)	H332
STOT SE 3 Resp Irrit.	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351
STOT RE 2	H373

Full text of H phrases see section 16

Adverse physiochemical, human health and environmental effects

No additional information available

2.2 Label elements

Hazard pictograms







Signal word Danger

EN (English) Page 1 of 8



# **Safety Data Sheet**

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Hazard statements H225 - Highly flammable liquid and vapor H304 - May be fatal if swallowed and enters airways H312 - Harmful in contact with skin H315 - Causes skin irritation H318 - Causes serious eye damage H332 - Harmful if inhaled H336 - May cause drowsiness or dizziness H351- Suspected of causing cancer H373 - May cause damage to organs through prolonged or repeated exposure H335 - May cause respiratory irritation Precautionary statements Prevention: P201- Obtain special instructions before use P202- Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking P233 - Keep container tightly closed P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof electrical/ventilating/light/.../equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P260 - Do not breathe dust/fume/gas/mist/vapors/spray P264 - Wash exposed area's thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective gloves/protective clothing/eye protection/face P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or Response: doctor/physician. P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue P308+P313 - IF exposed or concerned: Get medical advice/attention P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P331 - Do NOT induce vomiting P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362 - Take off contaminated clothing and wash before reuse P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction P405+P403+P235 - Store locked up in a well ventilated place. Keep Storage: cool. Disposal: P501 - Dispose of contents/container in accordance with local/regional/national/international regulations

2.3 Other hazards

EN (English) Page 2 of 8

None known



# **Safety Data Sheet**

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Full text of H and P phrases: see section 16

### Section 3. Composition / information on ingredients

#### 3.1 Substances

Not applicable

#### 3.2 Mixture

Name Product identifier		%	
Tert Butyl Acetate	Trade Secret	Trade Secret	
Xylene	1330-20-7	< 7.6	
Solvent Naphtha	Trade Secret	Trade Secret	
1,2,4-Trimethylbenzene	95-63-6	< 2.5	
Ethylbenzene	100-41-4	<2.3	
Cumene	98-82-8	< 0.2	
Alcohol	Trade Secret	Trade Secret	

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration is being withheld as Trade Secret, while all health and safety properties and effects are included in the SDS.

#### Section 4. First aid measures

4.1	Description	of first aid	measures
<b>→</b> . I	DESCRIDER	ui ilisi alu	IIICasulcs

First-aid measures general Get medical advice/attention if you feel unwell. Never give anything by

mouth to an unconscious person.

breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a Poison Center or doctor/physician.

First-aid measures after skin contact If skin irritation persists, seek medical attention. Remove or take off

immediately all contaminated clothing. Rinse skin with water or shower.

Wash off immediately with soap and plenty of water.

First-aid measure after eye contact When contact lenses are worn, remove if possible. In case of contact

with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.

First-aid measures after ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention

immediately.

#### 4.2 Most important symptoms and effects, acute and delayed

Symptoms/injuries after inhalation May cause irritation to the respiratory tract. Overexposure to vapors may

result in headache, nausea, drowsiness or dizziness.

Symptoms/injuries after skin contact May cause skin irritation or burning sensation

Symptoms/injuries after eye contact

May cause eye irritation or injury

Symptoms/injuries after ingestion May cause severe irritation or burns to the mucous membrane of the

mouth, throat, esophagus and stomach

#### 4.3 Indication of any immediate medical attention and special treatment needed

No additional information available

EN (English) Page 3 of 8



# **Safety Data Sheet**

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

### Section 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing mediaDry chemical, foam, carbon dioxideUnsuitable extinguishing mediaDo not use heavy water stream

5.2 Special hazards arising from the substance or mixture

**Reactivity**Thermal decomposition products may cause a health hazard.

5.3 Advice for firefighters

Other information

Firefighting instructions Flammable Liquid! This material releases vapors when heated above

ambient temperatures. Vapors can cause a flash fire. Use water spray

or fog to cool exposed containers.

Protective equipment for firefighters Firefighters should always wear self-contained breathing apparatus

(SCBA) and full protective gear when fighting any chemical fire. On heating or burning harmful gasses/vapors may be released.

This product may cause the floor to become slippery.

#### Section 6. Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

General measures Extremely Flammable. Eliminate any ignition sources. Dike or impound

spilled material. Use Non-sparking tools. All equipment must be grounded. Take proper precautions to ensure your own health and

safety before attempting spill control or cleanup.

**6.11 Protective Equipment** Equip cleanup crew with proper protective equipment.

**6.2 Environmental precautions** Prevent entry to sewers and public waters.

Notify authorities if liquid enters sewers or public waters.

#### 6.3 Methods and materials for containment and cleaning up

**Methods for cleaning up**Soak up spills with inert solids, such as clay or diatomaceous earth.

Collect into vapor tight containers and dispose of properly.

# Section 7. Handling and storage

#### 7.1 Precautions for safe handling

**Protective measures**Wash hands and other exposed areas with soap and water before

eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use

keep containers tightly closed. Avoid breathing vapor or mist.

**Hygiene measures** Wash contaminated clothing before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions Store in accordance with local regulations. Store in original container in

a cool well-ventilated place away from heat, sparks and open flame.

Keep containers tightly closed until ready for use.

Incompatible materials Strong oxidizing agents

Storage temperature Store in a cool dry environment away from sources of ignition.

### Section 8. Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limits

Ingredient name	Occupational exposure limits ACGIH TLV (United States)
Tert Butyl Acetate	TWA: 200 ppm 8 hours
Xylene	TWA: 100 ppm 8 hours

EN (English) Page 4 of 8



to concrete problems

### SPARKL-SEAL LVOC

# **Safety Data Sheet**

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Solvent Naphtha	TWA: 100 ppm 8 hours
1,2,4-Trimethylbenzene	TWA: 25 ppm 8 hours
Ethylbenzene	TWA: 100 ppm 8 hours
Cumene	TWA: 50 ppm 8 hours

8.2 Exposure controls

Appropriate engineering controls

Use with adequate ventilation to keep product vapor concentrations

below specified TLV

**Eye and face protection**Chemical goggles and/or face shields are required to prevent potential

eve contact, irritation or injury.

**Skin protection** Wear chemical resistant gloves and appropriate protective clothing and

boots as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered

before reuse.

**Respiratory protection**General room ventilation is normally adequate. Avoid breathing the

product mist or vapors. The use of an appropriate respirator is

recommended whenever the airborne concentrations exceed the TLV.

### Section 9. Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance Clear liquid

**Odor** Sweet

Odor ThresholdNo data availablePHNo data availableMelting pointNo data availableFreezing pointNo data availableBoiling point> 98 C (>200 F)

Flash point > 4 C > 40 F PMCC

Relative evaporation rate (butyl acetate=1)
Flammability (solid, gas)
Upper/lower explosive limits
Vapor pressure
Vapor density

No data available
No data available
No data available
No data available

**Relative density (Specific gravity)** 0.89 Kg per Liter 7.4 Lbs per Gallon

SolubilityWater: NegligiblePartition coefficient n-octanol/waterNo data availableAuto-ignition temperatureNot applicableViscosityNo data availableVOC contentNo data available

### Section 10. Stability and reactivity

10.1ReactivityNo additional information available10.2Chemical stabilityStable under normal conditions10.3Possibility of hazardous reactionsHazardous polymerization will not occur.

10.4 Conditions to avoid

10.5 Incompatible materials

Tazardous polymenzation will not occurrent to a polym

10.6 Hazardous decomposition products carbon monoxide, carbon dioxide, various hydrocarbon derivatives

#### Section 11. Toxicology information

#### 11.1 Information on toxicological effects

Acute toxicity

No adverse effects expected under intended use.

Irritation/Corrosion Skin May cause skin irritation

EN (English) Page 5 of 8



# **Safety Data Sheet**

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

**Eyes** May causes serious eye irritation and damage.

Respiration or skin sensitization

May cause respiratory irritation

Germ cell mutagenicity

No data available

Carcinogenicity IARC NTP

Xylene	3	
Ethylbenzene	2B	
Cumene	2B	Reasonably Anticipated To Be Human Carcinogen

- 2B Limited evidence in humans and less than sufficient evidence in animals.
- 3 Inadequate in humans and inadequate or limited in animals.

Reproductive toxicity

No data available

Specific target organ toxicity

Single exposure No data available Repeated exposure No data available

Aspiration hazard May be fatal if swallowed and enters airways

# Section 12. Ecological information

12.1 EcotoxicityNot established12.2 Persistence and degradabilityNot established12.3 Bio accumulative potentialNot established

12.4 Mobility in soilNo additional information available12.5 Other adverse effectsAvoid release to the environment

#### SECTION 13. Disposal Considerations

13.1 Waste treatment methods The user of this material has the responsibility to dispose of unused

material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

#### SECTION 14. Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

**14.1 UN number** UN1123

**14.2 UN proper shipping name** Butyl Acetates, 3, UN1123

14.3 Transport hazard class(es) Flammable Liquid

14.4 Packing group

<u>14.5 Environmental hazards</u> No additional information available

14.6 Special precautions for user
14.7 Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code No additional information available

14.8 Transport in bulk according to

CFR 49 173.15 Not applicable

#### SECTION 15. Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.2 USA Regulations

Section 313 Contains the following ingredients at or above the reporting level

requirements of Section 313. This information must be included in all

SDS's copied or distributed for this material.

EN (English) Page 6 of 8



# **Safety Data Sheet**

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

CHEMICAL CAS # MAX WEIGHT %

 Xylene
 1330-20-7
 7.6

 Ethylbenzene
 100-41-4
 2.3

 1,2,4-Trimethylbenzene
 95-63-6
 2.5

TSCA All ingredients are listed or exempted

PROPOSITION 65 WARN

**WARNING**: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>."

<u>15.1.3 Canada Regulations</u>

This SDS has been prepared according to the hazard criteria of the Hazardous Products Regulation (HPR) (WHMIS 2015) and the SDS

contains all of the information required by the HPR

**DSL** All ingredients are listed or exempted

**15.2 Chemical safety assessment**A Chemical Safety Assessment has not been carried out.

### Section 16. Other information

Date of issue 3-1-2019
Version 2.4
Number 676
Date of previous issue 7-7-2015

Preparer Nox-Crete Manufacturing Inc.

#### **Reference Documentation**

The information and recommendations contained herein are, to the best of Nox-Crete Manufacturing's knowledge and belief, accurate and reliable as of the date issued. You can contact Nox-Crete Manufacturing to insure that this document is the most current available from Nox-Crete Manufacturing. The information and recommendations are offered for the buyer's/user's consideration and examination. It is the buyer's/user's responsibility to satisfy themselves that the product is suitable for the intended use. Appropriate warnings and safe-handling procedures should be provided to all handlers and users. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Since the information provided herein may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and buyer/user may rely thereon only at their risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further, since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each buyer/user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. If buyer/user repackages this product, it is the buyer's/user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Nox-Crete Manufacturing urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with this product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part is not permitted.

#### Full text of H and P phrases

EN (English) Page 7 of 8



to concrete problems

# SPARKL-SEAL LVOC

# **Safety Data Sheet**

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Flam Liq. 2	H225	Highly flammable liquid and vapor
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways
Acute Tox. 4 (dermal)	H312	Harmful in contact with skin
Skin Irrit. 2	H315	Causes skin irritation
Eye Dam. 1	H318	Causes serious eye damage
Acute Tox. 4 (inhalation)	H332	Harmful if inhaled
STOT SE 3 Resp Irrit.	H335	May cause respiratory irritation
STOT SE 3 drowsiness	H336	May cause drowsiness or dizziness
Carc. 2	H351	Suspected of causing cancer
STOT RE 2	H373	May cause damage to organs through prolonged or repeated

- P201- Obtain special instructions before use
- P202- Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat/sparks/open flames/hot surfaces-No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical/ventilating/light/.../equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P264 Wash exposed area's thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice/attention

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P331 - Do NOT induce vomiting

P332+P313 - If skin irritation occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention

P362 - Take off contaminated clothing and wash before reuse

P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction

P405+P403+P235 - Store locked up in a well ventilated place. Keep cool.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

EN (English) Page 8 of 8