



U-Flow[®] Mechanical Seal

PRODUCT DATA SPECIFICATIONS

PRODUCT DESCRIPTION

The roofing industry's original mechanical compression seal provides a watertight mechanical seal that prevents damage to the roof and building from water back-up. U-Flow Seals feature tough nylon flanges, stainless steel screws and EPDM rubber gaskets. Available in 3-in., 4-in., 5-in. and 6-in. sizes.

FEATURES & BENEFITS

- OlyFlow drains with U-Flow Seals install in minutes from the rooftop, so you won't disturb building occupants.
- Provides a watertight seal that prevents damage from water back-up.
- There's only one original U-Flow Mechanical Seal.
- Can be used on aluminum and copper OlyFlow drains shortened in the field.

APPLICATION

The seal is activated by tightening the internal screws with the U-Flow screwdriver. This compresses the thermoplastic seal, forcing it to expand and make contact with the wall of the old pipe, thus preventing vertical movement and stopping water backup damage.

APPROVALS & STANDARDS

ANSI/SPRI RD-1 is a national performance standard for retrofit roof drains. While most retrofit drains are not tested to this standard, OlyFlow Insert Drains with the U-Flow Seal exceed the standard, which requires that the seal hold a 10-ft. column of water for 24 hours without leaking.



PHYSICAL DATA

SIZE IN	O. D. OF PRE-EXPANDED SEAL	FIT INTO PIPE I.D.	FULLY EXPANDED IN
3	2.86"	2.88"	3.40
4	3.74"	3.76"	4.40
5	4.73"	4.75"	5.40
6	5.75"	5.77"	6.40

Due to manufacturing variances and jobsite inconsistencies, these figures are to be used as a guideline and are not a guaranteed fit in "tight" situations.

ORDERING INFORMATION

CAT. NO.	SIZE IN	PKG QTY	WEIGHT LBS
UF3	3	1	1
UF4	4	1	1
UF5	5	1	1
UF6	6	1	1



U-Flow[®] Mechanical Seal

INSTALLATION PROCEDURE

STEP 1

Simply insert the narrow end of the U-Flow Seal into the bottom of the drain stem.

STEP 2

Using the U-Flow Screwdriver, tighten the seal's screws, accessible through the top of the drain, until seal expands and locks to the drain stem.



STEP 3

Place the drain with attached seal inside the existing drain pipe.

STEP 4

Tighten the seal screws in sequence, in order to provide uniform compression of the seal's compressing ring (the lowest part on the seal). Screws should be tightened with a few turns each, one by one. This procedure should be repeated until screws are hand-tight and no vertical movement of the drain is possible. U-Flow 3-in. and 4-in. seals have three (3) screws each, while U-Flow 5-in. and 6-in. seals have four (4) screws each. The order of tightening is shown below.

For technical assistance contact
OMG at 800-633-3800.



ROOFING PRODUCTS

153 BOWLES ROAD, AGAWAM, MA 01001 USA
800-633-3800 413-789-0252 OMGROOFING.COM

Superior productivity.
Superior performance.

OlyFlow[®] and U-Flow[®] are trademarks of OMG, Inc. Copyright © 2020 OMG, Inc. All rights reserved.

