

OSI[®]

Professional Grade Adhesives & Sealants

GS-121[™] SEALANT

GUTTER & SEAM

- Seals most common gutters and downspout materials
- Expands and contracts with temperature changes
- Permanently flexible waterproof seal

OSI[®] GS-121[™] Gutter & Seam sealant is designed especially for sealing aluminum, galvanized and vinyl gutters and downspouts. The high quality formula provides a permanent flexible waterproof seal that expands and contracts with changes in weather. OSI GS-121 is excellent for sealing seams, joints and cracks in gutter troughs, and will bond to any clean surface. It can be easily painted and will not lose its strong waterproof bond or become brittle even after years of exposure to freezing and thawing cycles.





Professional Grade Adhesives & Sealants

Recommended Uses

- Sealing around aluminum, galvanized and vinyl clad gutters and downspouts
- Excellent for sheet metal work, ducts and ventilator joints
- Sealing seams, joints and cracks in gutter troughs

Not Recommended For

- Applications as an expansion joint control sealant
- Bonding, polystyrene foam and polypropylene or polyethylene plastics
- Joints deeper than 3/8" (9.5 mm) without the use of backing material
- Use indoors without proper ventilation to the outdoors during application and cure
- Use on copper

Coverage

A 10 fl oz (295 mL) cartridge will extrude approx. 30.6 ft (9.3 m) of a 1/4" (6 mm) bead. A 10 fl oz (295 mL) cartridge will extrude approx. 13.6 ft (4.1 m) of a 3/8" (9.5 mm) bead.

Storage And Disposal

NOT DAMAGED BY FREEZING. Store in a cool, dry place. Take unwanted product to an approved household hazardous waste transfer facility. Hardened material may be disposed of with trash.

Typical Cured Properties

Color:	White and Aluminum
Shrinkage: (ASTM D 2453)	30%
Hardness, Shore A:	40
Elongation:	500%
180° Peel Adhesion: (ASTM C794)	
Painted Aluminum	18 pli
Service Temperature:	-0°F (-18°C) to 150°F (66°C)
Water Resistance:	Yes

Disclaimer

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent. All marks are trademarks or registered trademarks of Henkel Corporation and its affiliates in the USA and elsewhere.



Henkel Corporation
Professional and Consumer Adhesives
Phone 1-800-624-7767
Fax (440) 250-7873
www.henkel.com www.osipro.com