



Revision Number: 007.1

Issue date: 05/12/2022

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name:** OSI® QB-300 Multi-Purpose Construction Adhesive  
**IDH number:** 827629  
**Product type/use:** Solvent based adhesive  
**Restriction of Use:** None identified  
**Region:** United States  
**Company address:** Henkel Corporation, One Henkel Way, Rocky Hill, Connecticut 06067  
**Contact information:** Telephone: +1 (860) 571-5100  
 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711  
 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887  
 Internet: www.henkeln.com

**2. HAZARDS IDENTIFICATION**

EMERGENCY OVERVIEW	
WARNING:	CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

PICTOGRAM(S)

**Precautionary Statements**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or fumes. Wash affected area thoroughly after handling. Wear protective gloves, clothing, eye and face protection.

**Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

**Storage:** Store locked up.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	40 - 50

Hydrocarbons, C6, isoalkanes, < 5% n-hexane	64742-49-0	20 - 30
Rosin ester	Proprietary	10 - 20
Kaolin	1332-58-7	5 - 10
Titanium dioxide	13463-67-7	0.1 - 1
Quartz (SiO <sub>2</sub> ), <1% respirable	14808-60-7	0.1 - 1
Naphthalene	91-20-3	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice. If breathing is difficult, give oxygen.
<b>Skin contact:</b>	Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If skin irritation persists, call a physician.
<b>Eye contact:</b>	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
<b>Ingestion:</b>	Do not induce vomiting, seek medical advice immediately.
<b>Symptoms:</b>	See Section 11.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide. In case of fire, keep containers cool with water spray.
<b>Special firefighting procedures:</b>	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode. Wear full protective clothing.
<b>Unusual fire or explosion hazards:</b>	Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors are heavier than air and may travel along floor to an ignition source.
<b>Hazardous combustion products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Ventilate area. Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

## 7. HANDLING AND STORAGE

**Handling:**

During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Do not cut, grind, weld, or drill on or near this container. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8. Keep out of the reach of children. Containers should be grounded and bonded to the receiving container.

**Storage:**

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

**For information on product shelf life, please review labels on container or check the Technical Data Sheet.**

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	None	100 ppm (400 mg/m3) PEL	None	None
Rosin ester	None	None	None	None
Kaolin	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None
Naphthalene	10 ppm TWA (SKIN)	10 ppm (50 mg/m3) PEL	None	None

**Engineering controls:**

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

**Respiratory protection:**

Use a NIOSH approved supplied air respirator with an organic cartridge if the potential to exceed established exposure limits exists.

**Eye/face protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Beige
<b>Odor:</b>	Slightly, mineral-oil-like
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	155 mm hg (20 °C (68°F))
<b>Boiling point/range:</b>	57 - 74 °C (134.6 - 165.2 °F)no method
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	1.369
<b>Vapor density:</b>	Heavier than air.
<b>Flash point:</b>	-17.80 °C (0.04 °F) no method
<b>Flammable/Explosive limits - lower:</b>	1 %
<b>Flammable/Explosive limits - upper:</b>	7 %
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	4.4 Greater than butyl acetate., (Butyl acetate = 1)
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	20 %; 280 g/l (calculated)
<b>Viscosity:</b>	280,000 - 400,000 mPa.s
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.
<b>Incompatible materials:</b>	Strong oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

<b>Relevant routes of exposure:</b>	Inhalation, Skin contact, Eye contact
-------------------------------------	---------------------------------------

### Potential Health Effects/Symptoms

<b>Inhalation:</b>	Irritates the nose, throat and respiratory system. Exposure to high doses may cause central nervous system depression. Such doses may also cause adverse effects in the liver, kidneys, and lungs. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
<b>Skin contact:</b>	Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.
<b>Eye contact:</b>	Contact with eyes can cause eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
<b>Ingestion:</b>	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	Inhalation LC50 (Rat, 4 h) = > 5,610 mg/m3 Inhalation LC50 (Rat, 4 h) = > 7,630 mg/m3	No Data
Rosin ester	None	Irritant
Kaolin	Oral LD50 (Rat) = > 5,000 mg/kg Dermal LD50 (Rat) = > 5,000 mg/kg	Nuisance dust
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l	Irritant, Respiratory, Some evidence of carcinogenicity
Quartz (SiO2), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity
Naphthalene	Oral LD50 (Rat) = 490 mg/kg Oral LD50 (Rat) = 2.6 g/kg Oral LD50 (Rat) = 2,200 mg/kg Oral LD50 (Rat) = 2,400 mg/kg Dermal LD50 (Rat) = > 20 g/kg Dermal LD50 (Rabbit) = > 2.0 g/kg Inhalation LC50 (Rat, 4 h) = > 0.4 mg/l Inhalation LC50 (Rat, 4 h) = > 78 ppm	Blood, Central nervous system, Eyes, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	No	No	No
Rosin ester	No	No	No
Kaolin	No	No	No
Titanium dioxide	No	Group 2B	No
Quartz (SiO2), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes
Naphthalene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

<b>Proper shipping name:</b>	Adhesives
<b>Hazard class or division:</b>	3
<b>Identification number:</b>	UN 1133
<b>Packing group:</b>	II

**International Air Transportation (ICAO/IATA)**  
**Proper shipping name:** Adhesives  
**Hazard class or division:** 3  
**Identification number:** UN 1133  
**Packing group:** II

**Water Transportation (IMO/IMDG)**  
**Proper shipping name:** ADHESIVES  
**Hazard class or division:** 3  
**Identification number:** UN 1133  
**Packing group:** II

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health, Fire  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). n-Hexane (CAS# 110-54-3).

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 15

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 05/12/2022

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.