



PRO PINK[®] COMFORTSEAL[™] FRAMING GASKET



Owens Corning[®] ProPink ComfortSeal[™] Framing Gasket is a low cost, durable, easy to install, compressible polyethylene foam gasket specially designed to seal air leakage gaps.

Features

- Compressible closed-cell polyethylene foam gasket
- Long-lasting and durable
- Cost-effective
- Installs and cuts easily
- Reduces air infiltration and heat loss
- Reduces noise transmission
- Insect resistant
- Moisture resistant



Physical Properties

	PROPERTY	TEST METHOD	VALUE
PHYSICAL	Vertical compressive strength (psi)	ASTM D3575-08	
	Compressive strength	Suffix D @ 25%/50%	2.7/10.4
	Compression set (%)	ASTM D3575-08 Suffix B	29.4
	Tear resistance (lb/ft ²)	ASTM D3575-08 Suffix T MD/CMD	8.3/11.5
	Density (lb/ft ³)	ASTM D3575-08	1.2
MOISTURE	Water absorption (lb/ft ²)	ASTM D3575-08 Suffix L	< 0,1 / sq ft / 24 hours
	Water vapor transmission rate	ASTM F-1249	
	GM/100 in ² /24 hours	Method 3005 FED STD 101	0.089
THERMAL	Thermal resistance R-Value @ initial thickness (hr-ft ² -0F/BTU)	ASTM C518-91	0.68

1 R means resistance to heat flow; the higher the value, the greater the insulation power. Value given is for initial thickness. Value after installation/compression will be lower.

Standards, Code Compliance

- Class A Fire Rating
- Does not support mold growth
- GreenGuard™ Certified

Applications

- Air leakage control
The closed-cell foam, 3/16 inch thickness, easily compresses to seal air gaps that commonly occur between the wood framing and drywall juncture. These gaps occur as a result of misaligned vertical studs, dimensional wood instabilities (from expansion and contraction), and/or air gaps that occur from the installation of wood-frame structural connectors or clips often referred to as "hurricane clips."
- Noise control
ProPink ComfortSeal™ Framing Gasket also provides noise isolation between rooms by reducing the transmission of sound vibrations from the drywall to the wood-frame structure.

Installation Instructions

- Place the ProPink ComfortSeal™ Framing Gasket over the face of the top plate with the ribbed surface of the foam facing outward toward the drywall.
- Continuously apply 5/16 inch heavy-duty staples a minimum of 3 inches on center unless otherwise specified, horizontally along the lower half of the gasket to ensure ProPink ComfortSeal™ Framing Gasket is well secured to the top plate.
- Allow the foam gasket to span over the surface of structural ties or clips as they occur.

Recommended Tools

- Safety glasses
- Cut-resistant gloves
- Ladder
- Construction or hammer stapler
- 5/16 inch heavy-duty staples
- Scissors or utility knife

Storage Recommendations

- Store product in packaging away from heat sources
- Do not store in the sun

Dimensions

MATERIAL	COLOR	LENGTH	PRODUCT SIZE
Polyethylene Foam	Pink	50 ft rolls	3" wide x 3/16" thick
Polyethylene Foam	Black	50 ft rolls	3" wide x 3/16" thick

Environmental and Sustainability

Owens Corning is a world leader in building material systems, insulation, and composite solutions, delivering a broad range of high-quality products and services.

Owens Corning is committed to driving sustainability by delivering solutions, transforming markets, and enhancing lives. More information can be found at www.owenscorning.com.

Certifications and Sustainable Features

- GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.



Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.



OWENS CORNING INSULATING SYSTEMS, LLC

ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659

1-800-GET-PINK®
www.owenscorning.com