

1 Identification of the substance/preparation and of the company/undertaking

Product details

Product category: FAÇADE
 Trade name: PAREX USA 365 FLASHING MEMBRANE
 Application/preparation of the substance: EIFS Accessories
 Manufacturer/Supplier: PAREXUSA, Inc.
 4125 E. LA PALMA AVE
 SUITE 250
 ANAHEIM, CA 92807
 Further information obtainable from: pedro.paredes@parexusa.com
 Contact phone number: 800-226-2424
 In case of emergency, contact CHEMTREC: 800-424-9300

2 Hazards identification

Hazard pictograms (GHS-US):

Irritant



Health Hazards



Signal word (GHS-US):

Warning

Hazard statement (GHS-US):

H303 Can be harmful if swallowed
 H320 Causes eye irritation
 H335 May cause respiratory irritation
 H313 May be harmful in contact with skin

Precautionary statements (GHS-US):

P402 Store in a dry place.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water
 IF IN EYES: Rinse cautiously with water for several minutes.
 P305+P351+P338 Remove contact lenses, if present and easy to do. Continue rinsing.
 P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

HMIS codes:

| | |
|----------------------|----|
| Health | 1* |
| Flammability | 1 |
| Reactivity | 0 |
| Protective equipment | B |

Information concerning particular hazards for human and environment:

May be harmful if ingested.
 Dust may be irritating to eyes, respiratory system, and skin.
 Not known to cause reproductive harm or birth defects.
 Keep out of reach of children.

3 Composition/information on ingredients

Chemical characterization

| Dangerous components: | | | |
|-----------------------|-----------------------------|----------------|-----------------------|
| CAS # | Name | Exposure Limit | |
| 8052-42-4 | Asphalt, petroleum, bitumen | OSHA TLV-TWA | 0.5 mg/m ³ |
| 1317-65-3 | Calcium carbonate | OSHA PEL-TWA | 5 mg/m ³ |
| | | OSHA TLV-TWA | 10 mg/m ³ |

4 First aid measures

| | |
|----------------------|---|
| General information: | n/a |
| After inhalation: | Remove to fresh air. If not breathing, give artificial respiration. If having difficulty breathing, give oxygen. Get immediate medical attention. |
| After skin contact: | Wash affected area thoroughly with soap and water. Remove contaminated clothes and launder before re-use. |
| After eye contact: | Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention. |
| After swallowing: | Do not induce vomiting. Get medical attention immediately. |

5 Fire-fighting measures

| | |
|------------------------------------|--|
| General information: | |
| Flash point: | >320 F |
| Flammable Limits | LEL: Not Applicable UEL: Not Applicable |
| Auto ignition Temperature | Not determined |
| Extinguishing Media | Use foam or dry chemical to extinguish fire. Use fog nozzles if water is used. Water streams may cause violent eruptions and spread the burning of asphalt. Use water to cool fire exposed containers and structures. |
| Unusual Fire or Explosion Hazards | Product will burn if exposed to elevated temperatures or fire. Hot asphalt may ignite flammable mixtures on contact. Toxic vapors including hydrogen sulfide may release upon combustion. Hydrogen sulfide vapors are heavier than air, may accumulate in low areas and flashback ignited. |
| Special Firefighting instructions: | Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Do not allow run-off from fire fighting to enter drains or water courses. |
| Explosion Data | None Known |

6 Accidental release measures

| | |
|--|---|
| Measures for environmental protection: | Keep spilled products out of sewers, streams, and water systems. |
| Measures for cleaning/collecting: | For dry material, collect by sweeping and scooping. Transfer collected material to a container, being careful to minimize creation of dust. For wet material, scoop material up and transfer to an open container. Allow material to dry before disposal. |
| Additional information: | See section 13 and section 15 for specific regulatory information concerning this product. |

7 Handling and storage

| | |
|-----------|---|
| Handling: | Wear appropriate protective equipment when working with this product. Promptly remove dusty clothing, or clothing wet with product mix, and launder before re-using. Wash thoroughly after exposure to product mixtures. Keep out of reach of children. |
| Storage: | Store in a dry location. Atmospheric temperatures and pressures do not affect the shelf life of this product. |

8 Exposure controls/personal protection

Additional information about design of technical facilities: n/a

| Ingredients with limit values that require monitoring at the workplace: | | | |
|---|-----------------------------|----------------|-----------|
| Dangerous components: | | | |
| CAS # | Name | Exposure Limit | |
| 8052-42-4 | Asphalt, petroleum, bitumen | OSHA TLV-TWA | 0.5 mg/m3 |
| 1317-65-3 | Calcium carbonate | OSHA PEL-TWA | 5 mg/m3 |
| | | OSHA TLV-TWA | 10 mg/m3 |

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE , ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find how low to protect yourself and your family by contacting the National Lead Hotline at 1800-424-LEAD or log onto www.epa.gov/lead

Additional information: The lists valid during the making were used as a basis.

Personal protective equipment:

| | |
|------------------------|---|
| ventilation | Use local exhaust. General exhaust acceptable if the exposure to materials above is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, and 1910.108. |
| respiratory protection | If personal exposure cannot or may not be controlled below applicable limits by ventilation, wear properly fitted respirator approved by NIOSH/MSHA for protection against materials described above. |
| eye protection | Wear safety glasses to reduce the potential for eye contact. |
| skin protection | Prevent prolonged or repeated contact by using rubber gloves and appropriate protective clothing. |

9 Physical and chemical properties

| General information: | |
|---------------------------------------|--|
| form | Solid black tape with a white/tan wrapping and no odor |
| color | black |
| odor | odorless |
| pH | n/a |
| Change in condition: | |
| melting point/melting point range | n/a |
| boiling point/boiling point range | n/a |
| evaporation rate: | n/a |
| vapor density: | n/a |
| Specific gravity: | 1.3 |
| Solubility in/Miscibility with water: | n/a |
| Density at 20°C: | 10.56 lb/gal |
| VOC: | 0 g/L (0 lb/gal) |

10 Stability and reactivity

| | |
|-----------------------------------|---|
| Conditions to be avoided: | None known |
| Chemical stability: | Stable under normal storage and handling conditions |
| Materials to be avoided: | Strong Oxidizers, avoid water if product is molten |
| Hazardous polymerization: | Will not occur |
| Dangerous decomposition products: | Combustion will produce carbon monoxide, sulfur oxides, hydrogen sulfide, acrolein, aldehydes, ketones, and unidentified organic compounds. |

11 Toxicological information

| | |
|---------------------------------------|--|
| Acute toxicity: | n/a |
| Primary irritant effect: | |
| on the skin | May cause irritation, defatting of the skin and dermatitis. Contact with product at elevated temperatures may cause thermal burns. |
| on the eye | May cause irritation with redness, tearing and blurred vision. Contact with product at elevated temperatures may cause thermal burns. |
| through ingestion | No adverse effects are expected from normal use. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| through inhalation | No adverse effects are expected at ambient temperatures. This product is not intended to be heated but if it is vapors released may cause respiratory irritation. At elevated temperatures hydrogen sulfide may be released. The release of hydrogen sulfide gas in various concentrations may cause irritation of the eyes and respiratory tract, headache, dizziness, nausea, and drowsiness. Exposure to high concentrations of hydrogen sulfide can cause respiratory arrest and death |
| Additional toxicological information: | n/a |

12 Ecological information

| | |
|--|-----|
| Elimination (persistence and degradability): | n/a |
| Behavior in environmental systems: | n/a |
| Mobility and bioaccumulation potential: | n/a |
| General notes: | n/a |

13 Disposal considerations

| | |
|--------------------------------------|--|
| Product recommendation: | This product must be disposed of in accordance with applicable local, state and federal regulations. Where possible, it is best to use up any excess material. |
| Uncleansed packaging recommendation: | Disposal must be made according to official regulations. |

14 Transport information

| | |
|--------------------------------|--|
| Land transport USDOT | Not classified as a dangerous good under transport regulations |
| Sea transport IMDG | Not classified as a dangerous good under transport regulations |
| Air transport IATA/ICAO | Not classified as a dangerous good under transport regulations |

