



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

### SECTION 1. IDENTIFICATION

Product name : SikaWall®-4090 Elastomeric Coating

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Carcinogenicity (Inhalation) : Category 1A

#### GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

P308 + P313 IF exposed or concerned: Get medical advice/attention.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Mixtures**

**Components**

| Chemical name                              | CAS-No.    | Classification                                       | Concentration (% w/w) |
|--------------------------------------------|------------|------------------------------------------------------|-----------------------|
| Talc                                       | 14807-96-6 |                                                      | $\geq 0.1 - < 1$      |
| Quartz (SiO <sub>2</sub> ) $>5\mu\text{m}$ | 14808-60-7 | Carc. 1A; H350<br>STOT RE 1; H372<br>STOT SE 3; H335 | $\geq 0.1 - < 1$      |

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

Most important symptoms and effects, both acute and delayed : No information available.  
May cause cancer by inhalation.  
No known significant effects or hazards.

Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.

Environmental precautions : Try to prevent the material from entering drains or water courses.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.  
Keep container tightly closed in a dry and well-ventilated



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components                      | CAS-No.    | Value type<br>(Form of exposure)    | Control parameters / Permissible concentration | Basis     |
|---------------------------------|------------|-------------------------------------|------------------------------------------------|-----------|
| Talc                            | 14807-96-6 | TWA (Dust)                          | 20 Million particles per cubic foot            | OSHA Z-3  |
|                                 |            | TWA (respirable dust fraction)      | 2 mg/m <sup>3</sup>                            | OSHA P0   |
|                                 |            | TWA (Respirable particulate matter) | 2 mg/m <sup>3</sup>                            | ACGIH     |
|                                 |            | PEL (respirable)                    | 0.05 mg/m <sup>3</sup>                         | OSHA CARC |
| Quartz (SiO <sub>2</sub> ) >5µm | 14808-60-7 | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup>                        | ACGIH     |
|                                 |            | TWA (Respirable dust)               | 0.05 mg/m <sup>3</sup>                         | OSHA Z-1  |
|                                 |            | TWA (respirable)                    | 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2    | OSHA Z-3  |
|                                 |            | TWA (respirable)                    | 250 mppcf / %SiO <sub>2</sub> +5               | OSHA Z-3  |
|                                 |            | TWA (respirable dust fraction)      | 0.1 mg/m <sup>3</sup>                          | OSHA P0   |
|                                 |            | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup> (Silica)               | ACGIH     |
|                                 |            | PEL (respirable)                    | 0.05 mg/m <sup>3</sup>                         | OSHA CARC |
|                                 |            | TWA (respirable dust fraction)      | 0.1 mg/m <sup>3</sup>                          | OSHA P0   |
|                                 |            | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup>                        | ACGIH     |



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

|  |  |                                     |                                  |       |
|--|--|-------------------------------------|----------------------------------|-------|
|  |  | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup> (Silica) | ACGIH |
|--|--|-------------------------------------|----------------------------------|-------|

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Personal protective equipment

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : liquid

**Color** : various

**Odor** : slight, ammoniacal



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

|                                                  |                                              |
|--------------------------------------------------|----------------------------------------------|
| Odor Threshold                                   | : No data available                          |
| pH                                               | : 9 - 9.5                                    |
| Melting point/range / Freezing point             | : No data available                          |
| Boiling point/boiling range                      | : No data available                          |
| Flash point                                      | : Not applicable                             |
| Evaporation rate                                 | : No data available                          |
| Flammability (solid, gas)                        | : No data available                          |
| Upper explosion limit / Upper flammability limit | : No data available                          |
| Lower explosion limit / Lower flammability limit | : No data available                          |
| Vapor pressure                                   | : 23 hpa                                     |
| Relative vapor density                           | : No data available                          |
| Density                                          | : ca. 1.85 g/cm <sup>3</sup> (68 °F / 20 °C) |
| Solubility(ies)                                  |                                              |
| Water solubility                                 | : soluble                                    |
| Solubility in other solvents                     | : No data available                          |
| Partition coefficient: n-octanol/water           | : No data available                          |
| Autoignition temperature                         | : No data available                          |
| Decomposition temperature                        | : No data available                          |
| Viscosity                                        |                                              |
| Viscosity, dynamic                               | : No data available                          |
| Viscosity, kinematic                             | : > 20.5 mm <sup>2</sup> /s (104 °F / 40 °C) |
| Explosive properties                             | : No data available                          |
| Oxidizing properties                             | : No data available                          |
| Volatile organic compounds (VOC) content         | : 78 g/l                                     |

---

### SECTION 10. STABILITY AND REACTIVITY

|            |                                                               |
|------------|---------------------------------------------------------------|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
|------------|---------------------------------------------------------------|



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| Chemical stability                 | : The product is chemically stable.                   |
| Possibility of hazardous reactions | : Stable under recommended storage conditions.        |
| Conditions to avoid                | : No data available                                   |
| Incompatible materials             | : No data available                                   |
| Hazardous decomposition products   | : No decomposition if stored and applied as directed. |

---

### SECTION 11. TOXICOLOGICAL INFORMATION

Not classified due to lack of data.

#### Skin corrosion/irritation

Not classified due to lack of data.

#### Serious eye damage/eye irritation

Not classified due to lack of data.

#### Respiratory or skin sensitization

##### Skin sensitization

Not classified due to lack of data.

##### Respiratory sensitization

Not classified due to lack of data.

##### Germ cell mutagenicity

Not classified due to lack of data.

##### Carcinogenicity

May cause cancer by inhalation.

|             |                                                                         |            |
|-------------|-------------------------------------------------------------------------|------------|
| <b>IARC</b> | Group 1: Carcinogenic to humans                                         |            |
|             | Quartz (SiO <sub>2</sub> )                                              | 14808-60-7 |
|             | (Silica dust, crystalline)                                              |            |
|             | Group 2B: Possibly carcinogenic to humans                               |            |
|             | Titanium dioxide (> 10 µm)                                              | 13463-67-7 |
|             | Group 2B: Possibly carcinogenic to humans                               |            |
|             | Carbon black                                                            | 1333-86-4  |
| <b>OSHA</b> | OSHA specifically regulated carcinogen                                  |            |
|             | Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 |
|             | (crystalline silica)                                                    |            |
|             | OSHA specifically regulated carcinogen                                  |            |
|             | Quartz (SiO <sub>2</sub> )                                              | 14808-60-7 |
|             | (crystalline silica)                                                    |            |
|             | OSHA specifically regulated carcinogen                                  |            |
|             | silicon dioxide                                                         | 7631-86-9  |



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

(crystalline silica)

|            |                                                                                                       |            |
|------------|-------------------------------------------------------------------------------------------------------|------------|
| <b>NTP</b> | Known to be human carcinogen<br>Quartz (SiO <sub>2</sub> )<br>(Silica, Crystalline (Respirable Size)) | 14808-60-7 |
|------------|-------------------------------------------------------------------------------------------------------|------------|

### Reproductive toxicity

Not classified due to lack of data.

### STOT-single exposure

Not classified due to lack of data.

### STOT-repeated exposure

Not classified due to lack of data.

### Aspiration toxicity

Not classified due to lack of data.

### Further information

#### Product:

Remarks : Carbon black (1333-86-4)  
Animal Toxicity:  
Rat, oral, duration 2 year  
Effect: no tumors  
  
Mouse, oral, duration 2 years  
Effect: no tumors  
Mouse, dermal, duration 18 months  
Effect: no skin tumors  
Rat, inhalation, duration 2 years  
Target organ: lungs  
Effect: inflammation, fibrosis, tumors  
Note: Tumors in the rat lung are considered to be related to the "particle overload phenomenon" rather than to a specific chemical effect of carbon black itself in the lung. These effects in rats have been reported in many studies on other poorly soluble inorganic particles and appear to be rat specific. Tumors have not been observed in other species (i.e., mouse and hamster) for carbon black or other poorly soluble particles under similar circumstances and study conditions. Mortality studies (human data): A study on carbon black production workers in the UK (Sorahan, 2001) found an increased risk of lung cancer in two of the five plants studied; however, the increase was not related to the dose of carbon black. Thus, the authors did not consider the increased risk in lung cancer to be due to carbon black exposure. A German study of carbon black workers at one plant (Morfeld, 2006; Buechte, 2006) found a similar increase in lung cancer risk but, like the Sorahan, 2001 (UK study) found no association with carbon black exposure. A large US study of 18 plants showed a reduction in lung cancer risk in carbon black pro-



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

duction workers (DEll, 2006). Based upon these studies, the February 2006 Working Group at the International Agency for Research on Cancer (IARC) concluded that the human evidence for carcinogenicity was inadequate (IARC, 2010). Since the IARC evaluation of carbon black, Sorahan and Harrington (2007) have re-analyzed the UK study data using an alternative exposure hypothesis and found a positive association with carbon black exposure in two of the five plants. The same exposure hypothesis was applied by Morfeld and McCunney (2009) to the German cohort; in contrast, they found no association between carbon black exposure and lung cancer risk and, thus, no support for the alternative exposure hypothesis used by Sorahan and Harrington. Overall, as a result of these detailed investigations, no causative link between carbon black exposure and cancer risk in humans has been demonstrated.

**IARC CANCER CLASSIFICATION:** In 2006 IARC re-affirmed its 1995 finding that there is "inadequate evidence" from human health studies to assess whether carbon black causes cancer in humans. IARC concluded that there is "sufficient evidence" in experimental animal studies for the carcinogenicity of carbon black. IARC's overall evaluation is that carbon black is "possibly carcinogenic to humans" (Group 2B)". This conclusion was based on IARC's guidelines, which generally require such a classification if one species exhibits carcinogenicity in two or more animal studies (IARC, 2010).

Solvent extracts of carbon black were used in one study of rats in which skin tumors were found after dermal application and several studies of mice in which sarcomas were found following subcutaneous injection. IARC concluded that there was "sufficient evidence" that carbon black extracts can cause cancer in animals (Group 2B).

**ICGIH CANCER CLASSIFICATION:** Confirmed Animal Carcinogen with Unknown Relevance to Humans (Category A3 Carcinogen).

**ASSESSMENT:** Applying the guidelines of self-classification under the Globally Harmonized System of Classification and Labeling of Chemicals, carbon black is not classified as a carcinogen. Lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rats tumors are a result of a secondary non-genotoxic mechanism that has questionable relevance for classification in humans. In support of this opinion, the CLP Guidance for Specific Target Organ Toxicity - Repeated Exposure (STOT-RE), cites lung overload under mechanisms not relevant to humans. Human health studies show that exposure to carbon black does not increase the risk to carcinogenicity.

Titanium dioxide (13463-67-7)



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
May be harmful to the environment if released in large quantities.  
Water polluting material.



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 3082
- Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(2-octyl-2H-isothiazole-3-one (OIT))
- Class : 9
- Packing group : III
- Labels : Miscellaneous
- Packing instruction (cargo aircraft) : 964
- Packing instruction (passenger aircraft) : 964

##### IMDG-Code

- UN number : UN 3082
- Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(2-octyl-2H-isothiazole-3-one (OIT))
- Class : 9
- Packing group : III
- Labels : 9
- EmS Code : F-A, S-F
- Marine pollutant : yes

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

DOT: As per 49 CFR 171.4, Non-bulk materials (<119 Gal) are exempt from being classified as a Marine Pollutant.

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **CERCLA Reportable Quantity**

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### **SARA 304 Extremely Hazardous Substances Reportable Quantity**

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### **SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Carcinogenicity

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

#### **California Prop. 65**

**⚠ WARNING:** This product can expose you to chemicals including Titanium dioxide, which is known to the State of California to cause cancer, and ethylene oxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

---

### SECTION 16. OTHER INFORMATION

#### **Full text of other abbreviations**

|           |                                                                                    |
|-----------|------------------------------------------------------------------------------------|
| ACGIH     | : USA. ACGIH Threshold Limit Values (TLV)                                          |
| OSHA CARC | : OSHA Specifically Regulated Chemicals/Carcinogens                                |
| OSHA P0   | : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)               |
| OSHA Z-1  | : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-3  | : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-                        |



## SikaWall®-4090 Elastomeric Coating

Revision Date 06/06/2024

Print Date 06/06/2024

|                 |                                    |
|-----------------|------------------------------------|
|                 | eral Dusts                         |
| ACGIH / TWA     | : 8-hour, time-weighted average    |
| OSHA CARC / PEL | : Permissible exposure limit (PEL) |
| OSHA P0 / TWA   | : 8-hour time weighted average     |
| OSHA Z-1 / TWA  | : 8-hour time weighted average     |
| OSHA Z-3 / TWA  | : 8-hour time weighted average     |

### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 06/06/2024

100000057489  
US / Z8