

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

1 Identification

Product identifier

- · Trade name: AC-20 +Silicone Black
- · Other means of identification: Non-Sag, Acrylic Latex Caulking Compound
- · Recommended use and restriction on use
- · Recommended use: Sealant
- · Restrictions on use: No relevant information available.

[•] Details of the supplier of the Safety Data Sheet

• Manufacturer/Supplier: Pecora Corporation 165 Wambold Road Harleysville, PA 19438 215-723-6051

• Emergency telephone number:

CHEMTREC 1-800-424-9300 (US/Canada)

2 Hazard(s) identification

[•] Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

[•] Label elements

· GHS label elements Not regulated.

- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: Not regulated.
- · Precautionary statements: Not regulated.

· Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Componen	ts:		
1317-65-3	Limestone		40-60%
64741-65-7	Naphtha (petroleum), heavy alkylate	 Flam. Liq. 3, H226 Asp. Tox. 1, H304 	<3%
14808-60-7	Quartz		<3%
	Propylene glycol		<3%
1333-86-4	Carbon black		<1%

· Additional information:

Non-classification as a carcinogen is based on non-inhalable form of product. IARC listings for carbon black and quartz note that the substance must be respirable.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

(Cont'd. on page 2)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: AC-20 +Silicone Black

(Cont'd. of page 1)

4 First-aid measures

[•] Description of first aid measures

After inhalation:

Respiration of particulates is unlikely during normal usage.

Supply fresh air; consult doctor in case of complaints.

• After skin contact:

Wash with soap and water.

Seek medical treatment in case of complaints.

• After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Most important symptoms and effects, both acute and delayed:
- Gastric or intestinal disorders when ingested.
- Indication of any immediate medical attention and special treatment needed:

No relevant information available.

5 Fire-fighting measures

• Extinguishing media

• Suitable extinguishing agents: Foam

Carbon dioxide Fire-extinguishing powder

Water fog / haze

• For safety reasons unsuitable extinguishing agents: Water stream.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment as required.

• Environmental precautions Avoid release to the environment.

• Methods and material for containment and cleaning up

Towel or mop up material and collect in a suitable container.

For larger spills, add sawdust, chalk or other inert binding material, then sweep up and discard.

Reference to other sections

See Section 7 for information on safe handling.

- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: AC-20 +Silicone Black

(Cont'd. of page 2)

7 Handling and storage

[·] Handling

• Precautions for safe handling:

Open and handle receptacle with care.

Keep out of reach of children.

Avoid contact with the eyes and skin.

[•] Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

[•] Control parameters

· Control paran	neters
· Components w	vith limit values that require monitoring at the workplace:
1317-65-3 Lime	stone
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
1333-86-4 Carb	on black
PEL (USA)	Long-term value: 3.5 mg/m ³
REL (USA)	Long-term value: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m³ *inhalable fraction
EL (Canada)	Long-term value: 3 mg/m³ IARC 2B
EV (Canada)	Long-term value: 3.5 mg/m³
LMPE (Mexico)	Long-term value: 3* mg/m³ A3, *fracción inhalable
57-55-6 Propyle	ene glycol
WEEL (USA)	Long-term value: 10 mg/m ³
EV (Canada)	Long-term value: 155* 10** mg/m³, 50* ppm *vapour and aerosol;**aerosol only
14808-60-7 Qua	artz
PEL (USA)	Long-term value: 0.05* mg/m³ *resp. dust; 30mg/m3/%SiO2+2
REL (USA)	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A
TLV (USA)	Long-term value: 0.025* mg/m³
L	(Cont'd. on page 4)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

	(Cont'd. of p
	*as respirable fraction
EL (Canada)	Long-term value: 0.025 mg/m³ ACGIH A2; IARC 1
EV (Canada)	Long-term value: 0.10* mg/m³ *respirable fraction
LMPE (Mexico)	Long-term value: 0.025* mg/m³ A2, *fracción respirable
Avoid breathing	
Not required und Use suitable res A NIOSH appro Protection of h	
Not required und Use suitable res A NIOSH approv Protection of h Wear protective Gloves are advis	piratory protective device in case of insufficient ventilation. ved dust respirator should be used for operations generating dust.

9 Physica	and	chemical	properties
-----------	-----	----------	------------

Appearance: Form:	Paste	
Color:	Black	
	According to product specification	
Odor:	Mild	
	Acrylic	
Odor threshold:	Not determined.	
pH-value:	7.0-7.5	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
Flash point:	>140 °C (>284 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: AC-20 +Silicone Black

		(Cont'd. of page
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Non-oxidizing.	
Vapor pressure:	Not determined.	
Density:		
Relative density:	2.25	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
Solubility in / Miscibility with		
Water:	Not determined.	
Partition coefficient (n-octanol/wat	ter): Not determined.	
Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
VOC content:	<25 g/L	
Other information	No relevant information available.	

10 Stability and reactivity

• **Reactivity:** No relevant information available.

· Chemical stability: Stable under normal temperatures and pressures.

· Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

- Reacts with strong alkali.
- Reacts with strong oxidizing agents.
- Reacts with strong acids.
- Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers, strong bases, strong acids

[•] Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

11 Toxicological information

[·] Information on toxicological effects

• Acute toxicity: Based on available data, the classification criteria are not met.

- · LD/LC50 values that are relevant for classification: None.
- Primary irritant effect:
- On the skin: Based on available data, the classification criteria are not met.
- On the eye: Based on available data, the classification criteria are not met.

(Cont'd. on page 6)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: AC-20 +Silicone Black (Cont'd. of page 5) · Sensitization: Based on available data, the classification criteria are not met. · IARC (International Agency for Research on Cancer): Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied. 1333-86-4 Carbon black 2B 14808-60-7 Quartz 1 NTP (National Toxicology Program): 14808-60-7 Quartz **OSHA-Ca** (Occupational Safety & Health Administration): None of the ingredients are listed. · Probable route(s) of exposure: Ingestion. Eye contact. Skin contact. • Germ cell mutagenicity: Based on available data, the classification criteria are not met. · Carcinogenicity: Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

• Reproductive toxicity: Based on available data, the classification criteria are not met.

• **STOT-single exposure:** Based on available data, the classification criteria are not met.

· STOT-repeated exposure: Based on available data, the classification criteria are not met.

• Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

[·] Toxicity

· Aquatic toxicity No relevant information available.

· Persistence and degradability No relevant information available.

· Bioaccumulative potential: No relevant information available.

• Mobility in soil: No relevant information available.

· Other adverse effects No relevant information available.

13 Disposal considerations

[·] Waste treatment methods

· Recommendation:

Smaller quantities can be disposed of with household waste.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

[·] Uncleaned packagings

• **Recommendation:** Disposal must be made according to official regulations.



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: AC-20 +Silicone Black

(Cont'd. of page 6)

UN-Number		
DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
UN proper shipping name DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Transport hazard class(es)		
DOT, ADR/RID/ADN, IMDG, IATA		
Class	Not regulated.	
Packing group		
DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Environmental hazards		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	ll of	
MARPOL73/78 and the IBC Code	Not applicable.	

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture
 United States (USA)

·SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

• TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

Proposition 65 (California)

· Chemicals known to cause cancer:

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

12174-11-7 Attapulgite (Palygorskite)

14808-60-7 Quartz

1333-86-4 Carbon black

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

(Cont'd. on page 8)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 14, 2020

Trade name: AC-20 +Silicone Black

(Cont'd. of page 7)

1

2B

• Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

• EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

14808-60-7 Quartz

1333-86-4 Carbon black

Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent OSHA: Occupational Safety & Health Administration Flam. Liq. 3: Flammable liquids - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com