PHILLIPS MANUFACTURING CO.
Engineered to Perform

Submittal Form

1-1/2" Cold Rolled Channel

Cold Rolled Channels are used for furring walls, ceilings and laterally bracing studs. Also utilized for suspended ceiling and partition construction and as a stiffener for furring walls in metal framing. Features tightly formed corners and consistent equal height legs to facilitate ease of installation. Manufactured from hot-dipped galvanized, 16 gauge steel with .0538" minimum base material thickness. Also available 3/4".



3/4" or 1-1/2"

Drawing not to scale

Product Data and Ordering Information

Material: 16 gauge, prime or G40 galvanized coating
Part Number: 150U50

Length	Pieces Per Bundle	Bundles Per Pallet	Feet Per Bundle
10'	10	40	100
16'	10	40	160
20'	10	40	200

All Phillips products are made in the U.S.A.

ASTM and Code Standards

All Phillips cold rolled channels meet or exceed the following ASTM standards:

- ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard
- ASTM A653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process

SDS and other technical information available at www.phillipsmfg.com.

Leed Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.
MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content: 30%
Post-consumer recycled content: 25%
Pre-consumer recycled content: 5%

Storage

Avoid bending or other damage and store in a dry place protected from moisture.

Leed v4 for building and Design Construction

• MR Prerequisite: Construction and Demolition Waste Management Planning.
• MR Credit: Construction and Demolition Waste Management.
• MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials, Option2.
• MR Credit: Building Product Disclosure and Optimization Environmental Product Declaration, Options 1 & 2.
• MR Credit: Building Product Disclosure and Optimization Material Ingredients, Option 1.
• MR Credit: Building Life-Cycle Impact Reduction, Option 4