
SHAFTWALL/STAIRWELL & AREA SEPARATION WALL

TABBED J-TRACK

Phillips Tabbed J-Track is used with common shaftwall studs at floor and ceiling cavity shaftwalls, vertical chases and area separation walls. The tabs retain a 1" shaftliner. J-Track is manufactured with galvanized steel. Phillips Tabbed J-Track is available with either a 2-1/4" or 3" leg. 2-1/4" leg is available in both 25 and 20 gauge steel and 3" leg is available in 20 gauge steel. Phillips provides widths of 2-1/2" (250J), 4" (400J) and 6" (600J) to suit all needs (6" available in 20 gauge only). Packaging depends on your chosen length, width, leg size and gauge; ask your sales representative for more information.





PART NUMBER: 2HH-25HDG

HEMMED H-STUD

Phillips Hemmed H-Stud is a key framing component in area separation wall assemblies. This product features 2" wide vertical members which are inserted into the U-Track for framing solid partition separation walls. This product is manufactured to length for your convenience. Phillips Hemmed H-Stud follows nationally recognized evaluation service ICC ES, Inc. Legacy Report 90-26.01.



Drawing not to scale

U-TRACK

Phillips U-Track is used at the top and bottom of vertical panels to secure shaftliner panels and H-Studs in area separation wall assemblies. U-Track is fastened at the floor and ceiling to support the H-Studs. This product has a 2" width.







ASW CLIPS

Phillips ASW Clips are attached to the wood or steel framing at vertical steel framing stud/wood framing intersections. ASW Clips are 2" wide with 2" x 2-1/2" legs. Packaging is 500 pieces per carton.

SIZES AND PACKAGING			
Hemmed H-Stud			
Length	Pieces Per Bundle	Bundles Per Pallet	Feet Per Bundle
8'	10	55	80
10'	10	55	100
12'	10	55	120
U-Track			
10'	10	54	100

UPC labeling available upon request