

## 1-3/8" J-Weep

J-Weep is a versatile product used in several applications. Commonly used as a casing bead or plaster stop in stucco. The punched weep holes allow for usage as a sill weep screed in exterior stucco applications. Perforated flanges aid attachment and plaster keying and the 3-1/2" nailing flange meet applicable code requirements. (3/4" special order, minimum quantities may apply.)

### Product Data and Ordering Information

Material: .018 min thickness, galvanized steel  
Part Numbers: JW13HDG

Length	Pieces Per Carton	Cartons Per Pallet	Feet Per Carton
10'	10	50	100

All Phillips products are made in the U.S.A.

### ASTM and Code Standards

Phillips J-Weep meets or exceeds ASTM C 1063 Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster. SDS and other technical information available at [www.phillipsmfg.com](http://www.phillipsmfg.com).

### Leed Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

### Storage

Avoid bending or other damage and store in a dry place protected from moisture.



3/4", 3/8", 1/2", 7/8" or 1-3/8"

*Drawing not to scale*