# Submittal Form



# gripSTIK® Vinyl Drywall Beads and Trims

## **Product Benefits**

Phillips gripSTIK® Vinyl Drywall Beads and Trims are designed with ease of installation in mind. Phillips offers these top quality products to finish any room. Phillips gripSTIK® Vinyl Products feature many benefits:

- Specially textured flanges and bullnose face for paint and joint compound adhesion. No mud additives or priming needed.
- Knurled flanges to enhance joint compound adhesion.
- Durable and impact resistant products manufactured from PVC.
- Impervious to rust, corrosion, galvanic corrosion and electrolysis and are not affected by fast setting joint compounds or topping compounds.
- Dent resistant. Retains original shape.
- Tapered flanges for seamless finish work.
- Perforated flanges for excellent joint compound adhesion as the joint compound penetrates through the bead to the drywall to enhance long-lasting adhesion.
- Perforated flanges for faster drying.
- Ignition resistant as rigid vinyl is self extinguishing and will not continue to support combustion once flame source is removed, therefore, it will not cause a fire to re-start or spread.

## Certification

All Phillips gripSTIK<sup>®</sup> Vinyl Beads and Trims meet or exceed ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard, ASTM D3678-97 and ASTM D1784-03.

#### Limitations

Product is designed for interior use.

#### Storage

Avoid damage and store in a covered area away from direct sunlight.

#### **Paint Adhesion**

Cover with any type of paint. No priming is required.

#### **Installation Recommendations**

Phillips recommends installation in accordance with applicable ASTM standards and using prevalent industry standards. Phillips detailed installation recommendations are available at www.phillipsmfg.com.

#### Made in the U.S.A.

Phillips is proud that all gripSTIK® vinyl beads, trims and accessories are made in the United States of America.

Submittal Approvals:	
Job Name:	
Contractor:	Date:

The information and recommendations contained herein are, to the best of Phillips Manufacturing Company's knowledge and belief, accurate and reliable as of the date issued. Phillips Manufacturing Company has no control over the conditions of handling and use, and makes no warranty regarding the results obtained from the use of this data. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to determine that they are suitable and complete for its particular use. Phillips reserves the right to make alterations and amendments to the detailed specifications at its discretion. Phillips disclaims responsibility for all actions, proceedings, liabilities, claims, damages, cost, losses, and expenses in relation to, or arising out of, incorrect utilization of this information.



