


# 3.4 Self-Furring Dimpled Diamond Mesh Lath

Self-Furring Dimpled Diamond Mesh Lath is used extensively in stucco work as plaster reinforcement over masonry walls as well as in steel column fireproofing. It is also widely used as a reinforcement for base coat in ceramic tile work. Used over solid surfaces like concrete, cement board, column fireproofing, masonry and replastering over old surfaces. The self-furring dimples hold the metal lath 1/4" away from the surface to be plastered. The dimpled raised lath substrate provides a mechanical bond over solid surfaces and is easily shaped for curved or contoured surfaces. To maintain the designed furring characteristics, fasteners must be applied within the dimple cavity.



# **Product Data and Ordering Information**

Material: Hot-dipped galvanized

Part Number: 34SLHDG8

Std Wt./	Sheet	Pieces Per	Bundles	Sq. Yds.
Sq. Yd.	Size	Bundle	Per Pallet	Per Bundle
3.40	27" x 97"	10	25	20

All Phillips products are made in the U.S.A.

#### ASTM and Code Standards

Phillips Diamond Lath products meets or exceeds:

 ASTM A653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process.

SDS and other technical information available at www.phillipsmfg.com.

# **Leed Credits for Recycled Content**

MR2 - The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 - Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content: 30% Post-consumer recycled content: 25% Pre-consumer recycled content: 5%

### Storage

Avoid bending or other damage and store in a dry place protected from moisture.

#### Leed v4 for building and Design Construction

- MR Prerequisite: Construction and Demolition Waste Management Planning.
- MR Credit: Construction and Demolition Waste Management.
- MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials, Option2.
- MR Credit: Building Product Disclosure and Optimization Environmental Product Declaration, Options 1 & 2.
- MR Credit: Building Product Disclosure and Optimization Material Ingredients, Option 1.
- MR Credit: Building Life-Cycle Impact Reduction, Option 4



