




# 1-3/8" # 7 Foundation Weep Screed

#7 Foundation Weep Screed provides a stucco stop and screed for wood and masonry in exterior stucco applications. The 3-1/2" nailing flange serves as a straight-edge stop at the sill plate line and flashing when water-resistant paper or paper backed lath is installed over the flange at the sill plate line in exterior stucco applications. Punched weep holes enable keying as well as moisture weeping and perforated flanges aid attachment and plaster keying. (5/8", 3/4" and 1" special order, minimum quantities may apply.) The 1-3/8" Foundation Weep Screed is typically used with one inch foam on one coat plaster systems or in exterior insulation and finish systems.



## **Product Data and Ordering Information**


Material: 0.012 galvanized Part Number: WS13HDG

Γ	Length	Pieces Per	Cartons Per	Feet Per
		Carton	Pallet	Carton
Ī	10'	10	50	100

All Phillips products are made in the U.S.A.

### **ASTM and Code Standards**

Phillips #7 Foundation Weep Screed meets or exceeds ASTM C 1063 Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster. MSDS and other technical information available at www.phillipsmfg.com



## **Leed Credits for Recycled Content**

MR2 - The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content: 30%
Post-consumer recycled content: 25%
Pre-consumer recycled content: 5%

#### Storage

Avoid bending or other damage and store in a dry place protected from moisture.



