



1/2" # 7 Foundation Weep Screed

#7 Foundation Weep Screed provides a stucco stop and screed for wood and masonry in exterior stucco applications. The 3-1/2" nailing flange serves as a straight-edge stop at the sill plate line and flashing when water-resistant paper or paper backed lath is installed over the flange at the sill plate line in exterior stucco applications. Punched weep holes enable keying as well as moisture weeping and perforated flanges aid attachment and plaster keying. (5/8", 3/4" and 1" special order, minimum quantities may apply.) Also available in zinc.

Product Data and Ordering Information

Material: 0.018 galvanized steel or zinc

Part Number: WS5HDG

Length	Pieces Per	Cartons Per	Feet Per
	Carton	Pallet	Carton
10'	10	50	100


All Phillips products are made in the U.S.A.

ASTM and Code Standards

Phillips #7 Foundation Weep Screed meets or exceeds:

- ASTM C 1063 Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- Zinc: 99.95% pure special high grade zinc ASTM B69

SDS and other technical information available at www.phillipsmfg.com



1/2", 7/8" or 1-3/8" Drawing not to scale

Leed Credits for Recycled Content

MR2 - The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content: 30% Post-consumer recycled content: 25% Pre-consumer recycled content: 5%

Storage

Avoid bending or other damage and store in a dry place protected from moisture.



