



gripSTIK® 5/8" Vinyl L-Tear Strip

gripSTIK® 5/8" Vinyl L-Tear Strip provides a clean line at a variety of wallboard intersections. The tear-off strip provides a protective edge and a guide for drywall finishing knives. Once joint compound is applied, finished and painted, the tear-off strip is removed to form a clean, crisp edge. Won't rust and impact resistant. Easy to cut with shears, knife or fine-tooth hacksaw.



Product Data and Ordering Information

Material: Extruded rigid vinyl; contains no asbestos
Part Numbers: TS6VYL

Length	Pieces Per Carton	Cartons Per Pallet	Feet Per Carton
8'	50	48	400
9'	50	48	450
10'	50	48	500

All Phillips products are made in the U.S.A.

ASTM and Code Standards

Phillips gripSTIK® 5/8" Vinyl L-Tear Strip meets or exceeds the following ASTM Standards:

- ASTM C 1047 Standard Specification for Accessories for Gypsum Wallboard
- ASTM D 1784 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly (Vinyl Chloride) (CPVC) Compounds
- ASTM D 3678 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Interior-Profile Extrusions

SDS and other technical information available at www.phillipsmfg.com

Patents

U.S. Patents 6,295,776 and 6,691,476

Leed Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:


Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

Storage

Avoid damage and store in a covered area away from direct sunlight.

Leed v4 for building and Design Construction

- MR Prerequisite: Construction and Demolition Waste Management Planning.
- MR Credit: Construction and Demolition Waste Management.
- MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials, Option2.
- MR Credit: Building Product Disclosure and Optimization Environmental Product Declaration, Options 1 & 2.
- MR Credit: Building Product Disclosure and Optimization Material Ingredients, Option 1.
- MR Credit: Building Life-Cycle Impact Reduction, Option 4



Also available in 1/4", 3/8" and 1/2"

Drawing not to scale