

# Submittal Form



# gripSTIK® 1/2" Vinyl L-Trim

gripSTIK® 1/2" Vinyl L-Trim provides a sharp edge at door, window, ceiling and other terminations. The many perforations and raised shoulder enhance strong compound adhesion and provide a flush finish. No primer is required for this impact resistant trim. Easy to cut with shears, knife or fine-tooth hacksaw. Won't rust.

# **Product Data and Ordering Information**

NUFACTURING CO.

Material: Extruded rigid vinyl; contains no asbestos

Part Numbers: LT5VYL

| Length | Pieces Per | Cartons Per | Feet Per |
|--------|------------|-------------|----------|
|        | Carton     | Pallet      | Carton   |
| 8'     | 80         | 48          | 640      |
| 9'     | 80         | 48          | 720      |
| 10'    | 80         | 48          | 800      |

All Phillips products are made in the U.S.A.

#### **ASTM and Code Standards**

Phillips gripSTIK® 1/2" Vinyl L-Trim meets or exceeds the following ASTM Standards:

- ASTM C 1047 Standard Specification for Accessories for Gypsum Wallboard
- ASTM D 1784 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly (Vinyl Chloride) (CPVC) Compounds
- ASTM D 3678 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Interior-Profile Extrusions

SDS and other technical information available at www.phillipsmfg.com

#### **Patents**

U.S. Patents 6,295,776 and 6,691,476

## **Leed Credits for Recycled Content**


MR2 - The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content: 30%
Post-consumer recycled content: 25%
Pre-consumer recycled content: 5%

### Storage

Avoid damage and store in a covered area away from direct sunlight.





Also available in 3/8" and 5/8"

Drawing not to scale



