





# gripSTIK® 3/8" Bullnose Splay (Mini)

gripSTIK® 3/8" Bullnose Splay (Mini) was designed for accenting detail in niches, layers, outside corners, windows and other areas at open angles exceeding 120°. This easy-to-install corner support can be nailed, stapled or applied with spray adhesive. The specially knurled and perforated flanges allow excellent joint compound adhesion. No mud additives or priming are needed prior to painting. Phillips bead is dent resistant, won't rust and easy to cut with shears, knife or fine-tooth hacksaw.


# Phillips bead is dent resistant, won't rust and easy to cut with shears, knife or fine-tooth hacksaw. Product Data and Ordering Information Material: Extruded rigid vinyl; contains no asbestos


Part Number: MBSVYL

Dimensions:

Length	Pieces Per	Cartons Per	Feet Per
	Carton	Pallet	Carton
8"	35	50	280
9'	35	50	315
10'	35	50	350

1" leg x 1" leg, 3/8" radius





Drawing not to scale

Open Angle

#### **ASTM and Code Standards**

Phillips gripSTIK® 3/8" Bullnose Splay (Mini) meets or exceeds:

- ASTM C 1047 Standard Specification for Accessories for Gypsum Wallboard
- ASTM D 1784 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly (Vinyl Chloride) (CPVC) Compounds
- ASTM D 3678 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Interior-Profile Extrusions SDS and other technical information available at www.phillipsmfg.com

# **Patents**

U.S. Patents 6,295,776 and 6,691,476

### **Leed Credits for Recycled Content**

MR2 - The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content: 30% Post-consumer recycled content: 25% Pre-consumer recycled content: 5%

## **Storage**

Avoid damage and store in a covered area away from direct sunlight.



