

2" Z-Furring Channel

Z-Furring Channels are used to furr out interior masonry, poured concrete and other applications. This product supports insulation while providing a uniform plane for gypsum panel attachment. Available in 25, 22 and 20 gauge and in 1" and 1-1/2". Also, available without pre-punched holes upon request.

Product Data and Ordering Information

Material: 25, 22 or 20 gauge, G40 galvanized coating
Part Number: ZCH200

Length	Pieces Per Bundle	Bundles Per Pallet	Feet Per Bundle
20 Gauge			
10'	10	60	100
12'	10	60	120
22 and 25 Gauge			
10"	20	60	200
12'	20	60	240

All Phillips products are made in the U.S.A.

ASTM and Code Standards

All Phillips resilient channels meet or exceed the following ASTM standards:

- ASTM C 645 Standard Specification for Nonstructural Steel Framing Members
- ASTM A653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process

SDS and other technical information available at www.phillipsmfg.com.

Leed Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:


Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

ASTM and Code Standards

Phillips Z-Furring Channels meet or exceed ASTM C 645 Standard Specification for Nonstructural Steel Framing Members.

Storage

Avoid bending or other damage and store in a dry place protected from moisture.



Drawing not to scale