


**kwikSTIK® Paper-Faced Metal Tape-On Trim
5/8" P4 L-Trim (PL5)**


kwikSTIK® Paper-Faced 5/8" P4 L-Trim tape-on trim is ideal where wallboard abuts with suspended ceilings, plaster, masonry and concrete walls, as well as untrimmed door and window jambs. Features over 50% thicker steel than ASTM standard C1047 minimum requirement for a strong, durable inside corner. The rigid steel-reinforced corner is covered with a unique, high strength paper providing maximum strength and protection while preventing cracking caused by the movement or shrinkage of framing members. Install by pressing firmly into joint compound and removing excess compound with a drywall knife or clean rag. This product also available without a bead.



Product Data and Ordering Information

Material: .0.040 min thickness, minimum G40 galvanized
Part Numbers: PL514EGB

Length	Pieces Per Carton	Cartons Per Pallet	Feet Per Carton
8"	50	56	400
9'	50	56	450
10'	50	56	500



Drawing not to scale

All Phillips products are made in the U.S.A.

ASTM and Code Standards

Phillips kwikSTIK® Paper-Faced Tape-On Metal L-Trim meets or exceeds:

- ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard*
- ASTM A653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process

SDS and other technical information available at www.phillipsmfg.com

Patents

U.S. Patents 6,295,776; 6,539,680; 6,722,092 and 7,013,610

Leed Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

Storage

Avoid bending or other damage and store in a dry place protected from moisture.