
MINI BULLNOSE (PMB)

Phillips kwikSTIK® Paper-Faced Tape-On Metal Bullnose Corner Beads (mini) are used on 90° outside corners with any standard drywall thickness for smooth, rounded corners. The rigid steel-reinforced corner is covered with a unique, high strength paper providing maximum strength and protection while preventing cracking caused by the movement or shrinkage of framing members. This product utilizes thicker steel that meet ASTM standard C1047. Install by pressing firmly into joint compound and removing excess compound with a drywall knife or clean rag.







SLOK-N (PBN)


Phillips kwikSTIK® SLOK-N nail-on bullnose corner bead is designed for smooth, round outside corners where nailing or other mechanical fastening is desired. This metal corner bead is covered with our specially engineered paper providing superior mud and paint adhesion. SLOK-N features approximately 20% thicker steel than ASTM standard C1047 minimum requirement for a strong, durable corner.




SLOK-NXW (PEN)

Phillips kwikSTIK® SLOK-NXW nail-on bullnose extra wide corner bead is designed for smooth, round outside corners where nailing or other mechanical fastening is desired. This product provides wider flanges for easier nailing and maximum coverage. SLOK-NXW features approximately 20% thicker steel than ASTM standard C1047 minimum requirement for a strong, durable corner. This metal corner bead is covered with our specially engineered paper providing superior mud and paint adhesion.





SIZES AND PACKAGING					
PMB, PBN, PEN					
Length	Pieces Per Carton	Cartons Per Pallet	Feet Per Carton		
8'	50	56	400		
9'	50	56	450		
10'	50	56	500		





NAIL-ON PAPER FACED CORNER BEADS



SLOK-NOS (PAN)

Phillips kwikSTIK® SLOK-NOS nail-on bullnose splay corner bead provides a round, smooth corner to open angles exceeding 120° where nailing or other mechanical fastening is desired. This product features approximately 20% thicker steel than ASTM standard C1047 minimum requirement for a strong, durable corner. SLOK-NOS is covered with our specially engineered paper providing superior mud and paint adhesion.



NAIL-ON SQUARE BEAD (PNW)

Phillips kwikSTIK® nail-on square bead is used on 90° corners for a clean professional look. This metal corner bead is covered with our specially engineered paper providing superior paint and mud adhesion. Standard flange length is 1-1/4".








P2 (PIC)

Phillips kwikSTIK® P2 tape-on inside corner trim is designed to form a true inside (90°) corner. This product features approximately 20% thicker steel than ASTM standard C1047 minimum requirement for a strong, durable inside corner. P2 is tape-on meaning no fasteners or nails are needed for installation. Specially engineered paper provides superior mud and paint adhesion.



SIZES AND PACKAGING				
PAN, PNW, PIC				
Length	Pieces Per Carton	Cartons Per Pallet	Feet Per Carton	
8'	50	56	400	
9'	50	56	450	
10'	50	56	500	

UPC labeling available upon request