

# kwikSTIK<sup>®</sup> Paper-Faced Tape-On Metal Corner Bead No Bead P1 X EL NB (P1N)

kwikSTIK<sup>®</sup> Paper-Faced Tape-On Metal Corner Beads is used on 90° outside corners with any standard drywall thickness for straight, precise corners. The rigid steel-reinforced corner is covered with a unique, high strength paper providing maximum strength and protection while preventing cracking caused by the movement or shrinkage of framing members. Features over 50% thicker steel than ASTM C1047 minimum requirement and is installed by pressing firmly into joint compound and removing excess compound with a drywall knife or clean rag.

## **Product Data and Ordering Information**

Material:.0.014 min thickness, minimum G40 galvanizedPart Number:P1N14EGB

Length	Pieces Per Carton	Cartons Per Pallet	Feet Per Carton
8"	50	56	400
9'	50	56	450
10'	50	56	500

All Phillips products are made in the U.S.A.

#### **ASTM and Code Standards**

All Phillips kwikSTIK<sup>®</sup> Paper-Faced Tape-On Metal Corner Beads meet or exceed the following ASTM standards:

- ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard\*
- ASTM A653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process

SDS and other technical information available at www.phillipsmfg.com.

### Patents

U.S. Patents 6,295,776; 6,539,680; 6,722,092 and 7,013,610

### Leed Credits for Recycled Content

MR2 - The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.


MR4 - Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

#### Storage

Avoid bending or other damage and store in a dry place protected from moisture.





Drawing not to scale

